

PART NUMBER	LDD-C514RI	REV.	В
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
06.24.96	E.C.N. #10188 & #10113./		Α
04.22.98	E.C.N. #10BRDR. & REDRAWN.		В







TYP


635


 $I_f = 10 \text{mA}$

UNITS

TEST COND

MAX





DIGIT DETAIL

2TIMI I	ΟF	SAFE	OPERATION	AΤ	25°C	PFR	CHIE

ELECTRO-OPTICAL CHARACTERISTICS $T_A = 25^{\circ}C$


PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	- 1.2	mW/*C
OPERATING, STORAGE TEMP.	-40 TO +85	•c
SOLDERING TEMP.	+ 260	•c
2.0mm FROM BODY	3	SEC. MAX

* t<10µS

PARAMETER

PEAK WAVELENGTH

				14			(
				ا ا	OIG 1		
A	В	c	D	E	F	G	DP
16	15	3	2	1	18	17	4



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION UNCONTROLLED DOCUMENT



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538 WEB: WWW.LUMEX.COM

I 0.56" DUAL DIGIT, SEVEN SEGMENT DISPLAY, 635nm RED, GREY FONT/WHITE SEGMENTS, COMMOI															
--	--	--	--	--	--	--	--	--	--	--	--	--	--	--	--

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

COMPIDE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLDE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

SISION ONCONTROLLED DOCOMENT									
	DATE:	07.28.9	2	DRAWN BY:	DU				
1	PAGE:	1 OF	1	CHKD BY:	SS				
	SCALE:	N/A		APRVD BY:	JD				
	UNIT:	mm [INC	Ή]	(Pb) [В				
_			-						

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: LDD-C514RI