DATE	REVISIONS	REV
4-22-98	E.C.N. #10BRDR. & REDRAWN./	Α

DRAWING NUMBER

rev A


TEST COND


 $I_r = 100 \mu A$ 


 $I_f = 10 \text{ mA}$ 


Α

## 









NO PIN: 7, 8, & 15

DU

## 0.8" SINGLE DIGIT, SEVEN SEGMENT DISPLAY, 660nm RED, GREY FONT/WHITE SEGMENTS, COMMON ANODE.

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT* STEADY CURRENT POWER DISSIPATION DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP. 2.0mm FROM BODY	150 30 100 -1.2 -20 TO +85 +260	mA mA mW mW/*C *C *C 3 SEC. MAX

LIMITS OF SAFE OPERATION AT 25°C PER CHIP

ELECTRO-OPTICAL CHARACTERISTICS TA =25°C If =10 mA

MAX

2.3

**UNITS** 

nm

 $V_f$ 

٧r

μcd

TYP

660 (RED)

1.8

13,300

MILKY WHITE DIFFUSED

PARAMETER

PEAK WAVELENGTH

FORWARD VOLTAGE

REVERSE VOLTAGE

AXIAL INTENSITY

EMITTED COLOR: FONT COLOR:

SEGMENT COLOR:

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE
THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE
FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

LUMEX INCORPORATED

MIN

4.0

RED

GREY

290 E. HELLEN ROAD PALATINE, ILLINOIS 60067 (847) 359–2790

CONFIDENTIAL INFORMATION
EXCEPT AS SPECIFICALLY AUTHORIZED IN WHITING BY LLUMEX INCORPORATED.
EXCEPT AS SPECIFICALLY AUTHORIZED IN WHITING BY LLUMEX INCORPORATED. THE HOLDER OF
THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT
SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE: 1-17-97

SCALE: N/A

CONFIDENTIAL INFORMATION
STORY FROM PROVIDENTIAL AND SHALL PROTECT

CHK'D: APPD:

PAGE 1 OF 1 LDS—A816RI A

UNLESS OTHERWISE SPECIFIED TOLERANCE IS ±.25mm (±0.010")

<sup>\*</sup> t<10µS

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: LDS-A816RI