
PART NUMBER	LDS-C516RI	REV.	D			
DATE	E.C.N. NUMBER AND REVISION COMMENTS					
07.21.95	CORRECTED SEGMENT REPRESENTATION. E.C.N. #10225.					
10.04.96						
04.20.98	E.C.N. #10BRDR. & REDRAWN.		С			
09.06.11	E.C.N. #10BRDR. & REDRAWN.		D			

PIN 10	PIN 6
+ + + +	
+ + + + +	
PIN 1 —	PIN 5



ELECTRO-OPTICAL	CHARACTERISTIC	CS TA=25°C	$I_f = 20 \text{mA}$		
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		660		nm	
FORWARD VOLTAGE		1.8	2.3	$V_{f}$	
REVERSE VOLTAGE	5.0			$V_r$	I <sub>r</sub> =100uA
AXIAL INTENSITY		13300		mcd	I <sub>f</sub> =20mA
EMITTED COLOR:	RED				
FACE COLOR:	GRAY				
SEGMENT COLOR:	MILKY V	WHITE DIFFUS	ED		

UNITS


mΑ


STEADY CURRENT	30	mA
POWER DISSIPATION	100	mW
DERATE FROM 25°C	-1.2	mW/*C
OPERATING TEMP.	-20 TO +85	·c
STORAGE TEMP.	-20 TO +85	•c
SOLDERING TEMP.	+260	•c
2.0mm FROM BODY		3 SEC. MAX
* t<10uS		

PARAMETER

PEAK FORWARD CURRENT\*

LIMITS OF SAFE OPERATION AT 25°C PER CHIP





CHARACTER DETAIL

			3	i,8 COI	MMON	CATHOD	DE
A T	В	c T	D	E	F	G [	OP _
7	6	4	2	1	9	10	5

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=  $^{+0.00}_{-0.00}$  PRECISION MAX.=  $^{+0.00}_{-0.000}$  PRECISION  $^{+0.00}_{-0.000}$  MAX.=  $^{+0.00}_{-0.000}$  PRECISION  $^{+0.000}_{-0.000}$  PRECISION  $^{+0.000}_{-0.0$ UNCONTROLLED DOCUMENT



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538

0.56" SINGLE DIGIT SEVEN SEGMENT DISPLAY, 660nm RED, GREY FONT/WHITE SEGMENTS, COMMON CATHODE.

\*\*THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.\*\*

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

JN	0/10	UNINIULL	LD DOCOMENT		
	DATE:	09.06.11	DRAWN BY:	AB	
	PAGE:	1 OF 1	CHKD BY:	KF	
	SCALE:	NTS	APRVD BY:	JD	
	UNIT:	mm [INCH]	Po		

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: LDS-C516RI