



UNCONTROLLED DOCUMENT









PART NUMBER SSF-LXH555VGD-5V-4

 REV.
 E.C.N. NUMBER AND REVISION COMMENTS
 DATE

 A
 E.C.N. #10BRDR, & REDRAWN.
 1.26.01

 B
 E.C.N. #10760.
 6.17.01

REV.

В

ELECTRO-OPTICAL CH	aracteristics	TA=25°C	$V_f = 5$	iν	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		565		nm	
FORWARD VOLTAGE		5.0	7.0	۷f	
REVERSE VOLTAGE	5.0			٧r	Aىر001=1ا
AXIAL INTENSITY		8		mcd	$V_f = 5 V$
VIEWING ANGLE		60		2x theta	
EMITTED COLOR:	GREEN				
EPOXY LENS FINISH:	GREEN DIFFU	ISED			

LIMITS OF SAFE OPERATION AT 25°C PER LED

PARAMETER	MAX	UNITS	
PEAK FORWARD CURRENT*	150	mA	
STEADY CURRENT	12	mA	
POWER DISSIPATION	310	mW	
DERATE FROM 25°C	-1.2	mW/°C	
OPERATING, STORAGE TEMP.	- 40 TO + 85	' C	
SOLDERING TEMP.	+ 260	.C	
2.0mm FROM BODY		3 SEC. MAX	
* 1 41 DC	·	·-	

* t<10µS

NOTES:

- 1. SSH-LXH555 HOLDER, BLACK NYLON. (4)
- 2. SSL-LXA227GD-5V LED. (4)
- 3. SSH-LXH555-SQR.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.029), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MN==±0.000 *UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.029), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MN==±0.000 *UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.029), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MN==±0.000 **ONLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.029), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MN==±0.000 **ONLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.010), X.XX=±0.25 (±0.010), X.XX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.005). MN==±0.000 **ONLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION MN==±0.000 **ONLESS OTHERWISE SPECIFIED TOLE

REV. PART NUMBER

B SSF-LXH555VGD-5V-4

T-1.8mm QUAD VERTICAL INDICATOR,
GREEN DIFFUSED, 5 VOLT.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY DF
LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX
INC, THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION
CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR
IN PART FROM DISCUGSINE AND DISSEMINATION TO ALL THROU PARTIES.

RELIABILITY NOTE
OUR NAMY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT
SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.
PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 11.18.97
PAGE: 1 OF 1
CT SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSF-LXH555VGD-5V-4