



## UNCONTROLLED DOCUMENT











REV.

PART NUMBER

| ELECTRO-OPTICAL CHARACTERISTICS TA=25°C If= 20mA |              |     |              |          |                         |
|--|--------------|-----|--------------|----------|-------------------------|
| PARAMETER  | MIN          | TYP | MAX          | ZTINU    | TEST COND               |
| PEAK WAVELENGTH                                  |              | 700 |              | nm       |                         |
| FORWARD VOLTAGE                                  |              | 2.0 | 2 <i>.</i> 5 | ۷f       |                         |
| REVERSE VOLTAGE                                  | 5.0          |     |              | ٧r       | I <sub>r</sub> = 1 ΩΟμΑ |
| AXIAL INTENSITY                                  |              | 1.5 |              | mcd      | $I_f = 20 \text{mA}$    |
| VIEWING ANGLE                                    |              | 60  |              | 2x theta |                         |
| EMITTED COLOR:                                   | RED          |     |              |          |                         |
| EPOXY LENS FINISH:                               | red diffused |     |              |          |                         |
|  |              |     |              |          |                         |

## LIMITS OF SAFE OPERATION AT 25°C

| PARAMETER                | MAX          | UNITS      |
|--------------------------|--------------|------------|
| PEAK FORWARD CURRENT*    | 50           | mA         |
| STEADY CURRENT           | 20           | mA         |
| POWER DISSIPATION        | 105          | mW         |
| DERATE FROM 25°C         | -1.2         | mW/°C      |
| OPERATING, STORAGE TEMP. | - 40 TO + 85 | •c         |
| SOLDERING TEMP.          | + 260        | •c         |
| 2.0mm FROM BODY          |              | 3 SEC. MAX |

<sup>\*</sup> t<10µS

## NOTES:

- 1. SSL-LXA227HD, RED LED.
- 2. SSH-LXH555, BLACK NYLON HOLDER.

U/V C U/V / T ( ) LEAD SIZE=±0.05 (±0.020), X.XX=±0.5 (±0.020), X.XX=±0.5 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). NN=+DECIMAL PRECISION MAX.= +0.001 (±0.000). NN=+DECIMAL PRECISION MAX.= +0.001 (±0.0

PART NUMBER

SSF-LXH555VHD

T-1.8mm VERTICAL INDICATOR,
700nm RED LED, RED DIFFUSED LENS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX NO. EXCEPT AS SPECIFICALLY AUTHORIZED IN WIRTING BY LUMEX INC, THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROJECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THRO PARTIES.

RELABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT

SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.

PLEASE PAY ATTENTION TO YOUR SUDDEFINE PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067—6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 6.14.99
PAGE: 1 OF 1
ct SCALE: N/A

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSF-LXH555VHD