## UNCONTROLLED DOCUMENT

+ + +

PIN 6

PIN 10 -

part number LDS-A5204RI REV.

17.50 [0.689] 14.85 [0.585] Ο + + + 0.30 [0.012] -(2 PLS.) PIN 1 PIN 5 DIGIT DETAIL 10° -0.50 [0.020] 2.54 [0.100] G (5 PLS.) 13.20 [0.520] (4 PLS.) - 10.16 [0.400] /F D () DP 3,8 COMMON ANODE B ¥ C ¥ D ¥ Ē F ¥ G DP Z Z Z A [ ↓  $\downarrow$ 10 5 6 9 \*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XX

7.00 [0.276]

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C If=10mA					
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635 (RED)		nm	
FORWARD VOLTAGE		2.0	2.5	Vf	
REVERSE VOLTAGE	5.0			٧r	I <sub>г</sub> =100µА
AXIAL INTENSITY		3000		μcd	lf=10mA
EMITTED COLOR:	RED				
FACE COLOR:	GRAY				
SEGMENT COLOR:	MILKY	WHITE DIFFUSE	D		

LIMITS (	DF	SAFE	OPERATION	AT	25°C	PER	DIE
----------	----	------	-----------	----	------	-----	-----

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	100	mA
STEADY CURRENT	30	тA
POWER DISSIPATION	112	mW
DERATE FROM 25'C	0.33	mA/•C
OPERATING, STORAGE TEMP.	-25 TO +85	<b>°</b> C
SOLDERING TEMP.	+ 260	•C
2.0mm FROM BODY		3 SEC. MAX

\* 1/10 DUTY CYCLE. 0.1ms PULSE WIDTH.

CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES WHEN WORKING WITH THIS PART.

	UNCONTROLLED DOCUMENT
XXX=±0.127 (±0.005).	LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECISION
<u>)N</u>	290 E. HELEN ROAD

					-0.00	-0	DECIMAL PRECISION
REV.	part number LDS—A5204RI	CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR	We Teme Photone To Kine	PAL PHC US	) E. HELEN ATINE, IL 6 )NE: +1.847 WEB: www.lu	60067–6976 7.359.2790 umex.com	
	0.52" SINGLE DIGIT, SEVEN SEGMENT DISPLAY, 635nm RED, GRAY FACE, MILKY WHITE SEGMENTS, COMMON ANODE.	IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. <u>RELIABILITY NOTE</u> OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.	DRAWN BY:	CHECKED BY:	WEB: www.lu APPROVED		2.24.03 1 OF 1

4.00±0.50

[0.157±0.020]

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: LDS-A5204RI