UNCONTROLLED DOCUMENT

Ø9.00 [Ø0.354] -

Ø5.00 [Ø0.197]

PART	NUMBER
SSI-LXI	H387HGW

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
Α	E.C.N. #10BRDR. & REDRAWN.	8.2.01

ELECTRO-OPTICAL	CHARACTE

ERISTICS TA=25°C $I_f = 20 \text{mA}$


PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		700 (RED)		пm	_
		565 (GREEN	>	nm	
FORWARD VOLTAGE (R/G)		2.0/2.2	2.5/2.6	Vf	
REVERSE VOLTAGE	5.0			V_r	I _r =100µA
AXIAL INTENSITY (R/G)		4/10		mcd	If = 20mA
VIEWING ANGLE		120		2x theta	


EMITTED COLOR: RED/GREEN

EPOXY LENS FINISH: MILKY WHITE DIFFUSED



Ø7.20 [Ø0.283]





LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	COLORS	MAX	UNITS
PEAK FORWARD CURRENT*		150	mA
STEADY CURRENT		25	mA
POWER DISSIPATION	(R/G)	120/105	mW
DERATE FROM 25°C	. , ,	- 1.2	mW∕*C
OPERATING, STORAGE TEMP.		-40 TO +85	°Ċ
SOLDERING TEMP.		+ 260	°C
2.0mm FROM BODY			3 SEC. MAX

^{*} t<10µS

NOTES:

- 1. SSL-LX433HGW LED.
- 2. HOLDER: LXP-SSI-387BSH, LXP-SSI-387BZL.
- 3. PANEL HOLE CUT OUT: 5/16" DIAMETER.

REV.

PART NUMBER SSI-LXH387HGW

T-5 FRESNEL LENS PANEL MOUNT INDICATOR. BICOLOR 700nm RED/565nm GREEN LED, MILKY WHITE DIFFUSED LENS.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY:

APPROVED BY: DATE: 8.2.01 1 OF 1 PAGE: SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSI-LXH387HGW