


PART NUMBER	LDS-C516RI	REV.	D
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
07.21.95	CORRECTED SEGMENT REPRESENTATION.		А
10.04.96	E.C.N. #10225.		В
04.20.98	E.C.N. #10BRDR. & REDRAWN.		С
09.06.11	E.C.N. #10BRDR. & REDRAWN.		D






ELECTRO-OPTICAL CH/	ARACTERISTIC	S T _A =25℃	l _f =20mA		
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		660		nm	
FORWARD VOLTAGE		1.8	2.3	٧ _f	
REVERSE VOLTAGE	5.0			Vr	I _r =100uA
AXIAL INTENSITY		13300		mcd	l _f =20mA
EMITTED COLOR:	RED				
FACE COLOR:	GRAY				
SEGMENT COLOR:	MILKY V	HITE DIFFUSE	D		

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	100	mW
DERATE FROM 25°C	-1.2	mW/*C
OPERATING TEMP.	-20 TO +85	•C
STORAGE TEMP.	-20 TO +85	•C
SOLDERING TEMP.	+260	•C
2.0mm FROM BODY		3 SEC. M



CHARACTER DETAIL



3,8 Common cathode							
A 7					F	G Z Z 1	

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: $x=\pm 1$ (±0.039), $x.x=\pm 0.5$ (±0.020), $x.xx=\pm 0.25$ (±0.010), $x.xx=\pm 0.127$ (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN = $\frac{+DECIMAL}{-DCCIMAL}$ PRECISION MAX.= $\frac{+0.00}{-0.00}$

	290 E. HELEN ROAD	0.00 SINGLE DIGH SEVEN SEGMENT DISLEAT, OCONTIN RED, ORET FORTY WITHE SEGMENTS, COMMON CATTODE.	DATE:	09.06.11	DRAWN BY:	AB
	PALATINE, IL 60067-6976 PHONE: +1.847.359.2790	**THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.**	PAGE:	1 OF 1	CHKD BY:	KF
	FAX: +1.847.359.6538 WEB: WWW.LUMEX.COM	CONFIDENTIAL INFORMATION CONTINUENT IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL	SCALE:	NTS	APRVD BY:	JD
Creating LED and LCD Solutions Together™			UNIT: r	mm [INCH]	Ø	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: LDS-C516RI