




PART NUMBER	LDS-C816RI	REV.	Α
DATE	E.C.N. NUMBER AND REVISION COMMENTS		REV.
04.22.98	E.C.N. #10BRDR. & REDRAWN.		Α











NO PIN: 7, 8, & 15

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: $X=\pm 1$ (±0.039), $X.X=\pm 0.5$ (±0.020), $X.XX=\pm 0.25$ (±0.010), $X.XXX=\pm 0.127$ (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION | MAX. = +0.00 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.000 | +0.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 FAX: +1.847.359.6538 WEB: WWW.LUMEX.COM

THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.

COMPIDENTIAL INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLDE OF IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

ON UNCONTROLLED DOCUMENT						
DATE:	01.17.97	DRAWN BY:	JH			
PAGE:	1 OF 1	CHKD BY:	KY			
SCALE:	N/A	APRVD BY:	SS			
UNIT: mm [INCH]		(R) A				

ELECTRO	-OPTICAL CHARACTER	RISTICS T _A = 25°C	$I_f = 10 \text{mA}$		
PARAMET	ER MIN	I TYP	MAX	UNITS	TEST COND
PEAK WA	AVELENGTH	660		nm	
FORWARI	VOLTAGE	1.8	2.3	V f	
REVERSE	VOLTAGE 4.0			٧r	I _r =100μΑ
AXIAL IN	TENSITY	13,300		μcd	$I_f = 10mA$
EMITTED	COLOR: RED				
FACE CO	DLOR: GRAY				
SEGMENT	COLOR: MILKY	WHITE DIFFUSED			

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	100	mW
DERATE FROM 25°C	- 1.2	mW/*C
OPERATING, STORAGE TEMP.	-20 TO +85	•C
SOLDERING TEMP.	+ 260	•c
2.0mm FROM BODY	3	SEC. MAX
* +<10C		

* t<10µS

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: LDS-C816RI