

LDS-N512RI-RA





CHARACTER DETAIL


8.00° — 14.20 [0.559] Ø0.51 [Ø0.020] DP 1.27 [0.050] (6 PINS) (5 PLS.)

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C $I_f = 10 \text{mA}$ PARAMETER MIN TYP MAX UNITS TEST COND PEAK WAVELENGTH 565 nm FORWARD VOLTAGE 2.2 2.6 ٧f REVERSE VOLTAGE V_r $I_{r}=100\mu A$ 5.0 AXIAL INTENSITY $l_f = 10 mA$ 2250 ucd EMITTED COLOR: **GREEN** FACE COLOR: **GRAY** SEGMENT COLOR: MILKY WHITE DIFFUSED

LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	- 1.2	mW/°C
OPERATING, STORAGE TEMP.	-40 TO +85	,C
SOLDERING TEMP.	+ 260	.C
2.0mm FROM BODY		3 SEC. MAX

^{*} t<10µS



UNCONTROLLED

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX.= +0.00

REV.

PART NUMBER IDS-N512RI-RA

0.56" SEVEN SEGMENT SINGLE DIGIT DISPLAY,
565nm GREEN CHIPS, GRAY FACE WITH WHITE SEGMENTS,
COMMON CATHODE, RIGHT DECIMAL POINT.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



GB

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com

TW WEB: www.lumex.com.tw APPROVED BY: DATE: DRAWN BY: CHECKED BY:

10.9.03 PAGE: 1 OF 1 SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

LDS-N512RI-RA