UNCONTROLLED DOCUMENT

6.00 [0.236] - 3.2 [0.126] -	9.20 [0.362]
6.00 [0.236] + \$\ \phi 4.75 [\phi 0.187]	
	3.18 [0.125] ↓ △
2.54 [0.100]	5.5±1.0 © [0.217±0.039]

PART NUMBER SSF-LXH100LID

E.C.N. NUMBER AND REVISION COMMENTS DATE CHG'D LEAD LENGTH. 10.2.93 В UPDATED SPECS. 7.28.95 С E.C.N. #10301. 1.30.97 D E.C.N. #10BRDR. & REDRAWN IN 3D. 5.14.02

ELECTRO-OPTICAL CH	ARACTERIS	TICS TA=25	5 ' C	If=20mA	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635		nm	
FORWARD VOLTAGE		2.0	2.5	۷f	
REVERSE VOLTAGE	5.0			V_r	1r=100µA
AXIAL INTENSITY		40		mcd	$I_f = 20 \text{mA}$
	1.0			mcd	$I_f = 2mA$
VIEWING ANGLE		60		2x theta	
EMITTED COLOR:	RED				
EPOXY LENS FINISH:	RED DIFFUSED				

B LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	mW/°C
OPERATING, STORAGE TEMP.	- 40 TO +85	°C
SOLDERING TEMP.	+ 260	° C
2.0mm FROM BODY		3 SEC. MAX

^{*} t<10uS

NOTES:

- 1. SSL-LX507F3LID, RED LED.
- 2. SSH-LXH100. BLACK HOLDER.

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=+DECIMAL PRECISION MAX.=+0.00 -0

REV.

PART NUMBER SSF-LXH100LID

ANDDE

T-5mm (T-1 3/4) LED, RIGHT ANGLE FAULT INDICATOR, 635nm RED DIFFUSED LED, LOW CURRENT.

<u>CONFIDENTIAL INFORMATION</u>
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



ВC

1290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

CHECKED BY: APPROVED BY: DATE: 7.15.93 DRAWN BY:

PAGE: 1 OF 1 SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSF-LXH100LID-01