
UNCONTROLLED DOCUMENT

PART NUMBER SSA-LXB10GW-RA

ı	KEV.	ı
	R	

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
Α	E.C.N. #10BRDR, & REDRAWN,	5.12.99
В	F.C.N. #11148	5.22.07

	25.10 [0.988] —	 1
1.74 [0.069] (10 PLS.)	_	2.54 [0.100] (9 PLS.)
5.00 [0.197] COMMON ANODE PIN 1	A B C D E F G H 1.91 (0.075) (10 PLS.) 19.10 (0.752)	3.00 [0,118]




ELECTRO-OPTICAL CH	ARACTERIS	TICS TA=25	i'C I	f=20mA	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH	5	65 (GREEN	l)	nm	
FORWARD VOLTAGE		2.2	2.6	۷f	
REVERSE VOLTAGE	5.0			٧r	I _r =10DμA
axial intensity		В		mcd	If=20mA
VIEWING ANGLE		160		2x theta	
EMITTED COLOR:	GREEN				
EPOXY LENS FINISH:	MILKY WI	HITE DIFFUS	SED		
FACE COLOR:	GRAY				

LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mΑ
STEADY CURRENT	25	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	- 1.2	mW/°C
OPERATING, STORAGE TEMP.	- 40 TO +85	rc
SOLDERING TEMP.	+ 260	ሪ
2.0mm FROM BODY		3 SEC. MAX
* +/10uS		

* t<10µ5



UNCONTROLLED DOCL

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAU SIZE=±0.05 (±0.002), LEAU LENGTH=±0.75 (±0.030). MN= +DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.127 (±0.005). LEAU SIZE=±0.05 (±0.002), LEAU LENGTH=±0.75 (±0.0030). MN= +DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.127 (±0.005). LEAU SIZE=±0.05 (±0.002), LEAU LENGTH=±0.75 (±0.0030). MN= +DECINAL PRECISION ARE: X=±1 (±0.0030), XX=±0.5 (±0.000), XXX=±0.127 (±0.000), XXX=±0.000 (±0.000), XXX

REV. PART NUMBER SSA-LXB10GW-RA

10 ELEMENT ARRAY, 565nm GREEN CHIPS, GRAY FACE WITH MILKY WHITE DIFFUSED EPOXY, RIGHT ANGLE.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTINUED IN THIS DOCUMENT IS THE PROPERTY OF
LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX
INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 10,28.95 PAGE: 1 OF 1 SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSA-LXB10GW-RA