

## PART NUMBER SSA-LXH1025SUGD

REV.

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C  $I_f = 20 \text{mA}$ TYP TEST COND PARAMETER MAX UNITS PEAK WAVELENGTH 574 nm FORWARD VOLTAGE 2.2 2.6 ٧f REVERSE VOLTAGE 5.0  $V_r$ Ir=100µA AXIAL INTENSITY 50 mcd  $I_f = 20 \text{mA}$ VIEWING ANGLE 110 2x theta GREEN EMITTED COLOR:

LIMITS OF SAFE OPERATION AT 25°C PER DIE

EPOXY LENS FINISH: GREEN DIFFUSED

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	mW/°C
OPERATING, STORAGE TEMP.	-40  TO  +85	<b>°</b> C
SOLDERING TEMP.	+ 260	°C
2.0mm FROM BODY		3 SEC. MAX

\* t<10µS


## NOTES:

- 1. SSH-LXH1025 HOLDER. MATERIAL: BLACK NYLON, UL V94-0.
- 2. SSL-LX25583SUGD, LED. (10 PCS.)
- SORT LEDS FOR MATCHED INTENSITY.

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN=+DECIMAL PRECISION MAX.= +0.00 -DECIMAL PRECIS

CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

CHECKED BY: APPROVED BY: DATE: 5.15.03 DRAWN BY: PAGE: 1 OF 1 SCALE: N/A

2.5mm x 5mm 10 LED RECTANGULAR ARRAY,

574nm AllnGaP GREEN LEDS, GREEN DIFFUSED LENS.

PART NUMBER

SSA-LXH1025SUGD

REV.

IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSA-LXH1025SUGD