UNCONTROLLED DOCUMENT		SSB-L>	SB-LX1515SID		REV.	
15.00 [0.591] SQR. 8 7 6 5 13.40 [0.528] SQR. 13.40 [0.528] 13.50 [0.441] 11.20 [0.441] 11.20 [0.441] 11.20 [0.441] 12.55 [0.494]	PARAME PEAK W FORWAF REVERS AXIAL IN VIEWING EMITEC	AVELENGTH D VOLTAGE E VOLTAGE 5.0 ITENSITY	TYP MAX   636 2.0 2.5   650 120 120	nm V <sub>f</sub> V <sub>r</sub> I <sub>r</sub> =	<u>ST CONE</u> = 100μΑ = 20mA	
1 2 3 4 0.25 [0.010] (2 PLS.)	PARAME PEAK F	RWARD CURRENT*	MAX 150		UNITS	
0.50 [0.020] (4 PLS)	POWER DERATE OPERAT SOLDER	CURRENT DISSIPATION FROM 25°C NG, STORAGE TEMP. NG TEMP. FROM BODY S	30 170 - 1.2 -40 T0 +85 + 260 3		mA m₩ C C SEC. MA	
$\begin{bmatrix} 7.62 & [0.300] \\ 2 & 3 & 6 & 7 \\ \hline & & & & & \\ \hline & & & & & \\ \hline & & & &$						
NLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.05 (±0.002), LEAD LENGTH=±0.05 (±0.010), X.XX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.05 (±0.002), LEAD LENGTH=\pm0.05 (\pm0.002), LEAD LENGTH=\pm0.05 (±0.002), LE	±0.75 (±0.030). MIN= +DECIMAL PRECISION -0.00				' <u>MET</u>	
290 E. HELEN ROAD PALATINE, IL 60067–6976	PS, RED DIFFUSED.		ATE: 06.26.01	DRAWN BY:	C	
PHONE: +1.847.359.2790 "The specifications may change at any time without notice due to i			AGE: 1 OF 1	CHKD BY:	KF	
Creating LED and LCD Solutions Together <sup>™</sup> FAX: +1.847.359.6538 WEB: WWW.LUMEX.COM THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AN EXCEPT AS SPECIFICALLY AN EXCEPT AS SPECIFICALLY AND SHALL PROTECT SAME IN WHOLE OR IN	UTHORIZED IN WRITING BY LUMEX INC., THE HOLDER		CALE: N/A	APRVD BY:	SS	
	N PART FROM DISCLOSURE AND DISSEMINATION TO AL	L ITIRU PARTIES.	NIT: mm [INCH]	<b>N</b>		

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSB-LX1515SID