


## UNCONTROLLED DOCUMENT

## PART NUMBER SSB-LX2755SYD







| ELECTRO-OPTICAL CH | ARACTERIS | STICS TA=25°C | ;   | $I_f = 20mA$ |                       |
|--------------------|-----------|---------------|-----|--------------|-----------------------|
| PARAMETER          | MIN       | ΤΥP           | MAX | UNITS        | TEST COND             |
| PEAK WAVELENGTH    |           | 590           |     | nm           |                       |
| FORWARD VOLTAGE    |           | 2.0           | 2.5 | ٧f           |                       |
| REVERSE VOLTAGE    | 5.0       |               |     | ٧r           | I <sub>r</sub> =100μΑ |
| AXIAL INTENSITY    |           | 200           |     | mcd          | $I_f = 20 \text{mA}$  |
| VIEWING ANGLE      |           | 160           |     | 2x theta     |                       |
| EMITTED COLOR:     | YELLOW    |               |     |              |                       |
| EPOXY LENS FINISH: | YELLOW    | DIFFUSED      |     |              |                       |

## LIMITS OF SAFE OPERATION AT 25°C PER CHIP

| PARAMETER                | MAX         | UNITS      |  |
|--------------------------|-------------|------------|--|
| PEAK FORWARD CURRENT*    | 150         | mA         |  |
| STEADY CURRENT           | 30          | mA         |  |
| POWER DISSIPATION        | 105         | m₩         |  |
| DERATE FROM 25°C         | -1.2        | mW/°C      |  |
| OPERATING, STORAGE TEMP. | - 40 TO +85 | <b>'</b> Ċ |  |
| SOLDERING TEMP.          | + 260       | <b>'</b> C |  |
| 2.0mm FROM BODY          |             | 3 SEC. MAX |  |
| * 1.410 C                |             |            |  |

\* t<10µS

REV.

6.10 [0.240]

0.50 [0.020]

(4 PLS.)

PART NUMBER
SSB-LX2755SYD

→ 7.62 [0.300] →

1.02 [0.040]

2.54 [0.100]

(3 PLS.)

10mm x 10mm SQUARE 4 CHIP LIGHT BAR, 590nm SUPER YELLOW CHIPS, YELLOW DIFFUSED.

CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HERBIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THRO PARTIES.

RELABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT

SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.
PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
U\$ WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY:

CT

CHECKED BY:

APPROVED BY: C

Y: DATE: 6.22.01 PAGE: 1 OF 1 SCALE: N/A

REV.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSB-LX2755SYD