


SSB-LX500S0D







13.97 [0.550]
Ø0.45 [Ø0.018] _
(3 PLS.) 2.54 [0.100] (2 PLS.) 5.08 [0.200]
J 3.08 [U.200]



PIN #2 : NO PIN

PIN #5: NO CONNECTION

ELECTRO-OPTICAL CH	IARACTERIS	TICS TA=25	'C	$I_f = 20mA$	
PARAMETER	MIN	ΤΥP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		610		nm	
FORWARD VOLTAGE		2.0	2.5	v_f	
REVERSE VOLTAGE	5.0			V_r	I _r =100μΑ
AXIAL INTENSITY		75		mcd	$I_f = 20 \text{mA}$
VIEWING ANGLE		160		2x theta	
EMITTED COLOR:	ORANGE				
EPOXY LENS FINISH:	ORANGE	DIFFUSED			

LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	m₩
DERATE FROM 25°C	- 1.2	mW/°C
OPERATING, STORAGE TEMP.	- 40 TO +85	' C
SOLDERING TEMP.	+ 260	' C
2.0mm FROM BODY		3 SEC. MAX
· · · · · · · · · · · · · · · · · · ·		

* t<10µS

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.006). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.000). MN= +0.000 MA. = +

PART NUMBER

SSB-LX500S0D

7mm x 14mm 2 CHIP LIGHT BAR, 610nm SUPER ORANGE CHIPS, ORANGE DIFFUSED.

Confidential information

The information contained in this document is the property of Lumex No. Except as specifically authorazed in Writing by Lumex Cit., the holder of this document shall keep all information contained herein confidential and shall protect same in whole or in part from disclusive and dissembation to all third parties.

RELABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT

SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.

PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 6.21.01
PAGE: 1 OF 1
ct SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSB-LX500SOD