

PART NUMBER							
SSB-LX620SRW E							
REV.	E.C.N. NUMBER AND REVISION COMMENTS	D	ATE				
А	E.C.N. #10BRDR. & REDRAWN.	7.1	0.98				
В	E.C.N. #10BRDR. & REDRAWN.	4.2	8.00				
С	E.C.N. #10BRDR. & REDRAWN.	6.2	20.01				
D	E.C.N. #11148.	1.2	1.05				
Е	E.C.N. #11859.	05.0	02.13				

ELECTRO-OPTICAL CH	ARACTER	RISTICS TA=25°C		l f= 20mA	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		660		nm	
FORWARD VOLTAGE		1.8	2.3	Vf	
REVERSE VOLTAGE	4.0			Vr	Ir=100µA
AXIAL INTENSITY		70		mcd	$I_f = 20 mA$
VIEWING ANGLE		160		2x theta	
EMITTED COLOR:	RED				
EPOXY LENS FINISH:	MILKY	WHITE DIFFUSED			

LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	- 1.6	mW/*C
OPERATING, STORAGE TEMP.	- 40 TO + 85	•C
SOLDERING TEMP.	+ 260	•C
2.0mm FROM BODY		3 SEC. MAX
* +<10.0		



UNCONTROLLED DO

MAX.= +0.00 -DECIMAL PRECISION 290 E. HELEN ROAD CBA PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com Creating LED and LCD Solutions Together TW WEB: www.lumex.com.tw CHECKED BY: APPROVED BY: DATE: 4.28.00 OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PAGE: 1 OF 1 RED CHIPS, MILKY WHITE DIFFUSED, LEAD FREE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS. SCALE: СТ N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSB-LX620SRW