

REV. SSB-LX620SUGD В E.C.N. NUMBER AND REVISION COMMENTS DATE 1.21.05 05.02.13

ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^{\circ}C$ I f = 20mA						
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND	
PEAK WAVELENGTH		574		nm		
FORWARD VOLTAGE		2.2	2.6	Vf		
REVERSE VOLTAGE	5.0			۷r	µ_100µA	
AXIAL INTENSITY		65		mcd	$I_f = 20 mA$	
VIEWING ANGLE		160		2x theta		
EMITTED COLOR:	GREEN					
EPOXY LENS FINISH:	GREEN D	IFFUSED				

LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	MAX	UNITS	
PEAK FORWARD CURRENT*	150	mA	
STEADY CURRENT	25	mA	
POWER DISSIPATION	105	mW	
DERATE FROM 25°C	- 1.2	mW/*C	
OPERATING, STORAGE TEMP.	- 40 TO + 85	•C	
SOLDERING TEMP.	+ 260	•C	
2.0mm FROM BODY		3 SEC. MAX	
* +21005			

A

	· ·		, <i>,</i>	·	, -0.00	-DECIMAL PRECISION
RE	/. PART NUMBER	<u>CONFIDENTIAL INFORMATION</u> THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF) E. HELEN ROAD ATINE, IL 60067	
E	SSB-LX620SUGD	LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.		PHC US	HONE: +1.847.359.2790 JS WEB: www.lumex.com W WEB: www.lumex.com.tw	
	6mm x 20mm, 3 CHIP LIGHT BAR,	RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT	DRAWN BY:		APPROVED BY: [DATE: 3.25.04
574	nm SUPER ULTRA GREEN LED, GREEN DIFFUSED, LEAD FREE	SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.	СТ		I I I I	PAGE: 1 OF 1 SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSB-LX620SUGD