UNCONTROLLED DOCUMENT	_ 122	part number -LX25783HGW	rev. A
		ER AND REVISION COMMENTS	DATE 1.10.01
2.30 [0.091]			
7.00 [0.276]	ELECTRO-OPTICAL CHARACT PARAMETER PEAK WAVELENGTH FORWARD VOLTAGE (R/G)	MIN TYP MAX UNITS 700 (RED) nm 565 (GREEN) nm 2.0/2.2 2.5/2.6 Vf	TEST COND
1.00 [0.039]		5.0 Vr 3 mcd 60 2x theta /GREEN Y WHITE DIFFUSED	I _r =100µА If=20mA
RED ANDDE	LIMITS OF SAFE OPERATION PARAMETER PEAK FORWARD CURRENT* STEADY CURRENT POWER DISSIPATION DERATE FROM 25°C OPERATING, STORAGE TEMP. SOLDERING TEMP.	COLORS MAX 150 25 105 -1.2	UNITS mA mW mW/*C °C *C
0.50 [0.020] SQR. (2 PLS.) - 2.54 [0.100]	2.0mm FROM BODY * t<10µS		SEC. MAX
	9), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENG	WTROLLED DOCL ITH=±0.75 (±0.030). MIN= +DECIMAL PRECISION MAX. 290 E. HELEN ROAD	= +0.00 - decimal precision
REV. PART NUMBER A SSL-LX25783HGW	THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL REEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.	PALATINE, IL 60067-6 PHONE: +1.847.359.279 US WEB: www.lumex.cor TW WEB: www.lumex.cor	10 n
2.3mm x 8mm RECTANGULAR LED, BICOLOR RED/GREEN, MILKY WHITE DIFFUSED LENS.	RELIABILITY NOTE DRAWN BY: CHEC OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. DRAWN BY: CHEC PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS. CT CT CT CT	CKED BY: APPROVED BY: DATE PAGI SCAI	E: 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSL-LX25783HGW