
UNCONTROLLED DOCUMENT


PART NUMBER LDD-A4302RI


REV. В

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
Α	E.C.N. #10BRDR. & REDRAWN.	2-12-99
R	FCN #11148	4 26 07

PIN 18-	PIN 10	6.5
PIN 1-	+ + + + + + + + + + + + + + + + + + +	18,
I TIN T	I III /	








PARAMETER MIN TYP MAX UNITS TEST COND PEAK WAVELENGTH 565 (GREEN) nm FORWARD VOLTAGE 2.2 2.6 V _f REVERSE VOLTAGE 5.0 V _r I _r =1 00μA AXIAL INTENSITY 3900 μcd I _f =10mA					
FORWARD VOLTAGE 2.2 2.6 V_r REVERSE VOLTAGE 5.0 V_r I_r =100 μ A					
REVERSE VOLTAGE 5.0 V _r I _r =100µA					
1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1, 1					
AYIAI INTENSITY 3000 upd 14-10mA					
ANIAL INICIALITY 2500 pag 17-1011A					
EMITTED COLOR: GREEN					
FACE COLOR: GRAY					
SEGMENT COLOR: MILKY WHITE DIFFUSED					

LIMITS OF SAFE OPERATION AT 25°C PER CHIP

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	160	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	- 1.2	mW/°C
OPERATING, STORAGE TEMP.	- 40 TO +85	' C
SOLDERING TEMP.	+ 260	' C
2.0mm FROM BODY	3 SEC, MAX	

* t<10µS



UNCONTROLLED

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.0010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECINAL PRECISION MAX.= +0.00 (±0.002), XXX=±0.127 (±0.005).

REV.

PART NUMBER LDD-A4302RI

0.43" SEVEN SEGMENT, DUAL DIGIT DISPLAY, 565nm GREEN CHIPS, GRACE FACE WITH WHITE SEGMENTS, COMMON ANODE, RIGHT DECIMAL PLACES.

Confidential information

The information contained in this document is the property of Lumex No., except as specifically authorized in writing by Lumex inc., the holder of this document shall keep all information contained herein confidential and shall protect same in whole or IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

CHECKED BY: APPROVED BY: DRAWN BY: DATE: 4.6.98 PAGE: 1 OF 1 SCALE: N/A JC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

LDD-A4302RI