




UNCONTROLLED DOCUMENT

PART NUMBER
SSB-CEL8040UWWREV.
A

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
A	E.C.N. #11251.	6.6.05



*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030), MIN.=+0.00 DECIMAL PRECISION MAX.=+0.00 DECIMAL PRECISION

ELECTRO-OPTICAL CHARACTERISTICS $T_A=25^\circ\text{C}$ PER MODULE					$I_f=10\text{mA} \times 4$
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH				nm	
FORWARD VOLTAGE		3.5	3.8	V_f	
REVERSE VOLTAGE	5			V_r	$I_r=0.7\text{mA}$
LUMINOUS INTENSITY(*1)		140		cd/m ²	$I_f=10\text{mA} \times 4$
CHROMATICITY X		0.31			
COORDINATES(*2) Y		0.30			$I_f=10\text{mA} \times 4$
EMITTED COLOR:	WHITE				
REFLECTOR FINISH:	WHITE DIFFUSED				

*1. LUMINOUS INTENSITY TESTING CONDITION: 550nm WAVELENGTH.
*2. THE ICI STANDARD COLORIMETRIC SYSTEM.

LIMITS OF SAFE OPERATION AT 25°C PER MODULE

PARAMETER	MAX	UNITS
STEADY CURRENT	25 x 4	mA
POWER DISSIPATION	95 x 4	mW
OPERATING TEMP.	-25 TO +85	°C
STORAGE TEMP.	-25 TO +85	°C
SOLDERING TEMP.	+260	°C
2.0mm FROM BODY	3 SEC. MAX	

NOTES:

1. LIGHT GUIDE.
2. HOUSING REFLECTOR.
3. SSL-LX123544UWC (4 PCS.).
4. SHADING TAPE.
5. DOUBLE SIDED TAPE.

UNCONTROLLED DOCUMENT

REV.
APART NUMBER
SSB-CEL8040UWW

80mm x 40mm VIEW AREA, CUSTOM EDGE LIT LED BACKLIGHT,
WHITE LED, 4 CHIPS, 3.5V @ 10mA PER CHIP.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABILITY NOTE
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com
TW WEB: www.lumex.com.tw

DRAWN BY: JD	CHECKED BY:	APPROVED BY:	DATE: 9.13.04 PAGE: 1 OF 1 SCALE: N/A
-----------------	-------------	--------------	---

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

[SSB-CEL8040UWW](#)