UNCONTROLLED DOCUMENT

1.83 [0.072]

4.20 [0.165]

PART NUMBER SSI-LXMP059ID5V150 REV.

7.90 [0.311] 5.60 [0.220] (2)1.00 [0.039] n 3.00 [0.118] (3) 5.00 [0.197] EPOXY LENS FINISH: RED DIFFUSED 12.70 [0.500] LUMEX (4) (5) ' - <mark>-</mark> 0 1.00 [0.039] - 6.36 [0.250] 4.10 [0.161] 152.4+10.0 _____6.000+0.394_ _______6.000__ PANEL CUTOUT NOTES: 6.55 [0.258] 9.50 [0.374] 3. SSH-LXMP059-BSG2, BUSHING. 4.50 [0.177] CUT 155mm, STRIP 3mm & 9.5mm. 1.25~3.00 [0.049~0.118] *UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMAL PRECISION -0.00 CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF REV. PART NUMBER LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX А SSI-1 XMP059ID5V150 INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR Creating LED and LCD Solutions Together" IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES. RELIABILITY NOTE 635nm RED RECTANGULAR LED PANEL INDICATOR, CHECKED BY: APPROVED BY: DATE: DRAWN BY: OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. RED DIFFUSED LENS, 6" WIRE LEADS, 5 VOLTS. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS. JD BC

ELECTRO-OPTICAL CH	ARACTERISTICS	TA=25°C	V _f = 5	V	
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635		nm	
FORWARD VOLTAGE		5.0	7.0	Vf	
REVERSE VOLTAGE	5.0			Vr	lr=100µA
AXIAL INTENSITY		10		mcd	$V_{f} = 5 V$
VIEWING ANGLE		110		2x theta	
EMITTED COLOR:	RED				
EDOVY LENC EINICH.)			

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD VOLTAGE	7	V
STEADY CURRENT	12	mA
POWER DISSIPATION	310	mW
DERATE FROM 25°C	- 1.2	mW/°C
OPERATING, STORAGE TEMP.	-40 TO +85	°C

- 1. SSL-LX2573ID-5V, RED LED. TRIM LEADS TO 3~4mm LONG.
- 2. SSH-LXMP059-HSG, BLACK HOLDER.
- 4. ANODE LEAD: LXP-WST24RDTOC, RED INSULATED, 24 AWG.,
- CUT 155mm, STRIP 3mm & 9.5mm.
- 5. CATHODE LEAD: LXP-WST24BLTOC, BLACK INSULATED, 24 AWG.,
- 6. CRIMP OR SOLDER LEAD WIRES TO LED AND ASSEMBLE INTO HOUSING.

IINCONTROLLE MAX.= +0.00 -DECIMAL PRECISION

290 E. HELEN ROAD

PALATINE, IL 60067-6976

TW WEB: www.lumex.com.tw

8.7.01

1 OF 1

N/A

PAGE:

SCALE:

PHONE: +1.847.359.2790

US WEB: www.lumex.com

JD

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSI-LXMP059ID5V150