| UNCONTROLLED DOCUMENT | PART NUMBER RE |
|--|--|
| | SSL-LXA228SRC [|
| | REV. E.C.N. NUMBER AND REVISION COMMENTS DATE |
| | A E.C.N. #10541. 8.3.99 |
| | B E.C.N. #10743. 5.31.0 |
| | C E.C.N. #10784. 9.7.01 |
| | D E.C.N. #11148. 11.15.0 |
| 0.40 [0.016] | Define ELECTRO-OPTICAL CHARACTERISTICS TA=25°C If=20mA PARAMETER MIN TYP MAX UNITS TEST COND PEAK WAVELENGTH 660 nm FORWARD VOLTAGE 1.7 2.2 Vf FORWARD VOLTAGE 4.0 Vr Ir=100µA AXIAL INTENSITY 600 mcd If=20mA VIEWING ANGLE 25 2x theta EMITTED COLOR: RED EPOXY LENS FINISH: WATER CLEAR |
| | Imits of safe operation at 25°C |
| | PARAMETER MAX UNITS |
| 1.40 [0.055] — | PEAK FORWARD CURRENT* 160 mA |
| | STEADY CURRENT 25 mA POWER DISSIPATION 60 mW |
| | DERATE FROM 25°C -1.2 mW/°C |
| | OPERATING, STORAGE TEMP 40 TO + 85 °C |
| | SOLDERING TEMP. + 260 °C |
| | <u>2mm FROM BODY</u> <u>3 SEC. MAX</u> * t<10µS |
| 'UNLESS OTHERWISE SPECFIED TOLERANCES FER DECIMAL FRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.X | EX TOJIS EX TOJ |
| | DENTIAL INFORMATION 6 223 4 200 E. HELEN ROAD IRI |
| D SSL—LXA228SRC | 2) IN THE DOCUMENT IS THE PROPERTY OF COFFICALLY AUTHORIZED IN WIRTING BY LUNEX DOCUMENT SHALL KEEP ALL INFORMATION IAL AND SHALL PROTECT SAME IN WHOLE OR WE AND SHALL PROTECT SAME IN WHOLE OR IN THE DOCUMENT IS THE PROPERTY OF IN THE DOCUM |
| | AND DISSENTATION TO ALL THRO PARTIES. |
| T-2.5mm AXIAL LEADED LED, OUR NAMY YEARS OF ED | RENCE DATA ACCUMULATION INDICATE THAT CAUSE OF EARLY AND FUTURE FAILURE. PAGE: 1 OF 1 |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSL-LXA228SRC