UNCONTROLLED DOCUMENT			REV.
		SSL-LX55103IDFL-TR	R A
		REV. E.C.N. NUMBER AND REVISION COMMENTS	DATE
		A E.C.N. #11148	11.09.06
12.7±1.0 [0.500±0.039] 5.00 [0.197] 9.70 [0.382] 9.70 [0.382] 1 11.0 [0.433] 1 1 1 1 10 [0.433] 1 1 1 1 10 [0.433]	4° MAX. 4° MAX. 0.70 [0.028] MAX. (2 PLS.) 18.0 [0.709] 0.50 [0.020]	ELECTRO-OPTICAL GHARACTERISTICS $T_A=25^{\circ}C$ $I_f=20mA$ PARAMETER MIN TYP MAX UNITS PEAK WAVELENGTH 6355 nm FORWARD VOLTAGE 2.0 2.5 Vf REVERSE VOLTAGE 5.0 Vr AXIAL INTENSITY 15 mcd VIEWING ANGLE 110 2x theta EMITTED COLOR: RED EPOXY LENS FINISH: RED DIFFUSED LIMITS OF SAFE OPERATION AT 25'C PARAMETER MAX PEAK FORWARD CURRENT* 150 STEADY CURRENT 30 POWER DISSIPATION 105 DERATE FROM 25'C -1.2 OPERATING, STORAGE TEMP. -40 TO + 85 SOLDERING TEMP. +260	Ir = 100µA Ir = 100µA If = 20mA If = 20mA If = 20mA M M M M M C C C C SEC. MAX
TOP TAPE -/ CATHODE -/	SQR. (2 PLS.)	* t<10يرS	
		(UNCONTROLLED DOC	
"Unless otherwise specified tolerances per decimal precision are: $x=\pm 1$ (±0.039), X.	.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XXX=±0.127 (±0.005). Ц	L//V L/L/L/L/L/L/L/L/L/L/L/L/L/L/L/L/L/L	(_////_/V//_/V/ V.= -Decimal precision
A SSL-LX55103IDFL-TR	<u>confidential information</u> The information contained in this document is the property of MeX NG. Except as specifically authorized in writing by Lunex Inc., the holder of this document shall keep all information infaned herein confidential and shall protect same in whole or	290 E. HELLEN PALATINE, ILLINOI PHONE: (847) 3	ROAD IS 60067 59-2790
5mm SQUARE, 635nm RED LED, o	n part from disclosure and dissemination to all thro parties. <u>Reliability note</u> our nany years of experience data accumulation indicate that solder heat is a major cause of early and future failure. Please pay attention to your soldering process.	DRAWN BY: CHECKED BY: APPROVED BY: DAT PAC	E: 11.09.06

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSL-LX55103IDFL-TR