| UNCONTROLLED DOCUMENT | PART NUMBER REV SSL—LX507F3AD B REV. E.C.N. NUMBER AND REVISION COMMENTS DATE A E.C.N. #10BRDR. & REDRAWN IN 3D, 6.4.01 B E.C.N. #11148 11.01.06 |
|--|---|
| Ø4.75 [Ø0.187] + 7.20 [0.283] 1.00 [0.039] J MAX. | $\begin{array}{c c c c c c c c c c c c c c c c c c c $ |
| 26.40 [1.039] ANDDE A | LIMITS OF SAFE OPERATION AT 25°C PARAMETER MAX UNITS PEAK FORWARD CURRENT* 150 mA STEADY CURRENT 30 mA POWER DISSIPATION 105 mW DERATE FROM 25°C - 1.2 mW/°C OPERATING, STORAGE TEMP. - 40 TO + 85 °C SOLDERING TEMP. + 260 °C 2.0mm FROM BODY 3 SEC. MAX |
| *UNLESS OTHERWISE SPECIFIED TOLERANCES PER DEGINAL PRECISION ARE: X=±1 (±0.039), X,X=±0.5 (±0.020), X,XX=±0.25 (±0.010), X,XXX=±0.127 | |
| REV. PART NUMBER CONFIDENTIAL INFORMATION B SSL—LX507F3AD THE INFORMATION CONTINUES AS SPECIFICALLY AUTHORIZED IN WRITM INC, THE HOLDER OF THIS DOCUMENT IS THE PR UMEX NO. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITM INC, THE HOLDER OF THIS DOCUMENT IS ALL REP ALL IN CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME I IN PART FROM DESCLIGUIRE AND DES | RE BY LUNICK FORMATION IN WHOLE DR TO PARTIES. IN TO PARTIES. IN |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSL-LX507F3AD