

CTRO-OPTICAL CHARACTERISTICS TA=25°C If=20mA							
Ameter	MIN	TYP	MAX	UNITS	TEST COND	_	
K WAVELENGTH		525		nm			
WARD VOLTAGE		3.5	4.0	٧f			
'ERSE VOLTAGE	5.0			۷r	lr=100µA		
AL INTENSITY		150		mcd	lf=20mA		
NING ANGLE		120		2x theta			
TTED COLOR:	GREEN						
XY LENS FINISH:	WATER (LEAR					
TS OF SAFE OPERATION AT 25'C							
AMETER			MAX		UNITS		

REV.

DATE 4.2.01

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	130	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	-1.2	m₩/°C
OPERATING TEMP.	- 40 TO + 85	
STORAGE TEMP.	- 40 TO + 85	•C
* t<10uS		

CAUTION: STATIC SENSITIVE DEVICE Follow Proper E.S.D. Handling procedures WHEN WORKING WITH THIS PART. 1, 500 PIECES PER REEL. 2. THE CATHODE IS ORIENTED TOWARDS THE TAPE SPROCKET HOLE.

*UNLESS OTHERWISE SPECIFED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENSTH=±0.75 (±0.030), NN=+DECIMAL PRECISION MIX.=+0.00 290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw RIGHT ANGLE BOOMERANG SURFACE MOUNT LED, RELIABILITY NOTE DRAWN BY: CHECKED BY: APPROVED BY: 5.16.05 DATE: OUR MANY YEARS OF EXPERIENCE DATA ACCUNULATION INDICATE THAT PAGE: 1 OF 1 SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. 525nm ULTRA PURE GREEN LED, WATER CLEAR LENS, PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS. SCALE: JП N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SML-LXR44UPGC/9-TR