

SMI -H1505SIC

REV.

E.C.N. NUMBER AND REVISION COMMENTS DATE E.C.N. #11488. 04.10.08

PART NUMBER

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C $I_f = 20 \text{mA}$ **PARAMETER** MIN TYP MAX UNITS TEST COND 635 PEAK WAVELENGTH nm FORWARD VOLTAGE 2.0 2.5 ٧f REVERSE VOLTAGE 5.0 v_r Ir=100µA AXIAL INTENSITY 700 mcd $I_f = 20 \text{mA}$ 60 VIEWING ANGLE 2x theta **EMITTED COLOR:** RED EPOXY LENS FINISH: WATER CLEAR

LIMITS OF SAFE OPERATION AT 25°C PER DIE

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	100	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	90	mW
DERATE FROM 25°C	-1.2	mW/°C
OPERATING TEMP.	-30 TO +80	*C
STORAGE TEMP.	- 40 TO + 100	•C

*T<10µS

CONFIDENTIAL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 JS WEB: www.lumex.com

DRAWN BY:

CHECKED BY: APPROVED BY: DATE: 03.12.08 PAGE: 1 OF 1 SCALE: N/A

JN

SML-H1505SIC

PART NUMBER

5mm SURFACE MOUNTED DOME LED. 635nm SUPER INTENSITY RED. WATER CLEAR.

REV.

TW WEB: www.lumex.com.tw

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SML-H1505SIC