UNCONTROLLED DOCUMENT	PART NUMBER	LCD-	H2X1C50TR	REV.
0 VCOURCLED DOCUMENT	2.80 [0.110] MAX. 6.35 [0.250]	PIN NO. 1 SEGMENT 1BC PIN NO. 9 SEGMENT 2C CHARACTERISTICS FLUID TYPE: BACKGROUND COLOR: VIEWING DIRECTION: DISPLAY MODE: OPERATING VOLTAGE: OPERATING VOLTAGE: OPERATING METHOD: CONNECTION TYPE:	2 3 4 5 6 3F 3C 3E 3D 3C 10 11 12 13 14	7 8 3B 3A 15 16 2D COM
UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), X.X=±0.5 (±0.020), X.XX=±0.25 (±0.010), X.XX	x=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECIMA	L PRECISION MAX.= +0.00 -DECIMAL PREC		DOCUMENT
	• · · · · · · · · · · · · · · · · · · ·	16 PINS	DATE: 06.01.10 DRAN	WN BY: JH
200 E HELEN ROAD	" CHARACTER HEIGHT, 2 1/2 DIGIT LCD GLASS, TN, REFLECTIVE,	10 11113.		
290 E. HELEN ROAD 0.50 PALATINE, IL 60067-6976	"CHARACTER HEIGHT, 2 1/2 DIGIT LCD GLASS, TN, REFLECTIVE, "THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROV		PAGE: 1 OF 1 CHK	D BY: BC
290 E. HELEN ROAD 0.50 PALATINE, IL 60067-6976 PHONE: +1.847.359.2790		'EMENT.**	PAGE: 1 OF 1 CHK	D BY: BC VD BY: SA

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: LCD-H2X1C50TR