

REV.

SSF-LXH3250GGD

PATENT PENDING

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C If=20mA					
PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		565		nm	
FORWARD VOLTAGE		2.2	2,6	٧f	
REVERSE VOLTAGE	5.0			٧r	Ir=100μA
AXIAL INTENSITY		30		mcd	If=20mA
VIEWING ANGLE		60		2x theta	
EMITTED COLOR:	GREEN				
EPOXY LENS FINISH:	GREEN	DIFFUSED			

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	150	mA
STEADY CURRENT	25	mA
POWER DISSIPATION	105	mW
DERATE FROM 25°C	— 1.Б	mW/°C
OPERATING, STORAGE TEMP.	- 40 TO + 85	•c
SOLDERING TEMP.	+ 260	• C
2.0mm FROM BODY		3 SEC. MAX

NOTES:

- 1. SSH-LXH3250, BLACK HOLDER.
- 2. SSL-LX305F4GD, GREEN LED. (2 PCS.)

*UNLESS OTHERWISE SPECFED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0,039), XX=±0.5 (±0,020), XXX=±0.25 (±0,010), XXXX=±0.127 (±0,005). LEAD SIZE=±0.05 (±0,002), LEAD LENGTH=±0.75 (±0,030). MN=+DECIMAL PRECISION MAX.=+0.000

PART NUMBER REV. SSF-LXH3250GGD

DUAL T-3mm (T-1) SMT LED HOLDER WITH LOCATOR TAB, 565nm GREEN LED, GREEN DIFFUSED LENS.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUNEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

1.04 [0.041] (3 PLS)

2.40 [0.094]

RECOMMENDED SOLDER PAD LAYOUT

1.50 [0.059]

(4 PLS.)

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 U\$ WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY:

APPROVED BY:

DATE: 1.4.02 PAGE: 1 OF 1 SCALE: N/A

СТ

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSF-LXH3250GGD