UNCONTROLLED DOCUMENT	part number SSF—LXH1360SISUGW	REV.
4.60 [0.181] #2.90 [\$\vert\$0.114] 6.35 [0.250] 0.50 [0.020] RED ANDDE 0.50 [0.020] 0.50 [0.020] SQR. (2 PLS.) 3.60 [0.142] 3.60 [0.142] 3.60 [0.142] 1.80 [0.071] 1.80 [0.071] 1.00 [0.039] 1.00 [0.039] 1.00 [0.039] 1.00 [0.039] 3.60 [0.142]	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	)µA
$\begin{array}{c} \underline{\text{RECOMMENDED P.C.B. LAYOUT}}\\ \hline 2.54 \ \hline (0.100] & & & & & & \\ \hline & & & & & & \\ \hline & & & &$	LIMITS OF SAFE DPERATION AT 25°C PARAMETER COLORS MAX UNITS PEAK FORWARD CURRENT* 150 mA STEADY CURRENT (R/G) 30/25 mA POWER DISSIPATION 105 mW DERATE FROM 25°C -1.2 mW*C OPERATING, STORAGE TEMP40 TO +85 °C SOLDERING TEMP. +260 °C 2.0mm FROM BODY 3 SEC. MAX * t<10µS	X
*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). L   REV.   PART NUMBER   SF-LXH1360SISUGW   T-3mm (T-1) PCB INDICATOR WITH 2 LOCATOR PINS,   636nm RED/574nm GREEN, MILKY WHITE DIFFUSED LENS.	DRAWN BY: CHECKED BY: APPROVED BY: DATE: 01.3 PAGE: 1 C	

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSF-LXH1360SISUGW