

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: $x=\pm1$ (±0.039), $x.xx=\pm0.5$ (±0.020), $x.xx=\pm0.27$ (±0.005). LEAD SIZE=±0.05 (±0.022), LEAD LENGTH=±0.75 (±0.030). MIN= $\frac{-0.00}{-0.00}$ UNCONTROLLED DOCUMENT				
		DATE: 07.14.11	DRAWN BY:	AB
PALATINE, IL 600 PHONE: +1.847.3	**THE SPECIFICATIONS MAY CHANGE AT ANY TIME WITHOUT NOTICE DUE TO NEW MATERIALS OR PRODUCT IMPROVEMENT.** <u>CONTIDENTIAL</u> INCOMENTIAL INCOMENTIALI INTOMENTIALI INCOMENTIALI INCOMENTIALI INTOMENTIALI INTOMENTIALI INTOMENTIALI INCOMENTIALI INCOMENTIALI INTOMENTIALI INCOMENTIALI INTOMENTIALI INTOMENTIALI INCOMENTIALI INTOMENTIALI	PAGE: 1 OF 1	CHKD BY:	KF
FAX: +1.847.359.		SCALE: NTS	APRVD BY:	SS
Creating LED and LCD Solutions Together™ WEB: WWW.LUMEX.CO		UNIT: mm [INCH]	(Pb)	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSI-LXR1612YD-150B