SSL-LXS093SRSCC A RES FORMATION CLEED DOUGONALINA RES RES FORMATION CLEED FORMATION CLEED DOUGONALINA RES RES FORMATION CLEED FORMATION CLEED FORMATION CLEED FORMATION CLEED RES RES FORMATION CLEED FORMATION CLEED FORMATION CLEED FORMATION CLEED FORMATION CLEED RES RES FORMATION CLEED FORMATION CLEED FORMATION CLEED FORMATION CLEED FORMATION CLEED FORMATION CLEED RES FORMATION CLEED FO				
SSL - LX5093SRSCC A PS.50 (#0.222) + 500 (#0.1973)	UNCONTROLLED DOCUMENT	PART NUMBER	REV.	
REV PART NUMBER RED ISSN (2 PL3) Constrained restored re		SSL-LX5093SRSGC	A	
# EC.N. #10EROR. & REDRAMN N. 3D. 5.31.01 # EC.N. #10ER			JATF	
Control of the second seco				
RED GREEN ANDDE GREEN ANDDE GREEN ANDDE I.50 [0.059] 0.50 [0.020] I.50 [0.059] 0.50 [0.020] I.50 [0.00] SQR. (2 PLS.) 2.54 [0.100] UNLESS OHIGHNES SPECIAL PREDENT RE DECIMAL PREDENT ARE 1=11 (\$0.059] UNLESS OHIGHNES SPECIAL PREDENT RE DECIMAL PREDENT ARE 1=11 (\$0.059] UNLESS OHIGHNES SPECIAL PREDENT RE DECIMAL PREDENT ARE 1=11 (\$0.059] UNLESS OHIGHNES SPECIAL PREDENT	8.60 [0.339] 1.00 [0.039] MAX. 1.00 [0.039]	ELECTRO-OPTICAL CHARACTERISTICS TA=25°C If=20mA PARAMETER MIN TYP MAX UNITS TEST PEAK WAVELENGTH 660 (RED) nm 565 (GREEN) nm FORWARD VOLTAGE (R/G) 1.7/2.2 2.2/2.6 Vf REVERSE VOLTAGE (R/G) 4.0/5.0 Vr Ir=10 AXIAL INTENSITY (R/G) 350/200 mcd If=20n VIEWING ANGLE 30 Zx theto EMITTED GOLOR: RED/GREEN	<u>Cond</u>	
ANDRE ANDRE ANDRE ANDRE ANDRE MA UNIS ANDRE Intervention Intervention Intervention Intervention Intervention Intervention Intervention Intervention Intervention Intervention Intervention Intervention Intervention Intervention Intervention Intervention In				
POMER DISSIPATION (Ř/G) 100/105 mW DERATE RROW 25 G 0.50 [0.020] SOR (2 PLS) 2.54 [0.100] WILESS OHERWISE SPECIFIC TOLERWICES PER DECIMUL PRECEDING AKE: X=11 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXX=±0.25 (±0.002), LEAU SIZE=±0.26 (±0.002), LEAU EINGH=±0.75 (±0.003), WH = <u>100CUMEENT</u> WILESS OHERWISE SPECIFIC TOLERWICES PER DECIMUL PRECESION AKE: X=±1 (±0.039), XX=±0.25 (±0.010), XXX=±0.25 (±0.010), XXX=±0.25 (±0.010), XXX=±0.25 (±0.010), XXX=±0.25 (±0.002), LEAU SIZE=±0.26 (±0.002), LEAU EINGH=±0.75 (±0.003), WH = <u>100CUMEENT</u> WILESS OHERWISE SPECIFIC TOLERWICES PER DECIMUL PRECESION AKE: X=±1 (±0.039), XX=±0.55 (±0.020), XXX=±0.25 (±0.010), XXX=±0.25 (±0.002), LEAU SIZE=±0.05 (±0.002), LEAU EINGH=±0.75 (±0.003), WH = <u>100CUMEENT</u> WILESS OHERWISE SPECIFIC TOLERWICES PER DECIMUL PRECESION AKE: X=±1 (±0.039), XXX=±0.25 (±0.010), XXX=		PEAK FORWARD CURRENT* 150 mA		
Image: State of the state				
SULDERING TEMP. + 260 °C 2.0mm FROM BODY 3 SEC. MAX * t<10,JS SULDERING TEMP. + 260 °C 2.0mm FROM BODY 3 SEC. MAX * t<10,JS SULDERING TEMP. + 260 °C 2.0mm FROM BODY 3 SEC. MAX * t<10,JS SULDERING TEMP. + 260 °C 2.0mm FROM BODY 3 SEC. MAX * t<10,JS SULDERING TEMP. + 260 °C 2.0mm FROM BODY 3 SEC. MAX * t<10,JS SULDERING TEMP. + 260 °C 2.0mm FROM BODY 3 SEC. MAX * t<10,JS SULDERING TEMP. + 260 °C 2.0mm FROM BODY 3 SEC. MAX * t<10,JS SULDERING TEMP. + 260 °C 2.0mm FROM BODY 3 SEC. MAX * t<10,JS SULDERING TEMP. + 260 °C 2.0mm FROM BODY 8 SULDERING TEMP. + 260 °C SULDERING TEMP. + 260 °C 2.0mm FROM BODY 8 SULDERING TEMP. + 260 °C SULDERING TEMP. + 260 °C 2.0mm FROM BODY * t<10,JS SULDERING TEMP. + 260 °C 2.0mm FROM BODY * t<10,JS SULDERING TEMP. + 260 °C SULDERING TEMP. + 260 °C SULDER		DERATE FROM 25'G -1.2 mW/*C		
SQR, (2 PLS,) - 2.54 [0.100] * t<10,45 * t				
			X.	
"UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXX=±0.25 (±0.010), XXX=±0.127 (±0.030). LEAD SIZE=±0.05 (±0.020), LEAD LENGTH=±0.75 (±0.030). MN= ±000 - DECIMAL PRECISION REV. PART NUMBER A CONFIDENTIAL INFORMATION 290 E. HELEN ROAD 290 E. HELEN ROAD 290 E. HELEN ROAD CONFIDENTIAL INFORMATION THE INFORMATION CONTANED IN THIS DOCUMENT IS THE PROPERTY OF INVERTED IN WRITING BY LANER 290 E. HELEN ROAD PART NUMBER A CONFIDENTIAL INFORMATION CONFIDENTIAL INFORMATION CONTANED IN THIS DOCUMENT IS THE PROPERTY OF INVERTED IN WRITING BY LANER 290 E. HELEN ROAD PART NUMBER CONFIDENTIAL INFORMATION THE INFORMATION CONTANED IN THIS DOCUMENT IS THE PROPERTY OF INVERTED IN WRITING BY LANER 290 E. HELEN ROAD PART NUMBER A DOT OF STORE AND DET CONTANT ON THE INFORMATION CONTANED IN THIS DOCUMENT IS ALL PROTECT SAME IN WRITE BY LANER CONTAINED IN THE INFORMATION TO ALL THRO PARTIES. CONTAINED IN THE PROPERTY OF INVERTED IN WRITE BY LANER CONTAINED IN THE INFORMATION TO ALL THRO PARTIES. CONTAINED IN THE PROPERTY OF INVERTED IN WRITE BY LANER <th co<="" td=""><td></td><td>* t<10µS</td><td></td></th>	<td></td> <td>* t<10µS</td> <td></td>		* t<10µS	
A SSL-LX5093SRSGC T-5mm 660nm SUPER RED/565nm SUPER CREEN LED, WATER CLEAR LENS TO THE INFORMATION CONTAINED IN THIS DOCUMENT SHALL KEEP ALL INFORMATION THE INFORMATION CONTAINED IN THIS DOCUMENT SHALL KEEP ALL INFORMATION INC. THE INFORMATION CONTAINED IN THIS DOCUMENT SHALL KEEP ALL INFORMATION INC. THE INFORMATION CONTAINED IN THIS DOCUMENT SHALL KEEP ALL INFORMATION IN PART FROM DISCLISSING AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLISSING AND DISTUMENT OF ALL THRO PARTIES. TO SUDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. WATER CLEAR LENS TO FARE RED/565nm SUPER CREEN LED, WATER CLEAR LENS TO FARE RED/565nm SUPER CREEN LED, WATER CLEAR LENS TO FARE RED/565nm SUPER CREEN LED, THE INFORMATION CONTAINED IN THIS DOCUMENT SHALL KEEP ALL INFORMATION THE INFORMATION TO ALL THRO PARTIES. THE INFORMATION TO ALL THRO PARTIES. TO PARTIES. THE INFORMATION TO ALL THRO PARTIES. THE INFORMATION TO ALL TH		5). LEAJ SIZE= ± 0.05 (± 0.002), LEAJ LENGTH= ± 0.75 (± 0.030). MN= $\frac{+0.02}{-0.00}$ MAX.= $\frac{+0.02}{-0.000}$	NT . PRECISION	
A SSL-LX5093SRSGC T-5mm 660nm SUPER RED/565nm SUPER GREEN LED, WATER CLEAR LENS WATER LENS WATER CLEAR	THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY	DF PALATINE, IL 60067-6976	A	
T-5mm 660nm SUPER RED/565nm SUPER GREEN LED, WATER CLEAR LENS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SUDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. DRAWN BY: CHECKED BY: APPROVED BY: DATE: 8.23.95 PAGE: 1 OF 1	A SSL-LX5U935R5GC INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATIV CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOL	We have shown to Move for Way US WEB: www.lumex.com		
WATED CLEAD LENIS SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PAGE: 1 OF 1	T-5mm 660nm SUPER RED/565nm SUPER GREEN LED.	DRAWN BY: CHECKED BY: APPROVED BY: DATE: 8.3	3.95	
	DUR MANY YEARS DI EXPERIENCE DALA ACCUMULATION INDICATE DI SALAN SALAN DI ALTORIA DI ANTORIA DI	E PAGE: 1	OF 1	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex: SSL-LX5093SRSGC