

## UNCONTROLLED DOCUMENT

CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES WHEN WORKING WITH THIS PART.







REV.

REV.	E.C.N. NUMBER AND REVISION COMMENTS	DATE
Α	E.C.N. #10283.	12.11.96
В	E.C.N. #10BRDR, & REDRAWN IN 3D.	4.16.01

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C If=20mA							
PARAMETER	MIN	ΤΥP	MAX	UNITS	TEST COND		
PEAK WAVELENCTH		430		nm			
FORWARD VOLTAGE		4.5	5.5	$v_f$			
REVERSE VOLTAGE	5.0			$V_r$	Ir=100µА		
AXIAL INTENSITY		55		mcd	$I_f = 20 \text{mA}$		
VIEWING ANGLE		30		2x theta			
EMITTED COLΩR:	BLUE						
EPOXY LENS FINISH:	WATER	CLEAR					

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	100	mA
STEADY CURRENT	30	mA
POWER DISSIPATION	98	m₩
DERATE FROM 25°C	- 1.6	mW/°C
OPERATING, STORAGE TEMP.	- 40 TO + 85	<b>'</b> C
SOLDERING TEMP.	+ 260	<b>'</b> C
2.0mm FROM BODY		3 SEC. MAX
* 1×10.C		

\* t<10µS

UNCONTROLLED DOCUMENT

\*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.0010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MIN= +DECINAL PRECISION MAX.= +0.00 (±0.002), XXX=±0.5 (±0.000), XXXX=±0.127 (±0.005).

B SSL-LX3054SBC/A

T-3mm (T-1) 470nm SUPER BLUE LED, WATER CLEAR LENS.

Confidential information

The information contained in this document is the property of lumex ing. Except as specifically authorized in writing by lumex ing. The holder of this document shall keep all information contained herein confidential and shall protect same in whole or in part from disclusive and dissemination to all third parties.

RELABILITY NOTE

OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT

SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.

PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



BC

290 E. HELEN ROAD
PALATINE, IL 60067-6976
PHONE: +1.847.359.2790
US WEB: www.lumex.com

SCALE:

N/A

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 12.11.96
PAGE: 1 OF 1

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SSL-LX3054SBC/A