
UNCONTROLLED DOCUMENT


PART NUMBER
OED-ST3054C16

REV.

| REV. | E.C.N. NUMBER AND REVISION COMMENTS | DATE |
|------|-------------------------------------|---------|
| Α | E.C.N. #10BRDR, & REDRAWN IN 3D, | 5.30,03 |

Ø3.90 [Ø0.154] — Ø3.00 [Ø0.118]





Z COLLECTOR
EMITTER

ELECTRO-OPTICAL CHARACTERISTICS $I_A = 25^{\circ}C$

| PARAMETER | MIN | TYP | MAX | UNITS | TEST COND |
|------------------------|-------|-----|-----|-------|-------------------------------------|
| SPECTRAL SENSITIVITY | | 900 | | nm | _ |
| C/E BREAKDOWN VOLTAGE | 30 | | | ٧ | lc=100µA Ee= 0.0 mW/cm² |
| E/C BREAKDOWN VOLTAGE | 5.0 | | | ٧ | lc=100µA Ee= 0.0 mW/cm² |
| C/E SATURATION VOLTAGE | | | 0.5 | ٧ | lc= 2 mA Ee= 20 mW/cm² |
| COLLECTOR DARK CURRENT | | | 100 | пA | Vce=10V Ee= 0.0 mW/cm² |
| COLLECTOR ON CURRENT | | 13 | | mA | Vce= 5 V Ee= 1.0 mW/cm² |
| SWITCHING TIME | | 15 | | μS | lc=1mA Vce= 5 V,RI=100D Ω |
| EPOXY FINISH: WATER | CLEAR | | | | |

LIMITS OF SAFE OPERATION AT 25°C

| PARAMETER | MAX | UNITS |
|-----------------------|--------------|------------|
| C/E BREAKDOWN VOLTAGE | 30 | ٧ |
| E/C BREAKDOWN VOLTAGE | 5 | V |
| POWER DISSIPATION | 75 | mW |
| OPERATING TEMP. | - 20 TO + 70 | .c |
| STORAGE TEMP. | - 30 TO +80 | .c |
| SOLDERING TEMP. | + 260 | ' C |
| 2.0mm FROM BODY | | 3 SEC. MAX |

UNCONTROLLED DOCUMENT

*UNLESS OTHERWISE SPECIFIED TOLERANCES PER DECINAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.000), MIN= +0ECINAL PRECISION MAX.= +0.00 MAX

A OED-ST3054C16

Jmm PHOTO TRANSISTOR, WATER CLEAR LENS. CONFIDENTIAL INFORMATION

THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX NO. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISOLOGISURE AND DISSEMINATION TO ALL THIRD PARTIES.

RELIABLITY NOTE
OUR NAMY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT
SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE.
PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.



290 E. HELEN ROAD
PALATINE, IL 60067–6976
PHONE: +1.847.359.2790
US WFB: www.lumex.com

US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: CHECKED BY: APPROVED BY: DATE: 12.22.97
PAGE: 1 OF 1
BC SCALE: N/A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

OED-ST3054C16