UNCONTROLLED DOCUMENT CATHODE MARK [0,236] 1.80 [0.071] 6,00 7.00 [0.276] 1.60 [0.063] -11.00 [0.433] 0.85 [0.033] LEAD FREE REFLOW PROFILE 10 SEC. MAX. 255 0.10 [0.004] 0.15 [0.006] ඩ 90-120 SEC 160 EMPERATURE 150 ANODE ♦ CATHODE 24.00 [0.945] 21.00 [0.827] TIME TAPE FEED DIRECTION. TOTAL TIME ABOVE 220°C IS 60 SECONDS MAX. 4.00 [0.157] ─ 1.75 [0.069] 2,40 [0,094] 0,0 0 0 0 0 0 0 0000 ■ NOTE:

PART NUMBER SML-LX2723UPGC-TR

REV. E.C.N. NUMBER AND REVISION COMMENTS DATE 12.07,07 E.C.N. #11459.

REV.

ELECTRO-OPTICAL CHARACTERISTICS TA=25°C

PARAMETER	SYMBOL	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH			525		nm	
FORWARD VOLTAGE	v_f		3.2	4.0	٧	$I_f = 350 \text{mA}$
REVERSE VOLTAGE	٧ _٢	5			٧	lr=10µA
AXIAL INTENSITY	Ιv	33		60	lm	If=350mA
VIEWING ANGLE			120		2x theta	1, 556
EMITTED COLOR;	GREEN					
EPOXY LENS FINISH;	CLEAR					

LIMITS OF SAFE OPERATION AT 25°C

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	500	mA
STEADY CURRENT	350	mA
POWER DISSIPATION	2.0	W
DERATE FROM 25°C	-1.2	mW/°C
OPERATING, STORAGE TEMP.	- 40 TO + 85	°C
*T<10µS		

RECOMMENDED SOLDER PAD 14.40 [0.567] 3.00 [0.118] 4.00 [0.157] 3.00 [0.118] 4.00 [0.157]

*UNLESS OTHERWISE SPECFED TOLERANCES PER DECIMAL PRECISION ARE: X=±1 (±0.039), XX=±0.5 (±0.020), XXX=±0.25 (±0.010), XXXX=±0.127 (±0.005). LEAD SIZE=±0.05 (±0.002), LEAD LENGTH=±0.75 (±0.030). MN= +0.001 (±0.030), MNX.= +0.001 (±

12.00 [0.472]

290 E. HELEN ROAD PALATINE, IL 60067-6976 PHONE: +1.847.359.2790 US WEB: www.lumex.com TW WEB: www.lumex.com.tw

DRAWN BY: JN

CHECKED BY: I

APPROVED BY: 9.04.07 DATE:

PAGE: 1 OF 1 SCALE: N/A

PART NUMBER SML-LX2723UPGC-TR

7mm X 6mm SURFACE MOUNT HIGH POWER LED, 525nm ULTRA PURE GREEN , TAPE AND REEL.

REV.

CONFIDENTIAL INFORMATION
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUNEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

CAUTION: STATIC SENSITIVE DEVICE FOLLOW PROPER E.S.D. HANDLING PROCEDURES

WHEN WORKING WITH THIS PART

RELIABILITY NOTE OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT

250 PECES PER REEL

SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Lumex:

SML-LX2723UPGC-TR