1:2 Flux Coupled Transformer 5 - 200 MHz


Features

- Surface Mount
- 1:2 Impedance
- Excellent amplitude and phase Balance
- Available on Tape and Reel
- RoHS Compliant and Pb Free
- 260°C Reflow Compatible

Description

The MABACT0068 is a 1:2 RF Flux coupled balun transformer in a low cost surface mount package. Ideally suited for all CATV Broadband and FTTx applications. Suitable for use in 50 and 75 Ohm systems.

Functional Schematic



Pin Configuration

| Pin No. | Function | |
|---------|--------------------------|--|
| 1 | Secondary Dot (output 1) | |
| 2 | Centre Tap (ground) | |
| 3 | Secondary (output 2) | |
| 4 | Primary (ground) | |
| 5 | Primary Dot (input) | |

Electrical Specifications: Freq. = 5 - 200 MHz, T_A = 25°C, Z_0 = 75 Ω , P_{in} = 0 dBm

| Parameter | Conditions | Units | Min. | Тур. | Max. |
|-----------------------------------|----------------------------|-------|------|------------|------------|
| Impedance Ratio | — | | — | 1:2 | — |
| Insertion Loss | 5 - 65 MHz 65 - 200 MHz | dB | _ | 0.3 0.4 | 0.5 0.9 |
| Amplitude Balance | 5 - 65 MHz | dB | _ | 0.02 | ±0.15 |
| Phase Balance (ref value 180°) | 5 - 50 MHz | dB | _ | 0.0 | ±2.0 |
| Input Return Loss | 5 - 200 MHz | dB | 18 | 22 | _ |

Ordering Information¹

| Part Number | Description |
|-------------|-----------------|
| MABACT0068 | 2000 piece reel |

1. All sample boards include 5 loose parts.

Absolute Maximum Ratings

| Parameter | Absolute Maximum |
|-----------------------|------------------|
| Input RF Power | 250 mW |
| DC Current | 240 mA |
| Operating Temperature | -40°C to +85°C |

1



Rev. V1

MACOM Technology Solutions Inc. (MACOM) and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit <u>www.macom.com</u> for additional data sheets and product information.

1:2 Flux Coupled Transformer


5 - 200 MHz

Rev. V1


MACOM

Insertion Loss 1 (through pin 5 to pin 1) 0.0 -0.1 -0.2 -0.3 -0.4 æ B -0.5 -0.6 -0.7 -0.8 -0.9 -1.0 55 5 105 155 200 Frequency (M Hz)


Typical Performance Curves: $T_A = 25^{\circ}C$, $Z_0 = 75 \Omega$, $P_{IN} = 0 \text{ dBm}$




Amplitude Unbalance












Full temperature plots available on request


2

MACOM Technology Solutions Inc. (MACOM) and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit <u>www.macom.com</u> for additional data sheets and product information.


1:2 Flux Coupled Transformer 5 - 200 MHz

Part Outline Drawing






TOP VIEW




BOTTOM VJEW

- 1. Dimensions in mm
- 2. Tolerance: ±0.2 mm unless otherwise noted
- 3. Model number and lot code are printed on the reel
- 4. Plating finish: ENIG


PCB layout



Application Schematics



Carrier Tape Orientation



Tape & Reel Information

| Parameter | Units | Value | | |
|--|-------|-------|--|--|
| Qty per reel | - | 2000 | | |
| Reel Size | mm | 330 | | |
| Tape Width | mm | 12.00 | | |
| Pitch | mm | 8.00 | | |
| Orientation | - | F31 | | |
| Reference Application Note ANI-019 for orientation | | | | |

MACOM Technology Solutions Inc. (MACOM) and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit <u>www.macom.com</u> for additional data sheets and product information.

3

МЛСОМ

Rev. V1

1:2 Flux Coupled Transformer 5 - 200 MHz



Rev. V1

MACOM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with MACOM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppels or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.

⁴

MACOM Technology Solutions Inc. (MACOM) and its affiliates reserve the right to make changes to the product(s) or information contained herein without notice. Visit <u>www.macom.com</u> for additional data sheets and product information.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

MACOM: MABACT0068