


Avionics Pulsed Power Transistor 700W, 1030-1090 MHz, 32μs Pulse, 2% Duty

Rev. V1

Features

- NPN silicon microwave power transistors
- Common base configuration
- Broadband Class C operation
- High efficiency inter-digitized geometry
- Diffused emitter ballasting resistors
- Gold metallization system
- Internal input and output impedance matching
- Hermetic metal/ceramic package
- RoHS Compliant

Outline Drawing



Absolute Maximum Ratings at 25°C

| Parameter | Symbol | Rating | Units |
|---------------------------|-----------|-------------|-------|
| Collector-Emitter Voltage | V_{CES} | 80 | V |
| Emitter-Base Voltage | V_{EBO} | 3.0 | V |
| Collector Current (Peak) | I_C | 70 | A |
| Power Dissipation @ +25°C | P_{TOT} | 2.9 | kW |
| Storage Temperature | T_{STG} | -65 to +200 | °C |
| Junction Temperature | T_J | 200 | °C |

Electrical Specifications: $T_C = 25 \pm 5^\circ\text{C}$ (Room Ambient)

| Parameter | Test Conditions | Frequency | Symbol | Min | Max | Units |
|-------------------------------------|---|-----------------------------|--------------|-----|-------|-------|
| Collector-Emitter Breakdown Voltage | $I_C = 250\text{mA}$ | | BV_{CES} | 80 | - | V |
| Collector-Emitter Leakage Current | $V_{CE} = 50\text{V}$ | | I_{CES} | - | 25 | mA |
| Thermal Resistance | $V_{CC} = 50\text{V}$, $P_{out} = 700\text{W}$ | $F = 1030, 1090\text{ MHz}$ | $R_{TH(JC)}$ | - | 0.06 | °C/W |
| Input Power | $V_{CC} = 50\text{V}$, $P_{out} = 700\text{W}$ | $F = 1030, 1090\text{ MHz}$ | P_{IN} | - | 125 | W |
| Power Gain | $V_{CC} = 50\text{V}$, $P_{out} = 700\text{W}$ | $F = 1030, 1090\text{ MHz}$ | G_P | 7.5 | - | dB |
| Collector Efficiency | $V_{CC} = 50\text{V}$, $P_{out} = 700\text{W}$ | $F = 1030, 1090\text{ MHz}$ | η_C | 50 | - | % |
| Input Return Loss | $V_{CC} = 50\text{V}$, $P_{out} = 700\text{W}$ | $F = 1030, 1090\text{ MHz}$ | RL | - | -10 | dB |
| Load Mismatch Tolerance | $V_{CC} = 50\text{V}$, $P_{out} = 700\text{W}$ | $F = 1030, 1090\text{ MHz}$ | VSWR-T | - | 5:1 | - |
| Load Mismatch Stability | $V_{CC} = 50\text{V}$, $P_{out} = 700\text{W}$ | $F = 1030, 1090\text{ MHz}$ | VSWR-S | - | 1.5:1 | - |

Avionics Pulsed Power Transistor 700W, 1030-1090 MHz, 32μs Pulse, 2% Duty


Rev. V1

Typical RF Performance

| Freq. (MHz) | Pin (W) | Pout (W) | Gain (dB) | Ic (A) | Eff (%) | RL (dB) | VSWR-S (1.5:1) | VSWR-T (5:1) |
|-------------|---------|----------|-----------|--------|---------|---------|----------------|--------------|
| 1030 | 96 | 700 | 8.66 | 25.4 | 55.3 | -17.5 | S | P |
| 1090 | 101 | 700 | 8.42 | 25.7 | 54.5 | -16.7 | S | P |

RF Test Fixture Impedance


| F (MHz) | Z _{IF} (Ω) | Z _{OF} (Ω) |
|---------|---------------------|---------------------|
| 1030 | 1.1 - j1.4 | 1.2 - j0.8 |
| 1060 | 1.1 - j1.2 | 1.0 - j0.7 |
| 1090 | 1.0 - j1.0 | 0.8 - j0.7 |




Avionics Pulsed Power Transistor
700W, 1030-1090 MHz, 32 μ s Pulse, 2% Duty

Rev. V1

RF Power Transfer Curve 1030 MHz, Gain & Efficiency vs. Output Power




RF Power Transfer Curve 1090 MHz, Gain & Efficiency vs. Output Power




Avionics Pulsed Power Transistor

Rev. V1

Test Fixture Circuit Dimensions



Test Fixture Assembly



Avionics Pulsed Power Transistor 700W, 1030-1090 MHz, 32 μ s Pulse, 2% Duty

Rev. V1

M/A-COM Technology Solutions Inc. All rights reserved.

Information in this document is provided in connection with M/A-COM Technology Solutions Inc ("MACOM") products. These materials are provided by MACOM as a service to its customers and may be used for informational purposes only. Except as provided in MACOM's Terms and Conditions of Sale for such products or in any separate agreement related to this document, MACOM assumes no liability whatsoever. MACOM assumes no responsibility for errors or omissions in these materials. MACOM may make changes to specifications and product descriptions at any time, without notice. MACOM makes no commitment to update the information and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to its specifications and product descriptions. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document.

THESE MATERIALS ARE PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EITHER EXPRESS OR IMPLIED, RELATING TO SALE AND/OR USE OF MACOM PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, CONSEQUENTIAL OR INCIDENTAL DAMAGES, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. MACOM FURTHER DOES NOT WARRANT THE ACCURACY OR COMPLETENESS OF THE INFORMATION, TEXT, GRAPHICS OR OTHER ITEMS CONTAINED WITHIN THESE MATERIALS. MACOM SHALL NOT BE LIABLE FOR ANY SPECIAL, INDIRECT, INCIDENTAL, OR CONSEQUENTIAL DAMAGES, INCLUDING WITHOUT LIMITATION, LOST REVENUES OR LOST PROFITS, WHICH MAY RESULT FROM THE USE OF THESE MATERIALS.

MACOM products are not intended for use in medical, lifesaving or life sustaining applications. MACOM customers using or selling MACOM products for use in such applications do so at their own risk and agree to fully indemnify MACOM for any damages resulting from such improper use or sale.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[MACOM:](#)

[PH1090-700B](#)