
# TMC6100-EVAL Evaluation Kit

Document Revision V1.00 • 2019-Dec-20

The TMC6100-EVAL is designed for evaluating all features of the TMC6100. The evaluation board is part of TRINAMICs user-friendly plug-in system for chip evaluation. Just connect the TMC6100-EVAL with Landungsbruecke, the associated base board. Therefore, use the dedicated connector board, called Eselsbruecke. Eselsbruecke offers test points for every connector pin.



#### Applications

Robotics

• PMSM FOC drives

BLDC motors

- CNC Machines
- Industrial Drives
- LEV


### Features

- 3-phase BLDC/PMSM motor with up to 10A coil current
- Gate Drive Programmable 0.5A/1A/1.5A
- Supply Voltage 12...48V (55V max)
- SPI Interface for diagnostics / configuration
- Optional BBM logic for single line control
- Programmable Control Interface with 3 or 6 line drive
- Full Protection & programmable Diagnostics
- Onboard Current Shunt Amplifiers
  - Factory Automation

**MOTION CONTROL** 

- Blowers
- Pumps







## Contents

	Getting Started         1.1 First Start-Up	<b>3</b> 4
2	Hardware Information	5
	Revision History         3.1 Document Revision	<b>6</b> 6



### **1 Getting Started**

#### You need

- TMC6100-EVAL
- Landungsbruecke or Startrampe with latest firmware. We recommend the Landungs-bruecke as it offers faster USB communication.
- Latest TMCL-IDE (please download from www.trinamic.com) and PC
- 1x Eselsbruecke adapter board
- TMC4671-EVAL (Hardware FOC Controller)
- BLDC motor
- USB interface
- Power Supply
- · Cables for interface, motors and power

### Precautions

- Do not mix up connections or short-circuit pins.
- Avoid bounding I/O wires with motor wires.
- Do not exceed the maximum rated supply supply voltage!
- Do not connect or disconnect the motor while powered!
- Please check schematics for Jumper settings and input/output connector description.
- START WITH POWER SUPPLY OFF!




Figure 1: TMC6100-EVAL -Kit view



The Landungsbruecke operates on USB Power Supply. All other voltages are generated from +VM. Kit works only, when +VM is applied.



#### **1.1 First Start-Up**

- 1. Make sure that the latest version of the TMCL-IDE is installed. The TMCL-IDE can be downloaded from www.trinamic.com/support/software/tmcl-ide/.
- 2. Open the TMCL-IDE and connect the Landungsbruecke or Startrampe via USB to the computer. For Windows 8 and higher is no driver needed, on Windows 7 machines the TMCL-IDE is installing the driver automatically.
- 3. Verify that the Landungsbruecke or Startrampe is using the latest firmware version. The firmware version is shown in the connected device tree.

🚴 TMCL-IDE 3.0						
<u>File Tools Options Views Help</u>						
1						
Connected devices ×						
Device						
V 🕂 USB						
🗸 🏹 COM6: USB port						
🗸 🌰 ID1: Landungsbruecke [V 3.01]						
Uirect mode						

Figure 2: Firmware Version

4. The TMCL-IDE 3.0 needs room to show all important information and to provide a good overview. Therefore, arrange the main window related to your needs. We recommend using full screen. For evaluation boards it is essential to have access to the registers. Therefore open up the Register Browser (left side). For a better view click top right on the normal icon to get a maximized register browser window.

Board Assignment Settings	Board Assignment Settings
Automated board detection	Reset
Push scan for automated detection of connected boards. Please keep the evaluation board firmware up to date.	You can reset the board settings to defaults here. Form mos Trinamic chips it's a matter of firmware to restore defaults.
Scan	Please note that the default settings are not neccessarily the chip reset settings. The default
Scanning	O Motion controller board only
Manual board assignment	Power driver board only     Reset boards to defaul
Select connected boards manually. This is only recommended if automated detection fails somehow. Please keep the evaluation	Both
board firmware up to date. Choosing a wrong combination may lead to unexpected behaviour.	Driver Enable
board firmware up to date. Choosing a wrong combination	Driver Enable Please disable drivers before plug/unplug a motor t driver board. Otherwhise the driver may be damage     Enable drivers
board firmware up to date. Choosing a wrong combination may lead to unexpected behaviour. Motion controller Driver	Please disable drivers before plug/unplug a motor t driver board. Otherwhise the driver may be damage
board firmware up to date. Choosing a wrong combination may lead to unexpected behaviour. Motion controller none • Driver none •	Please disable drivers before plug/unplug a motor t driver board. Otherwhise the driver may be damage Enable drivers
board firmware up to date. Choosing a wrong combination may lead to unexpected behaviour. Motion controller Driver none a Diagnostics	Please disable drivers before plug/unplug a motor t driver board. Otherwhise the driver may be damage Enable drivers Diagnostics
bard firmware up to date. Choosing a wrong combination may lead to unexpected behaviour. Motion controller Driver none a Diagnostics Everything seems to be fine. Have Funl	Please disable drivers before plug/unplug a motor t driver board. Otherwhise the driver may be damage Enable drivers Diagnostics Everything seems to be fine. Have Funt
baard firmware up to date. Choosing a wrong combination may lead to unexpected behaviour.  Motion controller none	Please disable drivers before plug/unplug a motor t driver board. Otherwhise the driver may be damage Enable drivers Diagnostics Everything seems to be fine. Have Funt Information

Figure 3: Landungsbruecke Dialogue

©2019 TRINAMIC Motion Control GmbH & Co. KG, Hamburg, Germany Terms of delivery and rights to technical change reserved. Download newest version at www.trinamic.com



6. There is 1 solder option on the TMC6100-EVAL as highlighted in red in the image below. It allows for changing the VCCIO between 3.3V and 5V.Resistor R402 (0  $\Omega$ ) selects VCCIO = 3.3V and is assembled by default. R401 is not assembled in this case.If R401 (0  $\Omega$ ) is assembled instead of R402, then VCCIO = 5V.




Figure 4: Solder jumper on the TMC6100-EVAL

### 2 Hardware Information

All design files for our evaluation boards are available for free. The TMC6100-EVAL has been done with KiCAD. We offer the original ECAD files, Gerber data, the BOM, and PDF copies.

The files can be downloaded from the evaluation boards' website directly at <a href="https://www.trinamic.com/support/eval-kits/">https://www.trinamic.com/support/eval-kits/</a>.

Note

If files are missing on the website or something is wrong please send us a note.



## **3 Revision History**

### 3.1 Document Revision

Version	Date	Author	Description
1.00	2019-12-20	SK	Initial release.

Table 1: Document Revision

©2019 TRINAMIC Motion Control GmbH & Co. KG, Hamburg, Germany Terms of delivery and rights to technical change reserved. Download newest version at www.trinamic.com



# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Trinamic: TMC6100+TMC4671-EVAL-KIT TMC6100-EVAL