

#### **Features**

- Halogen Free. "Green" Device (Note 1)
- AEC-Q101 Qualified
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)
- For Surface Mount Application
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1

### **Maximum Ratings**

- Operating Junction Temperature Range: -55°C to +125°C
- Storage Temperature Range: -55°C to +150°C
- Maximum Thermal Resistance: 244°C/W Junction to Ambient(Note2)

MCC Part Number	Repetitive Peak Reverse Voltage V <sub>RRM</sub>	RMS Reverse Voltage V <sub>R(RMS)</sub>	DC Blocking Voltage V <sub>R</sub>
B0530WHE3	30V	21V	30V

## Electrical Characteristics @ 25°C Unless Otherwise Specifie


Average Forward Current	I <sub>F(AV)</sub>	0.5A	
Peak Forward Surge Current	I <sub>FSM</sub>	15A	@ t=8.3ms
Power Dissipation	P <sub>D</sub>	410mW	T <sub>A</sub> =25°C

Note: 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.


2. Part mounted on FR-4 board with recommended pad layout.

### **Internal Structure and Marking Code**






# 0.5 Amp Schottky Rectifier 30 Volts



DIMENSIONS					
DIM INCHES		MM		NOTE	
DIIVI	MIN N	MAX	MIN	MAX	NOTE
Α	0.140	0.152	3.55	3.85	
В	0.100	0.112	2.55	2.85	
С	0.055	0.071	1.40	1.80	
D		0.053		1.35	
Е	0.018	0.026	0.45	0.65	
G	0.006		0.15		
Н		0.010		0.25	
J		0.006		0.15	

#### Suggested Solder Pad Layout





# Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Conditions	Min.	Тур.	Max.	Units
Reverse Breakdown Voltage	$V_{BR}$	I <sub>R</sub> =100μA	30			V
Forward Voltage	V <sub>F1</sub>	I <sub>F</sub> =100mA			0.375	V
	$V_{F2}$	I <sub>F</sub> =500mA			0.55	V
Reverse Current	I <sub>R1</sub>	V <sub>R</sub> =15V			20	μA
	I <sub>R2</sub>	V <sub>R</sub> =30V			100	μΑ
Junction Capacitance	CJ	V <sub>R</sub> = 4V, f = 1MHz			50	pF
Reverse Recovery Time	t <sub>rr</sub>	$I_F = I_R = 10 \text{mA},$ $I_{rr} = 0.1 \times I_R, R_L = 100 \Omega$			30	ns





# **Curve Characteristics**


Fig. 1 - Typical Instantaneous Forward Characteristics 1000 Instantaneous Forward Current (mA) \_T<sub>A</sub>=100°C T<sub>A</sub>=7,5°C T<sub>A</sub>=25°C T<sub>A</sub>= -55°C 1 0.0

Instantaneous Forward Voltage (V)

0.2







0.6



# **Ordering Information**

Device	Packing		
Part Number-TP	Tape&Reel: 3Kpcs/Reel		

#### \*\*\*IMPORTANT NOTICE\*\*\*

**Micro Commercial Components Corp.** reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp**. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp**, and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp**, products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC):

B0530WHE3-TP BAS40-04HE3-13P