

#### **Features**

- Halogen Free Available Upon Request By Adding Suffix "-HF"
- · Glass Passivated Junction
- · Low Leakage Current And Fast Switching
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish/RoHS Compliant(Note 1)("P" Suffix Designates Compliant. See Ordering Information)

## **Maximum Ratings**

- Operating Junction Temperature Range: -55 °C to +150 °C
- Storage Temperature Range: -55 °C to +150 °C
- Typical Thermal Resistance: 60 °C/W Junction to Ambient
- Typical Thermal Resistance: 25 °C/W Junction to Lead

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
FR101GP	FR101GP	50V	35V	50V
FR102GP	FR102GP	100V	70V	100V
FR103GP	FR103GP	200V	140V	200V
FR104GP	FR104GP	400V	280V	400V
FR105GP	FR105GP	600V	420V	600V
FR106GP	FR106GP	800V	560V	800V
FR107GP	FR107GP	1000V	700V	1000V

#### Electrical Characteristics @ 25°C Unless Otherwise Specified


Average Forward Current	I <sub>F(AV)</sub>	1.0A	See Fig.1
Peak Forward Surge Current	I <sub>FSM</sub>	30A	8.3ms,Half Sine
Maximum Instantaneous Forward Voltage	$V_{F}$	1.30V	I <sub>FM</sub> =1.0A; T <sub>J</sub> =25°C*
Maximum DC Reverse Current At Rated DC Blocking Voltage	I <sub>R</sub>	5.0μA 100μA	T <sub>J</sub> =25°C; T <sub>J</sub> =100°C
Maximum Reverse Recovery Time FR101GP-104GP FR105GP FR106GP-107GP	t <sub>rr</sub>	150ns 250ns 500ns	I <sub>F</sub> =0.5A; I <sub>R</sub> =1.0A; Irr=0.25A
Typical Junction Capacitance	CJ	15pF	Measured at 1.0MHz V <sub>R</sub> =4.0V

<sup>\*</sup>Pulse Test: Pulse Width 300µsec, Duty Cycle 1%

Note: 1. High Temperature Solder Exemptions Applied, See EU Directive Annex 7a.

# 1.0 Amp Fast Recovery Rectifier 50 to 1000 Volts





DIMENSIONS					
DIM	INCHES		MM		NOTE
DIIVI	MIN	MAX	MIN	MAX	NOTE
Α	0.160	0.205	4.10	5.20	
В	0.080	0.107	2.00	2.70	Ф
С	0.028	0.035	0.71	0.90	Ф
D	1.000		25.40		



## **Curve Characteristics**




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge
Current

35

30

25

15

8.3 ms Single Half Sine-Wave


Fig. 4 - Typical Reverse Leakage Characteristics

10

Number of Cycles at 60 Hz

100

0





### **Ordering Information**

Device	Packing		
(Part Number)-TP	Tape&Reel: 5Kpcs/Reel		
(Part Number)-AP	Ammo Packing: 5Kpcs/Ammo Box		
(Part Number)-BP	Bulk:1Kpcs/Box,50Kpcs/Carton		

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

#### \*\*\*IMPORTANT NOTICE\*\*\*

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Micro Commercial Components Corp. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Micro Commercial Components Corp. and all the companies whose products are represented on our website, harmless against all damages. Micro Commercial Components Corp. products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

#### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

#### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC):

FR104GP-TP FR105GP-TP FR106GP-TP FR107GP-TP FR104GP-AP FR105GP-AP FR107GP-AP