

Features

- Halogen Free. "Green" Device (Note 1)
- High Current Capability and High Efficiency
- Lead Free Finish/RoHS Compliant(Note 2) ("P" Suffix Designates Compliant. See Ordering Information)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1

Maximum Ratings

• Operating Junction Temperature Range: -55°C to +150°C

• Storage Temperature Range: -55°C to +150°C

• Typical Thermal Resistance : 2 °C/W Junction to Case

MCC Part Number	Device Marking	Maximum Recurrent Peak Reverse Voltage	Maximum RMS Voltage	Maximum DC Blocking Voltage
MBRBL3045CT	MBRBL3045CT	45V	31.5V	45V


Electrical Characteristics @ 25°C Unless Otherwise Specified

Average Forward Current	I _{F(AV)}	30A	T _C =100°C
Peak Forward Surge Current	I _{FSM}	200A	8.3ms,half sine
Maximum Instantaneous Forward Voltage	V _F	0.53V 0.50V(Typ.)	I _{FM} =15A T _J =25°C
Maximum DC Reverse Current at Rated DC Blocking Voltage	I _R	0.2mA 50mA	T _J =25°C T _J =125°C


Note:

- 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
- 2. High temperature solder exemption applied, see EU directive annex 7a.

Internal Structure




30 Amp Schottky Barrier Rectifier 45 Volts



DIMENSIONS						
DIM	INCHES		MM		NOTE	
DIIVI	MIN	MAX	MIN	MAX	NOTE	
Α	0.331	0.370	8.40	9.40		
В	0.378	0.417	9.60	10.60		
С	0.165	0.189	4.20	4.80		
D	0.027	0.037	0.68	0.94		
E	0.045	0.055	1.14	1.40		
G	0.10		2.54		TYP.	
Н	0.096	0.134	2.43	3.40		
J	0.011	0.025	0.28	0.64		
K	0.071	0.131	1.80	3.32		
S	0.575	0.625	14.60	15.87		
V	0.042	0.058	1.07	1.47		
W	0.000	0.010	0.00	0.25		

Suggested Solder Pad Layout

Unit:mm





Curve Characteristics




Fig. 3 - Typical Instantaneous Forward Characteristics





Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current 225 200 Peak Forward Surge Current (A) 175 150 125 100 75 50 25 8.3 ms Single Half Sine-Wave 0 100 Number of Cycles at 60 Hz

Fig. 4 - Typical Reverse Leakage Characteristics





Ordering Information

Device	Packing		
Part Number-TP	Tape&Reel: 800pcs/Reel		
Part Number-BP	Tube: 5Kpcs/Ctn		

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. **Micro Commercial Components Corp**. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp**, and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp**, products are sold subject to the general terms and conditions of commercial sale, as published at

https://www.mccsemi.com/Home/TermsAndConditions.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Rev.3-5-08202023 3/3 MCCSEMI.COM

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC):

MBRBL3045CT-TP