


Features

- Internal Thermal Overload Protection
- Internal Short Circuit Current Limiting
- No External Components Required
- Moisture Sensitivity Level 1
- Epoxy Meets UL 94 V-0 Flammability Rating
- Halogen Free Available Upon Request By Adding Suffix "-HF"
- Lead Free Finish/RoHS Compliant ("P" Suffix designates RoHS Compliant. See ordering information)

Maximum Ratings

Parameter	Symbol	Value	Unit
Input Voltage (Vo=5.8V)	V ₁	30	V
Maximum Output Current	l _o	0.1	А
Operating Junction Temperature Range	T _{opr}	-20~120	°C
Storage Temperature Range	T _{STG}	-55~150	°C

Three-Terminal Low Current Positive Voltage Regulators





Electrical Characteristics

(V_i=10V, I_o=40mA, 0°C < T_j < 120 °C,C_i=0.33uF, C_o=0.1uF,Unless Otherwise Specified)

Parameter	Symbol	Test Conditions	Min	Тур	Max	Unit
Output Voltage		Tj=25°C	4.8	5.0	5.2	V
		7V≤V₁≤20V, I₀=1mA-40mA	4.7	-	5.25	V
	Vo		5.0			V
		7V≤V₁≤V _{MAX} I₀=1mA-700mA(Note1)	4.7		5.25	V
			5.0			V
Load Regulation	∆Vo	l₀=1mA-100mA,Tj=25°C	-	11	60	mV
		I₀=1mA-40mA, Tj=25°C	-	5.0	30	mV
Line Regulation	∆Vo	7V≤V₁≤20V,Tj=25°C	-	8	150	mV
		8V≤V₁≤20V,Tj=25°C	-	6	100	mV
Quiescent Current	lq		-	2.0	5.5	mA
Quiescent Current Change	$ riangle I_q$	8V≤V₁≤20V	-	-	1.5	mA
		1mA≤l₀≤40mA	-	-	0.1	mA
Output Noise Voltage	V _N	10Hz≤f≤100KHz	-	40	-	μV
Ripple Rejection	RR	8V≤V₁≤20V,f=120Hz,Tj=25°C	41	80	-	dB
Dropout Voltage	V _d	T _j =25°C	-	1.7	-	V


Note:

1.Bypass Capacitors are Recommended for Optimum Stability and Transient Response and should be Located as Close as Possible to The Regulators





Typcial Application



Curve Characteristics




Figure 1. Representative Schematic Diagram



Device	Packing
Part Number-TP	Tape&Reel:1Kpcs/Reel

Note : Adding "-HF" Suffix For Halogen Free, eg. Part Number-TP-HF

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources**. MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Micro Commercial Components (MCC): MC78L05F-TP-HF