

# DHS SERIES 1/2 PITCH SPST SURFACE MOUNT DIP SWITCHES

## FEATURES

Ultra-compact low-profile size.  
.050" (1.27mm) terminal spacing.  
Self-cleaning twin point contacts.  
Auto-insertable and reflow solderable.  
Process compatible with std'd. tape seal.

## GENERAL SPECIFICATIONS

### ELECTRICALS


Electrical life	1000 cycles minimum
Contact rating, non-switching	100 mA at 50 VDC
Contact rating, switching	100 mA at 6 VDC
Contact resistance	100 m $\Omega$ maximum
Insulation resistance	100 M $\Omega$ minimum
Dielectric strength	250 VDC for 1 min. between adjacent or opposite terminals
Capacitance	5 pf. max. between adjacent or opposite terminals

### MECHANICALS, THERMALS

Operating force	400 grams maximum
Vibration	10-55 Hz. per MIL-STD-202F, METHOD 201A
Shock	50 g (peak value) for 11 msec. per MIL-STD-202F, METHOD 213B
Operating temperature range	-40°C to +80°C

### SOLDERING & CLEANING RECOMMENDATIONS

Hand soldering	330°C max. for 3 seconds max. (30 watt iron max.)
Reflow soldering	Set oven at 215°C max. for 90 seconds max.
Cleaning (with standard tape seal in place)	1-1-1 Trichloroethane, Freon TE, Isopropyl alcohol or aqueous cleaner for 2 minutes max. at 20°C




## MATERIALS

Base	UL94V-O, glass fiber filled PPS, black
Cover	UL94V-O, glass fiber filled PPS, black
Actuators	UL94V-O, Polyamide, yellow
Contacts	Gold plated beryllium copper
Terminals	Gold plated copper alloy
Terminal seal	Epoxy
Tape seal	Polyimide

## PACKAGING


Supplied in tape & reel packaging.  
Reel & tape meets the requirements of EIA-481-A.



MODEL NUMBER	NO. OF POS.	A DIMENSION	
		IN( $\pm 0.012$ )	MM( $\pm 0.30$ )
DHS4C	4	.268	6.81
DHS6C	6	.368	9.35
DHS8C	8	.468	11.89
DHS10C	10	.568	14.43

Note: C at end of model no. indicates **C** style packaging. Substitute CR/TC for S for **CR/TC** packaging.

## MECHANICAL OUTLINE



P

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Apem:](#)

[DHS4S](#) [DHS8S](#) [DHS8SRTC](#) [DHS8CR](#) [DHS8CRTC](#) [DHS4C](#)