



**Three level inverter
Trench + Field Stop IGBT4
Power Module**

**$V_{CES} = 1200V$
 $I_C = 240A @ T_c = 80^\circ C$**


Application

- Solar converter
- Uninterruptible Power Supplies

Features

- Trench + Field Stop IGBT 4 Technology
 - Low voltage drop
 - Low leakage current
 - Low switching losses
 - Soft recovery parallel diodes
 - Low diode VF
 - RBSOA and SCSOA rated
- Kelvin emitter for easy drive
- Very low stray inductance
 - Symmetrical design
 - M5 power connectors
- High level of integration

Benefits

- Stable temperature behavior
- Very rugged
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Easy paralleling due to positive TC of VCEsat
- Low profile
- RoHS Compliant

Q1 to Q4 Absolute maximum ratings

Symbol	Parameter	Max ratings	Unit
V_{CES}	Collector - Emitter Breakdown Voltage	1200	V
I_C	Continuous Collector Current	$T_c = 25^\circ C$ 305 $T_c = 80^\circ C$ 240	A
I_{CM}	Pulsed Collector Current	$T_c = 25^\circ C$ 400	
V_{GE}	Gate - Emitter Voltage	± 20	V
P_D	Maximum Power Dissipation	$T_c = 25^\circ C$ 1000	W
RBSOA	Reverse Bias Safe Operating Area	$T_j = 150^\circ C$ 400A @ 1150V	

CAUTION: These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed. See application note APT0502 on www.microsemi.com

All ratings @ $T_j = 25^\circ\text{C}$ unless otherwise specified

Q1 to Q4 Electrical Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
I_{CES}	Zero Gate Voltage Collector Current	$V_{GE} = 0V$; $V_{CE} = 1200V$			2	mA
$V_{CE(sat)}$	Collector Emitter Saturation Voltage	$V_{GE} = 15V$ $I_C = 200A$	$T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$	1.8 2.2	2.2	V
$V_{GE(th)}$	Gate Threshold Voltage	$V_{GE} = V_{CE}$, $I_C = 5\text{ mA}$	5	5.8	6.5	V

Q1 to Q4 Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
C_{ies}	Input Capacitance	$V_{GE} = 0V$		12.3		nF
C_{oes}	Output Capacitance	$V_{CE} = 25V$		0.8		
C_{res}	Reverse Transfer Capacitance	$f = 1\text{MHz}$		0.69		
Q_G	Gate charge	$V_{GE} = \pm 15V$		1.7		μC
$T_{d(on)}$	Turn-on Delay Time	Inductive Switching (25°C) $V_{GE} = \pm 15V$ $V_{CE} = 600V$ $I_C = 200A$ $R_G = 3.6\Omega$		160		ns
T_r	Rise Time			30		
$T_{d(off)}$	Turn-off Delay Time			340		
T_f	Fall Time			80		
$T_{d(on)}$	Turn-on Delay Time	Inductive Switching (150°C) $V_{GE} = \pm 15V$ $V_{CE} = 600V$ $I_C = 200A$ $R_G = 3.6\Omega$		170		ns
T_r	Rise Time			40		
$T_{d(off)}$	Turn-off Delay Time			450		
T_f	Fall Time			170		
E_{on}	Turn-on Switching Energy	$V_{GE} = \pm 15V$ $V_{CE} = 600V$ $I_C = 200A$ $R_G = 3.6\Omega$	$T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$	10.4 21		mJ
E_{off}	Turn-off Switching Energy		$T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$	11 18.6		mJ
I_{SC}	Short circuit current	$V_{GE} \leq 15V$; $V_{CC} = 900V$ $t_p \leq 10\mu\text{s}$; $T_j = 150^\circ\text{C}$		1000		A
R_{thJC}	Junction to Case Thermal Resistance				0.15	$^\circ\text{C/W}$

CR1 to CR4 diode ratings and characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
V_{RRM}	Maximum Peak Repetitive Reverse Voltage		1200			V
I_{RM}	Maximum Reverse Leakage Current	$V_R = 1200V$	$T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$		150 400	μA
I_F	DC Forward Current		$T_c = 80^\circ\text{C}$	180		A
V_F	Diode Forward Voltage	$I_F = 150A$ $V_{GE} = 0V$	$T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$	1.7 1.65	2.2	V
t_{rr}	Reverse Recovery Time	$I_F = 150A$ $V_R = 600V$ $di/dt = 3800A/\mu\text{s}$	$T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$	155 300		ns
Q_{rr}	Reverse Recovery Charge		$T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$	14.6 30.4		
E_{rr}	Reverse Recovery Energy		$T_j = 25^\circ\text{C}$ $T_j = 150^\circ\text{C}$	5.2 11		mJ
R_{thJC}	Junction to Case Thermal Resistance				0.32	$^\circ\text{C/W}$

CR5 & CR6 diode ratings and characteristics

<i>Symbol</i>	<i>Characteristic</i>	<i>Test Conditions</i>		<i>Min</i>	<i>Typ</i>	<i>Max</i>	<i>Unit</i>
V _{RRM}	Maximum Peak Repetitive Reverse Voltage			1200			V
I _{RM}	Maximum Reverse Leakage Current	V _R =1200V	T _j = 25°C T _j = 150°C			150 400	μA
I _F	DC Forward Current		T _c = 80°C		240		A
V _F	Diode Forward Voltage	I _F = 200A V _{GE} = 0V	T _j = 25°C T _j = 150°C		1.9 1.85	2.4	V
t _{rr}	Reverse Recovery Time	I _F = 200A V _R = 600V di/dt = 4000A/μs	T _j = 25°C T _j = 150°C		155 300		ns
Q _{rr}	Reverse Recovery Charge		T _j = 25°C T _j = 150°C		18.6 39		μC
E _{rr}	Reverse Recovery Energy		T _j = 25°C T _j = 150°C		8.2 16		mJ
R _{thJC}	Junction to Case Thermal Resistance					0.25	°C/W

Thermal and package characteristics

<i>Symbol</i>	<i>Characteristic</i>	<i>Test Conditions</i>		<i>Min</i>	<i>Typ</i>	<i>Max</i>	<i>Unit</i>
V _{ISOL}	RMS Isolation Voltage, any terminal to case t = 1 min, 50/60Hz			4000			V
T _J	Operating junction temperature range			-40		175	°C
T _{STG}	Storage Temperature Range			-40		125	
T _C	Operating Case Temperature			-40		100	
Torque	Mounting torque	To heatsink	M6	3		5	N.m
		For terminals	M5	2		3.5	
Wt	Package Weight					300	g

Technical drawing of the 'Weighty Extreme' (4000 series) showing top, side, and front views with dimensions.

Top View Dimensions:

- Overall width: 108 ± 1
- Overall height: 22 ± 0.5
- Internal width: 93 ± 0.25
- Internal height: 48 ± 0.25
- Corner radius: $R6.50$
- Mounting hole diameter: $\varnothing 12 \pm 0.10$ (4x)
- Internal hole diameter: $\varnothing 6.40 \pm 0.10$ (4x)
- Internal hole diameter: $\varnothing 12 \pm 0.10$ (4x)
- Internal hole diameter: $\varnothing 14$
- Internal hole diameter: $\varnothing 12$
- Internal hole diameter: $M5$ (4x)
- Internal hole diameter: 7.8 MAX
- Internal hole diameter: 18.20 ± 0.50
- Internal hole diameter: 13.50 ± 0.50
- Internal hole diameter: 7.50 ± 0.50
- Internal hole diameter: 5.10 ± 0.50
- Internal hole diameter: 0
- Internal hole diameter: 7.50 ± 0.50
- Internal hole diameter: 13.50 ± 0.50
- Internal hole diameter: 17 ± 0.50
- Internal hole diameter: 27 ± 0.50
- Internal hole diameter: 27 ± 0.50
- Internal hole diameter: 48 ± 0.50
- Internal hole diameter: 48 ± 0.50


Side View Dimensions:








- Overall height: 62 ± 1
- Internal height: 16 ± 0.50
- Internal height: 6.50 ± 0.50 (4x)
- Internal height: 0.50 ± 0.05
- Internal height: 0.80 ± 0.10
- Internal height: 1 ± 0.10





Front View Dimensions:





- Overall width: 108 ± 1
- Overall height: 22 ± 0.5
- Internal width: 93 ± 0.25
- Internal height: 48 ± 0.25
- Corner radius: $R6.50$
- Mounting hole diameter: $\varnothing 12 \pm 0.10$ (4x)
- Internal hole diameter: $\varnothing 6.40 \pm 0.10$ (4x)
- Internal hole diameter: $\varnothing 12 \pm 0.10$ (4x)
- Internal hole diameter: $\varnothing 14$
- Internal hole diameter: $\varnothing 12$
- Internal hole diameter: $M5$ (4x)
- Internal hole diameter: 7.8 MAX
- Internal hole diameter: 18.20 ± 0.50
- Internal hole diameter: 13.50 ± 0.50
- Internal hole diameter: 7.50 ± 0.50
- Internal hole diameter: 5.10 ± 0.50
- Internal hole diameter: 0
- Internal hole diameter: 7.50 ± 0.50
- Internal hole diameter: 13.50 ± 0.50
- Internal hole diameter: 17 ± 0.50
- Internal hole diameter: 27 ± 0.50
- Internal hole diameter: 27 ± 0.50
- Internal hole diameter: 48 ± 0.50
- Internal hole diameter: 48 ± 0.50

Q1 to Q4 Typical performance curve





CR1 to CR4 Typical performance curve


CR5 & CR6 Typical performance curve


DISCLAIMER

The information contained in the document (unless it is publicly available on the Web without access restrictions) is PROPRIETARY AND CONFIDENTIAL information of Microsemi and cannot be copied, published, uploaded, posted, transmitted, distributed or disclosed or used without the express duly signed written consent of Microsemi. If the recipient of this document has entered into a disclosure agreement with Microsemi, then the terms of such Agreement will also apply. This document and the information contained herein may not be modified, by any person other than authorized personnel of Microsemi. No license under any patent, copyright, trade secret or other intellectual property right is granted to or conferred upon you by disclosure or delivery of the information, either expressly, by implication, inducement, estoppels or otherwise. Any license under such intellectual property rights must be approved by Microsemi in writing signed by an officer of Microsemi.

Microsemi reserves the right to change the configuration, functionality and performance of its products at anytime without any notice. This product has been subject to limited testing and should not be used in conjunction with life-support or other mission-critical equipment or applications. Microsemi assumes no liability whatsoever, and Microsemi disclaims any express or implied warranty, relating to sale and/or use of Microsemi products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Any performance specifications believed to be reliable but are not verified and customer or user must conduct and complete all performance and other testing of this product as well as any user or customers final application. User or customer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the customer's and user's responsibility to independently determine suitability of any Microsemi product and to test and verify the same. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the User. Microsemi specifically disclaims any liability of any kind including for consequential, incidental and punitive damages as well as lost profit. The product is subject to other terms and conditions which can be located on the web at <http://www.microsemi.com/legal/tnc.asp>

Life Support Application

Seller's Products are not designed, intended, or authorized for use as components in systems intended for space, aviation, surgical implant into the body, in other applications intended to support or sustain life, or for any other application in which the failure of the Seller's Product could create a situation where personal injury, death or property damage or loss may occur (collectively "Life Support Applications").

Buyer agrees not to use Products in any Life Support Applications and to the extent it does it shall conduct extensive testing of the Product in such applications and further agrees to indemnify and hold Seller, and its officers, employees, subsidiaries, affiliates, agents, sales representatives and distributors harmless against all claims, costs, damages and expenses, and attorneys' fees and costs arising, directly or indirectly, out of any claims of personal injury, death, damage or otherwise associated with the use of the goods in Life Support Applications, even if such claim includes allegations that Seller was negligent regarding the design or manufacture of the goods.

Buyer must notify Seller in writing before using Seller's Products in Life Support Applications. Seller will study with Buyer alternative solutions to meet Buyer application specification based on Sellers sales conditions applicable for the new proposed specific part.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Microchip:](#)

[APTGL240TL120G](#)