

High-Performance, Dual 150 mA μ Cap Ultra-Low Dropout Regulator

Features

- 2.3V to 5.5V Input Voltage Range
- Ultra-Low Dropout Voltage 35 mV @ 150 mA
- Tiny 6-Pin 1.6 mm x 1.6 mm Thin UDFN Leadless Package
- Low Cost 6-Lead TSOT-23 Package
- Bypass Pin for Improved Noise Performance
- High PSRR: >75 dB on Each LDO
- Ultra-Low Noise Output: >30 μ V_{RMS}
- Dual 150 mA Outputs
- μ Cap Stable with 1 μ F Ceramic Capacitor
- Low Quiescent Current: 150 μ A
- Fast Turn-On Time: 45 μ s
- Thermal Shutdown Protection
- Current Limit Protection

Applications

- Mobile Phones
- PDAs
- GPS Receivers
- Portable Electronics
- Portable Media Players
- Digital Still and Video Cameras


General Description

The MIC5321 is a tiny, dual ultra-low dropout linear regulator ideally suited for applications that require high PSRR because it provides a bypass pin for those noise sensitive portable electronics. The MIC5321 integrates two high-performance 150 mA ULDOs into a very compact 1.6 mm x 1.6 mm leadless UDFN package that provides exceptional thermal package characteristics.

The MIC5321 is a μ Cap design that enables operation with very small ceramic output capacitors for stability, thereby reducing required board space and component cost. The combination of extremely low dropout voltage, very high power supply rejection, very low output noise, and exceptional thermal package characteristics makes it ideal for powering RF application, cellular phone camera modules, imaging sensors for digital still cameras, PDAs, MP3 players and WebCam applications.


The MIC5321 is available in fixed-output voltages in the tiny 6-pin 1.6 mm x 1.6 mm leadless UDFN package, which is only 2.56 mm² in area, less than 30% the area of the SOT-23 and TSOP 3x3 packages. It's also available in the thin SOT-23 6-lead package and the standard size 6-pin 1.6 mm x 1.6 mm leadless WDFN package. Additional voltage options are available. For more information, contact Microchip.

Package Types




MIC5321

Typical Application Circuit



Functional Block Diagram



1.0 ELECTRICAL CHARACTERISTICS

Absolute Maximum Ratings †

Supply Input Voltage (V_{IN})	0V to +6V
Enable Input Voltage (V_{EN})	0V to +6V
Power Dissipation (P_D) Note 1	Internally Limited
ESD Rating (Note 2)	2 kV

Operating Ratings ‡

Supply Input Voltage (V_{IN})	+2.3V to +5.5V
Enable Input Voltage (V_{EN})	0V to V_{IN}

† **Notice:** Stresses above those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at those or any other conditions above those indicated in the operational sections of this specification is not intended. Exposure to maximum rating conditions for extended periods may affect device reliability.

‡ **Notice:** The device is not guaranteed to function outside its operating ratings.

Note 1: The maximum allowable power dissipation at any T_A (ambient temperature) is $P_{D(MAX)} = (T_{J(MAX)} - T_A)/\theta_{JA}$. Exceeding the maximum allowable power dissipation will result in excessive die temperature, and the regulator will go into thermal shutdown.

2: Devices are ESD sensitive. Handling precautions recommended. Human body model, 1.5 k Ω in series with 100 pF.

ELECTRICAL CHARACTERISTICS

Electrical Characteristics: $V_{IN} = EN = V_{OUT} + 1.0V$; higher of the two regulator outputs, $I_{OUTLDO1} = I_{OUTLDO2} = 100 \mu A$; $C_{OUT1} = C_{OUT2} = 1 \mu F$; $C_{BYP} = 0.01 \mu F$; $T_J = 25^\circ C$, **bold** values valid for $-40^\circ C \leq T_J \leq +125^\circ C$, unless noted. ([Note 1](#))

Parameter	Symbol	Min.	Typ.	Max.	Units	Conditions
Output Voltage Accuracy	V_{OUT}	-2.0	—	2.0	%	Variation from nominal V_{OUT}
		-3.0	—	3.0		Variation from nominal V_{OUT} ; $-40^\circ C$ to $+125^\circ C$
Line Regulation	$\Delta V_{OUT}/(V_{OUT} \times \Delta V_{IN})$	—	0.02	0.3	%V	$V_{IN} = V_{OUT} + 1V$ to 5.5V; $I_{OUT} = 100 \mu A$
		—	—	0.6		
Load Regulation	$\Delta V_{OUT}/V_{OUT}$	—	0.5	2.0	%	$I_{OUT} = 100 \mu A$ to 150 mA
Dropout Voltage (Note 2)	V_{DO}	—	0.1	—	mV	$I_{OUT} = 100 \mu A$
		—	12	50		$I_{OUT} = 50 mA$
		—	25	75		$I_{OUT} = 100 mA$
		—	35	100		$I_{OUT} = 150 mA$
Ground Current	I_{GND}	—	150	190	μA	EN = High; $I_{OUT1} = 150 mA$, $I_{OUT2} = 150 mA$
Ground Current in Shutdown	I_{SHDN}	—	0.01	2	μA	EN1 $\leq 0.2V$
Ripple Rejection	PSRR	—	75	—	dB	f = 1 kHz; $C_{OUT} = 1.0 \mu F$; $C_{BYP} = 0.1 \mu F$
		—	45	—		f = 20 kHz; $C_{OUT} = 1.0 \mu F$; $C_{BYP} = 0.1 \mu F$
Current Limit	I_{LIM}	300	550	950	mA	$V_{OUT} = 0V$
Output Voltage Noise	e_N	—	30	—	μV_{RMS}	$C_{OUT} = 1.0 \mu F$; $C_{BYP} = 0.01 \mu F$; 10 Hz to 100 kHz

ELECTRICAL CHARACTERISTICS (CONTINUED)

Electrical Characteristics: $V_{IN} = EN = V_{OUT} + 1.0V$; higher of the two regulator outputs, $I_{OUTLDO1} = I_{OUTLDO2} = 100 \mu A$; $C_{OUT1} = C_{OUT2} = 1 \mu F$; $C_{BYP} = 0.01 \mu F$; $T_J = 25^\circ C$, **bold** values valid for $-40^\circ C \leq T_J \leq +125^\circ C$, unless noted. (Note 1)

Parameter	Symbol	Min.	Typ.	Max.	Units	Conditions
Enable Inputs (EN)						
Enable Input Voltage	V _{IL}	—	—	0.2	V	Logic Low
	V _{IH}	1.1	—	—		Logic High
Enable Input Current	I _{IL}	—	0.01	1	μA	V _{IL} ≤ 0.2V
	I _{IH}	—	0.01	1		V _{IH} ≥ 1.0V
Turn-On Time						
Turn-On Time (LDO1 and LDO2)	t _{ON}	—	40	100	μs	C _{OUT} = 1.0 μF; No C _{BYP}
		—	45	100		C _{OUT} = 1.0 μF; C _{BYP} = 0.01 μF

Note 1: Specification for packaged product only.

- 2: Dropout voltage is defined as the input-to-output differential at which the output voltage drops 2% below its nominal V_{OUT} . For outputs below 2.3V, the dropout voltage is the input-to-output differential with the minimum input voltage 2.3V.

TEMPERATURE SPECIFICATIONS

Parameters	Sym.	Min.	Typ.	Max.	Units	Conditions
Temperature Ranges						
Operating Junction Temperature Range	T_J	-40	—	+125	$^\circ C$	Note 1
Lead Temperature	T_{LEAD}	—	—	+260	$^\circ C$	Soldering, 3 sec.
Storage Temperature	T_S	-65	—	+150	$^\circ C$	—
Package Thermal Resistances						
Thermal Resistance, UDFN/WDFN 6-Ld	θ_{JA}	—	100	—	$^\circ C/W$	—
Thermal Resistance, TSOT-23 6-Ld	θ_{JA}	—	235	—	$^\circ C/W$	—

Note 1: The maximum allowable power dissipation is a function of ambient temperature, the maximum allowable junction temperature and the thermal resistance from junction to air (i.e., T_A , T_J , θ_{JA}). Exceeding the maximum allowable power dissipation will cause the device operating junction temperature to exceed the maximum +125 $^\circ C$ rating. Sustained junction temperatures above +125 $^\circ C$ can impact the device reliability.

2.0 TYPICAL PERFORMANCE CURVES

Note: The graphs and tables provided following this note are a statistical summary based on a limited number of samples and are provided for informational purposes only. The performance characteristics listed herein are not tested or guaranteed. In some graphs or tables, the data presented may be outside the specified operating range (e.g., outside specified power supply range) and therefore outside the warranted range.




FIGURE 2-1: Power Supply Rejection Ratio.




FIGURE 2-4: Ground Current vs. Temperature.




FIGURE 2-2: Dropout Voltage vs. Output Current.




FIGURE 2-5: Ground Current vs. Temperature.




FIGURE 2-3: Output Voltage vs. Temperature.




FIGURE 2-6: Output Voltage vs. Input Voltage.




FIGURE 2-7: Dropout Voltage vs. Temperature.




FIGURE 2-10: Ground Current vs. Output Current.




FIGURE 2-8: Output Voltage vs. Output Current.




FIGURE 2-11: Current Limit vs. Input Voltage.




FIGURE 2-9: Output Voltage vs. Output Current.




FIGURE 2-12: Output Noise Spectral Density.




FIGURE 2-13: *Enable Turn-On.*




FIGURE 2-14: *Load Transient.*




FIGURE 2-15: *Line Transient.*

MIC5321

3.0 PIN DESCRIPTIONS

The descriptions of the pins are listed in [Table 3-1](#).

TABLE 3-1: PIN FUNCTION TABLE

Pin Number UDFN/WDFN	Pin Number TSOT	Pin Name	Description
1	3	VIN	Supply Input.
2	2	GND	Ground.
3	1	BYP	Reference Bypass: Connect external 0.01 μ F to GND to reduce output noise. May be left open.
4	6	EN	Enable Input (both regulators): Active-High Input. Logic High = On; Logic Low = Off; Do not leave floating.
5	5	VOUT2	Regulator Output: LDO2
6	4	VOUT1	Regulator Output: LDO1
HS Pad	—	ePAD	Exposed heatsink pad connected internally 3rto ground.

4.0 APPLICATION INFORMATION

4.1 Enable/Shutdown

The MIC5321 comes with a single active-high enable pin that allows both regulators to be disabled simultaneously. Forcing the enable pin low disables the regulator and sends it into a “zero” off-mode current state. In this state, current consumed by the regulator goes nearly to zero. Forcing the enable pin high enables the output voltage. The active-high enable pin uses CMOS technology and the enable pin cannot be left floating; a floating enable pin may cause an indeterminate state on the output.

4.2 Input Capacitor

The MIC5321 is a high-performance, high-bandwidth device. Therefore, it requires a well-bypassed input supply for optimal performance. A 1 μF capacitor is required from the input to ground to provide stability. Low-ESR ceramic capacitors provide optimal performance at a minimum of space. Additional high-frequency capacitors, such as small-valued NPO dielectric-type capacitors, help filter out high-frequency noise and are good practice in any RF-based circuit.

4.3 Output Capacitor

The MIC5321 requires an output capacitor of 1 μF or greater to maintain stability. The design is optimized for use with low-ESR ceramic chip capacitors. High ESR capacitors may cause high frequency oscillation. The output capacitor can be increased, but performance has been optimized for a 1 μF ceramic output capacitor and does not improve significantly with larger capacitance.

X7R/X5R dielectric-type ceramic capacitors are recommended because of their temperature performance. X7R-type capacitors change capacitance by 15% over their operating temperature range and are the most stable type of ceramic capacitors. Z5U and Y5V dielectric capacitors change value by as much as 50% and 60%, respectively, over their operating temperature ranges. To use a ceramic chip capacitor with Y5V dielectric, the value must be much higher than an X7R ceramic capacitor to ensure the same minimum capacitance over the equivalent operating temperature range.

4.4 Bypass Capacitor

A capacitor can be placed from the noise bypass pin to ground to reduce output voltage noise. The capacitor bypasses the internal reference. A 0.1 μF capacitor is recommended for applications that require low-noise outputs. The bypass capacitor can be increased, further reducing noise and improving PSRR. Turn-on time increases slightly with respect to bypass capacitance. A unique, quick-start circuit allows the

MIC5321 to drive a large capacitor on the bypass pin without significantly slowing turn-on time. Refer to the [Typical Performance Curves](#) section for performance with different bypass capacitors.

4.5 No-Load Stability

Unlike many other voltage regulators, the MIC5321 will remain stable and in regulation with no load. This is especially important in CMOS RAM keep-alive applications.

4.6 Thermal Considerations

The MIC5321 is designed to provide 150 mA of continuous current for both outputs in a very small package. Maximum ambient operating temperature can be calculated based on the output current and the voltage drop across the part. Given that the input voltage is 3.3V, the output voltage is 2.8V for V_{OUT1} , 2.5V for V_{OUT2} and the output current equals 150 mA. The actual power dissipation of the regulator circuit can be determined using the equation:

EQUATION 4-1:

$$P_D = (V_{IN} - V_{OUT1}) \times I_{OUT1} + (V_{IN} - V_{OUT2}) \times I_{OUT2} + V_{IN} \times I_{GND}$$

Because this device is CMOS and the ground current is typically <150 μA over the load range, the power dissipation contributed by the ground current is less than 1% and can be ignored for this calculation.

EQUATION 4-2:

$$P_D = (3.3V - 2.8V) \times 150mA + (3.3V - 1.5V) \times 150mA$$

$$P_D = 0.345W$$

To determine the maximum ambient operating temperature of the package, use the junction-to-ambient thermal resistance of the device and the following basic equation:

EQUATION 4-3:

$$P_{D(MAX)} = \frac{T_{J(MAX)} - T_A}{\theta_{JA}}$$

Where:

$T_{J(MAX)}$ = 125°C, the max. junction temp. of the die.
 θ_{JA} = Thermal resistance of 100°C/W.

The table below shows the junction-to-ambient thermal resistance for the UDFN package option.

Package	θ_{JA} Rec. Min. Footprint	θ_{JC}
6-Lead UDFN	100°C/W	2°C/W

MIC5321

Substituting P_D for $P_{D(MAX)}$ and solving for the ambient operating temperature will give the maximum operating conditions for the regulator circuit. The junction-to-ambient thermal resistance for the minimum footprint is 100°C/W .

The maximum power dissipation must not be exceeded for proper operation.

For example, when operating the MIC5321-MFYMT at an input voltage of 3.3V and 150 mA loads at each output with a minimum footprint layout, the maximum ambient operating temperature T_A can be determined as follows:


EQUATION 4-4:

$$0.345\text{ W} = (125^{\circ}\text{C} - T_A)/(100^{\circ}\text{C/W})$$
$$T_A = 90.5^{\circ}\text{C}$$

Therefore, a 2.8V/1.5V application with 150 mA at each output current can accept an ambient operating temperature of 90.5°C in a 1.6 mm x 1.6 mm UDFN package. For a full discussion of heat sinking and thermal effects on voltage regulators, refer to the “Regulator Thermals” section of Microchip’s [Designing with Low-Dropout Voltage Regulators](#) handbook.

5.0 PACKAGING INFORMATION

5.1 Package Marking Information



Note: MIC5321 has many voltage options and corresponding marking codes. The full list of them appear in [Table 5-1](#) on the next page.

Legend:	XX...X	Product code or customer-specific information
	Y	Year code (last digit of calendar year)
	YY	Year code (last 2 digits of calendar year)
	WW	Week code (week of January 1 is week '01')
	NNN	Alphanumeric traceability code
	(e3)	Pb-free JEDEC® designator for Matte Tin (Sn)
	*	This package is Pb-free. The Pb-free JEDEC designator ((e3)) can be found on the outer packaging for this package.
	•, ▲, ▼	Pin one index is identified by a dot, delta up, or delta down (triangle mark).
Note:	In the event the full Microchip part number cannot be marked on one line, it will be carried over to the next line, thus limiting the number of available characters for customer-specific information. Package may or may not include the corporate logo.	
	Underbar (_) symbol may not be to scale.	

Note: If the full seven-character YYWWNNN code cannot fit on the package, the following truncated codes are used based on the available marking space:
 6 Characters = YWWNNN; 5 Characters = WWNNN; 4 Characters = WNNN; 3 Characters = NNN;
 2 Characters = NN; 1 Character = N

MIC5321

TABLE 5-1: MIC5321 PACKAGE MARKING CODES

Part Number	Marking	Voltage	Package
MIC5321-GFYMT	BGF	1.8V/1.5V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-GGYMT	BGG	1.8V/1.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-GWYMT	BGW	1.8V/1.6V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-JGYMT	BJG	2.5V/1.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-JJYMT	BJJ	2.5V/2.5V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-KDYMT	BKD	2.6V/1.85V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-KGYMT	BKG	2.6V/1.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-LLYMT	BLL	2.7V/2.7V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-MFYMT	BMF	2.8V/1.5V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-MGYMT	BMG	2.8V/1.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-MKYMT	BMK	2.8V/2.6V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-MMYMT	BMM	2.8V/2.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-NDYMT	BND	2.85V/1.85V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-NKYMT	BNK	2.85V/2.6V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-NNYMT	BNN	2.85V/2.85V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-OFYMT	BOF	2.9V/1.5V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-OGYMT	BOG	2.9V/1.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-OOYMT	BOO	2.9V/2.9V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-PGYMT	BPG	3.0V/1.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-PJYMT	BPJ	3.0V/2.5V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-PKYMT	BPK	3.0V/2.6V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-PMYMT	BPM	3.0V/2.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-PNYMT	BPN	3.0V/2.85V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-PPYMT	BPP	3.0V/3.0V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-SFYMT	BSF	3.3V/1.5V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-SGYMT	BSG	3.3V/1.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-SJYMT	BSJ	3.3V/2.5V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-SKYMT	BSK	3.3V/2.6V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-SLYMT***	BSL	3.3V/2.7V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-SMYMT	BSM	3.3V/2.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-SNYMT	BSN	3.3V/2.85V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-SOYMT	BSO	3.3V/2.9V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-SPYMT	BSP	3.3V/3.0V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-SRYMT	BSR	3.3V/3.2V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-SSYMT	BSS	3.3V/3.3V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-MFYML	<u>BMF</u>	2.8V/1.5V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-MGYML	<u>BMG</u>	2.8V/1.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-MMYML	<u>BMM</u>	2.8V/2.8V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-PPYML	<u>BPP</u>	3.0V/3.0V	6-Lead 1.6 mm x 1.6 mm UDFN
MIC5321-GFYD6	<u>QBGF</u>	1.8V/1.5V	6-Lead 1.6 mm x 1.6 mm WDFN
MIC5321-GGYD6	<u>QBGG</u>	1.8V/1.8V	6-Lead 1.6 mm x 1.6 mm WDFN
MIC5321-GWYD6***	<u>QBGW</u>	1.8V/1.6V	6-Lead 1.6 mm x 1.6 mm WDFN
MIC5321-JGYD6***	<u>QB_JG</u>	2.5V/1.8V	6-Lead 1.6 mm x 1.6 mm WDFN
MIC5321-JJYD6***	<u>QB_JJ</u>	2.5V/2.5V	6-Lead 1.6 mm x 1.6 mm WDFN


TABLE 5-1: MIC5321 PACKAGE MARKING CODES (CONTINUED)

Part Number	Marking	Voltage	Package
MIC5321-KDYD6***	<u>QB</u> KD	2.6V/1.85V	6-Lead TSOT-23
MIC5321-KGYD6***	<u>QB</u> KG	2.6V/1.8V	6-Lead TSOT-23
MIC5321-LLYD6	<u>QB</u> LL	2.7V/2.7V	6-Lead TSOT-23
MIC5321-MFYD6	<u>QB</u> MF	2.8V/1.5V	6-Lead TSOT-23
MIC5321-MGYD6	<u>QB</u> MG	2.8V/1.8V	6-Lead TSOT-23
MIC5321-MKYD6	<u>QB</u> MK	2.8V/2.6V	6-Lead TSOT-23
MIC5321-MMYD6	<u>QB</u> MM	2.8V/2.8V	6-Lead TSOT-23
MIC5321-NDYD6***	<u>QB</u> ND	2.85V/1.85V	6-Lead TSOT-23
MIC5321-NKYD6***	<u>QB</u> NK	2.85V/2.6V	6-Lead TSOT-23
MIC5321-NNYD6***	<u>QB</u> NN	2.85V/2.85V	6-Lead TSOT-23
MIC5321-OFYD6***	<u>QB</u> OF	2.9V/1.5V	6-Lead TSOT-23
MIC5321-OGYD6***	<u>QB</u> OG	2.9V/1.8V	6-Lead TSOT-23
MIC5321-OOYD6***	<u>QB</u> OO	2.9V/2.9V	6-Lead TSOT-23
MIC5321-PGYD6	<u>QB</u> PG	3.0V/1.8V	6-Lead TSOT-23
MIC5321-PJYD6***	<u>QB</u> PJ	3.0V/2.5V	6-Lead TSOT-23
MIC5321-PKYD6***	<u>QB</u> PK	3.0V/2.6V	6-Lead TSOT-23
MIC5321-PMYD6***	<u>QB</u> PM	3.0V/2.8V	6-Lead TSOT-23
MIC5321-PNYD6***	<u>QB</u> PN	3.0V/2.85V	6-Lead TSOT-23
MIC5321-PPYD6	<u>QB</u> PP	3.0V/3.0V	6-Lead TSOT-23
MIC5321-SFYD6***	<u>QB</u> SF	3.3V/1.5V	6-Lead TSOT-23
MIC5321-SGYD6***	<u>QB</u> SG	3.3V/1.8V	6-Lead TSOT-23
MIC5321-SJYD6	<u>QB</u> SJ	3.3V/2.5V	6-Lead TSOT-23
MIC5321-SKYD6***	<u>QB</u> SK	3.3V/2.6V	6-Lead TSOT-23
MIC5321-SLYD6***	<u>QB</u> SL	3.3V/2.7V	6-Lead TSOT-23
MIC5321-SMYD6***	<u>QB</u> SM	3.3V/2.8V	6-Lead TSOT-23
MIC5321-SNYD6***	<u>QB</u> SN	3.3V/2.85V	6-Lead TSOT-23
MIC5321-SOYD6***	<u>QB</u> SO	3.3V/2.9V	6-Lead TSOT-23
MIC5321-SPYD6***	<u>QB</u> SP	3.3V/3.0V	6-Lead TSOT-23
MIC5321-SRYD6***	<u>QB</u> SR	3.3V/3.2V	6-Lead TSOT-23
MIC5321-SSYD6	<u>QB</u> SS	3.3V/3.3V	6-Lead TSOT-23

6-Lead 1.6 mm x 1.6 mm UDFN Package Outline and Recommended Land Pattern

6-Lead Ultra Thin Plastic Dual Flat, No Lead (HKA) - 1.6x1.6x0.6 mm Body [UDFN] With 1.26x0.50 mm Exposed Pad; Micrel Legacy Package TDFN1616-6LD-PL-1


Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Microchip Technology Drawing C04-1154 Rev A Sheet 1 of 2

6-Lead Ultra Thin Plastic Dual Flat, No Lead (HKA) - 1.6x1.6x0.6 mm Body [UDFN] With 1.26x0.50 mm Exposed Pad; Micrel Legacy Package TDFN1616-6LD-PL-1

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Dimension Limits	Units	MILLIMETERS		
		MIN	NOM	MAX
Number of Terminals	N	6		
Pitch	e	0.50 BSC		
Overall Height	A	0.50	0.55	0.60
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3	0.152 REF		
Overall Length	D	1.60 BSC		
Exposed Pad Length	D2	1.21	1.26	1.31
Overall Width	E	1.60 BSC		
Exposed Pad Width	E2	0.45	0.50	0.55
Terminal Width	b	0.20	0.25	0.30
Terminal Length	L	0.30	0.35	0.40
Terminal-to-Exposed-Pad	K	0.20	—	—


Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1154 Rev A Sheet 2 of 2

6-Lead Ultra Thin Plastic Dual Flat, No Lead (HKA) - 1.6x1.6x0.6 mm Body [UDFN] With 1.26x0.50 mm Exposed Pad; Micrel Legacy Package TDFN1616-6LD-PL-1

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E	0.50 BSC		
Center Pad Width	X2			1.30
Center Pad Length	Y2			0.55
Contact Pad Spacing	C		1.70	
Contact Pad Width (X6)	X1			0.30
Contact Pad Length (X6)	Y1			0.65
Contact Pad to Center Pad (X6)	G1	0.25		
Contact Pad to Contact Pad (X4)	G2	0.20		

Notes:


1. Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing C04-3154 Rev A

6-Lead 1.6 mm x 1.6 mm WDFN Package Outline and Recommended Land Pattern

6-Lead Very, Very Thin Dual Flat, No Lead Package (K3A) - 1.6x1.6x0.8 mm Body [WDFN] With 1.26x0.5 mm Exposed Pad; Micrel Legacy Package Code DFN1616-6LD-PL-1


Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Microchip Technology Drawing C04-1015 Rev A Sheet 1 of 2

6-Lead Very, Very Thin Dual Flat, No Lead Package (K3A) - 1.6x1.6x0.8 mm Body [WDFN] With 1.26x0.5 mm Exposed Pad; Micrel Legacy Package Code DFN1616-6LD-PL-1

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N	6		
Pitch	e	0.50 BSC		
Overall Height	A	0.70	0.75	0.80
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3	0.203 REF		
Overall Length	D	1.60 BSC		
Exposed Pad Length	D2	1.21	1.26	1.31
Overall Width	E	1.60 BSC		
Exposed Pad Width	E2	0.45	0.50	0.55
Terminal Width	b	0.20	0.25	0.30
Terminal Length	L	0.30	0.35	0.40
Terminal-to-Exposed-Pad	K	0.20	—	—


Notes:

- Pin 1 visual index feature may vary, but must be located within the hatched area.
- Package is saw singulated
- Dimensioning and tolerancing per ASME Y14.5M
 - BSC: Basic Dimension. Theoretically exact value shown without tolerances.
 - REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1015 Rev A Sheet 2 of 2

6-Lead Very, Very Thin Dual Flat, No Lead Package (K3A) - 1.6x1.6x0.8 mm Body [WDFN] With 1.26x0.5 mm Exposed Pad; Micrel Legacy Package Code DFN1616-6LD-PL-1

Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		0.50 BSC	
Center Pad Width	X2			1.30
Center Pad Length	Y2			0.30
Contact Pad Spacing	C		1.70	
Contact Pad Width (X6)	X1			0.30
Contact Pad Length (X6)	Y1			1.30
Contact Pad to Center Pad (X6)	G1	0.25		
Contact Pad to Contact Pad (X4)	G2	0.20		
Thermal Via Diameter	V		0.30	

Notes:


- Dimensioning and tolerancing per ASME Y14.5M
BSC: Basic Dimension. Theoretically exact value shown without tolerances.
- For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-3015 Rev A

6-Lead Thin SOT-23 Package Outline and Recommended Land Pattern

TITLE

6 LEAD TSOT PACKAGE OUTLINE & RECOMMENDED LAND PATTERN



Note: For the most current package drawings, please see the Microchip Packaging Specification located at <http://www.microchip.com/packaging>.

APPENDIX A: REVISION HISTORY

Revision A (May 2022)

- Converted Micrel document MIC5321 to Microchip data sheet DS20006678A.
- Minor text changes throughout.

MIC5321

NOTES:

PRODUCT IDENTIFICATION SYSTEM

To order or obtain information, e.g., on pricing or delivery, contact your local Microchip representative or sales office.

<u>Part Number</u>	<u>-XX</u>	<u>X</u>	<u>XX</u>	<u>-XX</u>
Device	Output Voltages	Temp. Range	Package	Media Type
Device: MIC5321: High-Performance, Dual 150 mA μ Cap Ultra-Low Dropout Regulator				
Output Voltages: GF = 1.8V/1.5V (UDFN & TSOT options only) GG = 1.8V/1.8V (UDFN & TSOT options only) GW = 1.8V/1.6V (UDFN & TSOT options only) JG = 2.5V/1.8V (UDFN & TSOT options only) JJ = 2.5V/2.5V (UDFN & TSOT options only) KD = 2.6V/1.85V (UDFN & TSOT options only) KG = 2.6V/1.8V (UDFN & TSOT options only) LL = 2.7V/2.7V (UDFN & TSOT options only) MF = 2.8V/1.5V (All package options) MG = 2.8V/1.8V (All package options) MK = 2.8V/2.6V (UDFN & TSOT options only) MM = 2.8V/2.8V (All package options) ND = 2.85V/1.85V (UDFN & TSOT options only) NK = 2.85V/2.6V (UDFN & TSOT options only) NN = 2.85V/2.85V (UDFN & TSOT options only) OF = 2.9V/1.5V (UDFN & TSOT options only) OG = 2.9V/1.8V (UDFN & TSOT options only) OO = 2.9V/2.9V (UDFN & TSOT options only) PG = 3.0V/1.8V (UDFN & TSOT options only) PJ = 3.0V/2.5V (UDFN & TSOT options only) PK = 3.0V/2.6V (UDFN & TSOT options only) PM = 3.0V/2.8V (UDFN & TSOT options only) PN = 3.0V/2.85V (UDFN & TSOT options only) PP = 3.0V/3.0V (All package options) SF = 3.3V/1.5V (UDFN & TSOT options only) SG = 3.3V/1.8V (UDFN & TSOT options only) SJ = 3.3V/2.5V (UDFN & TSOT options only) SK = 3.3V/2.6V (UDFN & TSOT options only) SL = 3.3V/2.7V (UDFN & TSOT options only) SM = 3.3V/2.8V (UDFN & TSOT options only) SN = 3.3V/2.85V (UDFN & TSOT options only) SO = 3.3V/2.9V (UDFN & TSOT options only) SP = 3.3V/3.0V (UDFN & TSOT options only) SR = 3.3V/3.2V (UDFN & TSOT options only) SS = 3.3V/3.3V (UDFN & TSOT options only)				
Temperature Range: Y = -40°C to +125°C				
Package: D6 = 6-Lead Thin SOT-23 ML = 6-Lead 1.6 mm x 1.6 mm WDFN MT = 6-Lead 1.6 mm x 1.6 mm UDFN				
Media Type: TR = 3,000/Reel (TSOT-23 option only) TR = 5,000/Reel (UDFN & WDFN options only)				
Examples: a) MIC5321-GGYMT-TR: MIC5321, 1.8V/1.8V Output Voltages, -40°C to +125°C Temp. Range, 6-Lead UDFN, 5,000/Reel b) MIC5321-KGYD6-TR: MIC5321, 2.6V/1.8V Output Voltages, -40°C to +125°C Temp. Range, 6-Lead TSOT-23, 3,000/Reel c) MIC5321-MMYML-TR: MIC5321, 2.8V/2.8V Output Voltages, -40°C to +125°C Temp. Range, 6-Lead WDFN, 5,000/Reel d) MIC5321-OFYMT-TR: MIC5321, 2.9V/1.5V Output Voltages, -40°C to +125°C Temp. Range, 6-Lead UDFN, 5,000/Reel e) MIC5321-SKYD6-TR: MIC5321, 3.3V/2.6V Output Voltages, -40°C to +125°C Temp. Range, 6-Lead TSOT-23, 3,000/Reel f) MIC5321-PPYML-TR: MIC5321, 3.0V/3.0V Output Voltages, -40°C to +125°C Temp. Range, 6-Lead WDFN, 5,000/Reel Note 1: Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.				

MIC5321

NOTES:

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
 - Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
 - Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
 - Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.
-

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at <https://www.microchip.com/en-us/support/design-help/client-support-services>.

THIS INFORMATION IS PROVIDED BY MICROCHIP “AS IS”. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP’S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer’s risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

For information regarding Microchip’s Quality Management Systems, please visit www.microchip.com/quality.

Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, CryptoMemory, CryptoRF, dsPIC, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Klear, LANCheck, LinkMD, maxStylus, maxTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, Flashtec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, QuietWire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, TrueTime, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, GridTime, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, Inter-Chip Connectivity, JitterBlocker, Knob-on-Display, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, NVm Express, NVMe, Omniscent Code Generation, PICDEM, PICDEM.net, PICKit, PICTail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SmartHLS, SMART-I.S., storClad, SQL, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, Symmcom, and Trusted Time are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2022, Microchip Technology Incorporated and its subsidiaries.

All Rights Reserved.

ISBN: 978-1-6683-0445-7

Worldwide Sales and Service

AMERICAS

Corporate Office
2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7200
Fax: 480-792-7277
Technical Support:
<http://www.microchip.com/support>
Web Address:
www.microchip.com

Atlanta
Duluth, GA
Tel: 678-957-9614
Fax: 678-957-1455

Austin, TX
Tel: 512-257-3370

Boston
Westborough, MA
Tel: 774-760-0087
Fax: 774-760-0088

Chicago
Itasca, IL
Tel: 630-285-0071
Fax: 630-285-0075

Dallas
Addison, TX
Tel: 972-818-7423
Fax: 972-818-2924

Detroit
Novi, MI
Tel: 248-848-4000

Houston, TX
Tel: 281-894-5983

Indianapolis
Noblesville, IN
Tel: 317-773-8323
Fax: 317-773-5453
Tel: 317-536-2380

Los Angeles
Mission Viejo, CA
Tel: 949-462-9523
Fax: 949-462-9608
Tel: 951-273-7800

Raleigh, NC
Tel: 919-844-7510

New York, NY
Tel: 631-435-6000

San Jose, CA
Tel: 408-735-9110
Tel: 408-436-4270

Canada - Toronto
Tel: 905-695-1980
Fax: 905-695-2078

ASIA/PACIFIC

Australia - Sydney
Tel: 61-2-9868-6733

China - Beijing
Tel: 86-10-8569-7000

China - Chengdu
Tel: 86-28-8665-5511

China - Chongqing
Tel: 86-23-8980-9588

China - Dongguan
Tel: 86-769-8702-9880

China - Guangzhou
Tel: 86-20-8755-8029

China - Hangzhou
Tel: 86-571-8792-8115

China - Hong Kong SAR
Tel: 852-2943-5100

China - Nanjing
Tel: 86-25-8473-2460

China - Qingdao
Tel: 86-532-8502-7355

China - Shanghai
Tel: 86-21-3326-8000

China - Shenyang
Tel: 86-24-2334-2829

China - Shenzhen
Tel: 86-755-8864-2200

China - Suzhou
Tel: 86-186-6233-1526

China - Wuhan
Tel: 86-27-5980-5300

China - Xian
Tel: 86-29-8833-7252

China - Xiamen
Tel: 86-592-2388138

China - Zhuhai
Tel: 86-756-3210040

ASIA/PACIFIC

India - Bangalore
Tel: 91-80-3090-4444

India - New Delhi
Tel: 91-11-4160-8631

India - Pune
Tel: 91-20-4121-0141

Japan - Osaka
Tel: 81-6-6152-7160

Japan - Tokyo
Tel: 81-3-6880-3770

Korea - Daegu
Tel: 82-53-744-4301

Korea - Seoul
Tel: 82-2-554-7200

Malaysia - Kuala Lumpur
Tel: 60-3-7651-7906

Malaysia - Penang
Tel: 60-4-227-8870

Philippines - Manila
Tel: 63-2-634-9065

Singapore
Tel: 65-6334-8870

Taiwan - Hsin Chu
Tel: 886-3-577-8366

Taiwan - Kaohsiung
Tel: 886-7-213-7830

Taiwan - Taipei
Tel: 886-2-2508-8600

Thailand - Bangkok
Tel: 66-2-694-1351

Vietnam - Ho Chi Minh
Tel: 84-28-5448-2100

EUROPE

Austria - Wels
Tel: 43-7242-2244-39
Fax: 43-7242-2244-393

Denmark - Copenhagen
Tel: 45-4485-5910
Fax: 45-4485-2829

Finland - Espoo
Tel: 358-9-4520-820

France - Paris
Tel: 33-1-69-53-63-20
Fax: 33-1-69-30-90-79

Germany - Garching
Tel: 49-8931-9700

Germany - Haan
Tel: 49-2129-3766400

Germany - Heilbronn
Tel: 49-7131-72400

Germany - Karlsruhe
Tel: 49-721-625370

Germany - Munich
Tel: 49-89-627-144-0
Fax: 49-89-627-144-44

Germany - Rosenheim
Tel: 49-8031-354-560

Israel - Ra'anana
Tel: 972-9-744-7705

Italy - Milan
Tel: 39-0331-742611
Fax: 39-0331-466781

Italy - Padova
Tel: 39-049-7625286

Netherlands - Drunen
Tel: 31-416-690399
Fax: 31-416-690340

Norway - Trondheim
Tel: 47-7288-4388

Poland - Warsaw
Tel: 48-22-3325737

Romania - Bucharest
Tel: 40-21-407-87-50

Spain - Madrid
Tel: 34-91-708-08-90
Fax: 34-91-708-08-91

Sweden - Gothenberg
Tel: 46-31-704-60-40

Sweden - Stockholm
Tel: 46-8-5090-4654

UK - Wokingham
Tel: 44-118-921-5800
Fax: 44-118-921-5820

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Microchip:

[MIC5321-NKYMT TR](#) [MIC5321-MFYMT TR](#) [MIC5321-GWYMT TR](#) [MIC5321-PNYMT TR](#) [MIC5321-SNYMT TR](#)
[MIC5321-SLYD6 TR](#) [MIC5321-SJYD6 TR](#) [MIC5321-KDYMT TR](#) [MIC5321-PPYMT TR](#) [MIC5321-LLYML TR](#)
[MIC5321-SRYMT TR](#) [MIC5321-MFYML TR](#) [MIC5321-NDYMT TR](#) [MIC5321-SSYMT TR](#) [MIC5321-PGYMT TR](#)
[MIC5321-GGYMT TR](#) [MIC5321-MMYD6 TR](#) [MIC5321-PMYMT TR](#) [MIC5321-JJYMT TR](#) [MIC5321-MGYML TR](#)
[MIC5321-SGYMT TR](#) [MIC5321-PGYD6 TR](#) [MIC5321-LLYD6 TR](#) [MIC5321-MKYMT TR](#) [MIC5321-MFYD6 TR](#)
[MIC5321-SSYML TR](#) [MIC5321-GGYD6 TR](#) [MIC5321-SFYMT TR](#) [MIC5321-MMYMT TR](#) [MIC5321-SOYMT TR](#)
[MIC5321-PPYD6 TR](#) [MIC5321-JGYMT TR](#) [MIC5321-PJYMT TR](#) [MIC5321-LLYMT TR](#) [MIC5321-46MYD6 TR](#)
[MIC5321-KGYMT TR](#) [MIC5321-SJYML TR](#) [MIC5321-PKYMT TR](#) [MIC5321-SKYMT TR](#) [MIC5321-SMYMT TR](#)
[MIC5321-OFYMT TR](#) [MIC5321-SLYMT TR](#) [MIC5321-OOYMT TR](#) [MIC5321-NNYMT TR](#) [MIC5321-MMYML TR](#)
[MIC5321-MKYD6 TR](#) [MIC5321-MGYMT TR](#) [MIC5321-OGYMT TR](#) [MIC5321-GFYD6 TR](#) [MIC5321-PPYML TR](#)
[MIC5321-46MYMT TR](#) [MIC5321-SPYMT TR](#) [MIC5321-SJYMT TR](#) [MIC5321-MGYD6 TR](#) [MIC5321-SSYD6 TR](#)
[MIC5321-GFYMT TR](#) [MIC5321-PGYMT-TR](#) [MIC5321-KGYMT-TR](#) [MIC5321-LLYML-TR](#) [MIC5321-SKYMT-TR](#)
[MIC5321-SLYD6-TR](#) [MIC5321-PKYMT-TR](#) [MIC5321-GFYMT-TR](#) [MIC5321-46MYMT-TR](#) [MIC5321-SLYMT-TR](#)
[MIC5321-SSYML-TR](#) [MIC5321-SJYMT-TR](#) [MIC5321-46MYD6-TR](#) [MIC5321-GGYD6-TR](#) [MIC5321-GFYD6-TR](#)
[MIC5321-GGYMT-TR](#) [MIC5321-MMYD6-TR](#) [MIC5321-PPYD6-TR](#) [MIC5321-SPYMT-TR](#) [MIC5321-SGYMT-TR](#)
[MIC5321-SRYMT-TR](#) [MIC5321-SSYMT-TR](#) [MIC5321-MGYMT-TR](#) [MIC5321-PPYML-TR](#) [MIC5321-MFYD6-TR](#)
[MIC5321-MGYML-TR](#) [MIC5321-MKYD6-TR](#) [MIC5321-NKYMT-TR](#) [MIC5321-SMYMT-TR](#) [MIC5321-SNYMT-TR](#)
[MIC5321-SOYMT-TR](#) [MIC5321-NNYMT-TR](#) [MIC5321-PMYMT-TR](#) [MIC5321-OFYMT-TR](#) [MIC5321-PPYMT-TR](#)
[MIC5321-JJYMT-TR](#) [MIC5321-LLYD6-TR](#) [MIC5321-GWYMT-TR](#) [MIC5321-PGYD6-TR](#) [MIC5321-SJYD6-TR](#)
[MIC5321-MGYD6-TR](#) [MIC5321-SFYMT-TR](#) [MIC5321-JGYMT-TR](#) [MIC5321-MFYMT-TR](#) [MIC5321-PNYMT-TR](#)