

# MTCH1010

## MTCH1010 Data Sheet

## Description

The Microchip MTCH1010 Touch Controller with digital output provides a simple way to add water tolerant touch detection or proximity sensing to any application. This device implements one capacitive sensor with active guarding capability. Sensitivity, response time, and oversampling can be configured via CFG input pins at run time. The MTCH1010 uses advanced optimization algorithms to actively suppress noise from the signal to achieve reliable touch detection.

The MTCH1010 provides one capacitive touch/proximity detection sensor which can work through plastic, wood, or even metal front panels with Microchip's proprietary Metal Over Capacitive (MOC) technology. It also supports a wide range of conductive materials as sensors, such as copper pad on PCB, silver ink, PEDOT or carbon printing on plastic film, Indium Tin Oxide (ITO) pad, wire/cable, etc. An open-drain active-low output will communicate the state of the sensor to a host microcontroller or drive an indication LED.

## Features

- Capacitive Touch Sensing
- High Signal to Noise Ratio (SNR)
- Adjustable Sensitivity
- Multi-Stage Active Noise Suppression Filters
- Automatic Environmental Compensation
- Water Tolerant Touch
- Support Wide Range of Sensor Shapes and Sizes
- Touch Indication by OUT Pin Level
- Detect Hysteresis
- Flexible Low-Power Mode
- Brown-Out Protection
- Operating Voltage Range:
  - 2V to 5.5V
- Operating Temperature:
  - - 40°C to +105°C

## **Typical Application**

- Light and Internet of Things (IoT) Switches
- Power Buttons
- White Goods and Appliance
- Office Equipment
- Toys
- Display and Keypad Back-Lighting Activation by Proximity
- Presence Detection

## **Table of Contents**

Des	scriptio	٦	1
Fea	tures		1
Тур	ical Ap	plication	1
1.	Pin Di	agram	4
2.	Config	juration	5
	2.1.	CFG0 – Response Time	5
	2.2.	CFG1 – Oversampling per Touch Scan Cycle	5
	2.3.	CFG2 – Touch Sensitivity	6
	2.4.	Further Preset Configurations	6
3.	Senso	r	8
	3.1.	CH0 – the Touch Electrode	8
	3.2.	SHIELD – Driven Shield	8
٨	Outou	*	0
4.			ອ ດ
	4.1.	0010	9
5.	Opera	tion	10
	5.1.	Power On / Reset	10
	5.2.	Run Time	10
6.	Exam	ple Circuit	11
	Rosno	onse Time	12
7.	rrespu		
7.	7.1.	Definitions	.12
7.	7.1. 7.2.	Definitions Measurement Time	.12 .12
7. 8.	7.1. 7.2. Power	Definitions Measurement Time	.12 .12 .12
7. 8. 9	7.1. 7.2. Power	Definitions Measurement Time Consumption	.12 .12 .12 .14
7. 8. 9.	7.1. 7.2. Power Electr	Definitions Measurement Time Consumption ical Specification	.12 .12 .12 .14 .15
7. 8. 9.	7.1. 7.2. Power Electri 9.1. 9.2	Definitions Measurement Time Consumption ical Specification Disclaimer Absolute Maximum Ratings	.12 .12 .12 .14 .15 .15
7. 8. 9.	7.1. 7.2. Power Electr 9.1. 9.2. 9.3.	Definitions Measurement Time Consumption ical Specification Disclaimer Absolute Maximum Ratings General Operating Ratings	.12 .12 .12 .14 .15 .15 .15
7. 8. 9.	<ul> <li>7.1.</li> <li>7.2.</li> <li>Power</li> <li>Electr</li> <li>9.1.</li> <li>9.2.</li> <li>9.3.</li> <li>9.4.</li> </ul>	Definitions Measurement Time Consumption ical Specification Disclaimer Absolute Maximum Ratings General Operating Ratings BOD and POR Characteristics	.12 .12 .12 .14 .15 .15 .15 .15 .15
7. 8. 9.	<ul> <li>7.1.</li> <li>7.2.</li> <li>Power</li> <li>Electri</li> <li>9.1.</li> <li>9.2.</li> <li>9.3.</li> <li>9.4.</li> <li>9.5.</li> </ul>	Definitions. Measurement Time. Consumption. Consumption. Disclaimer. Absolute Maximum Ratings. General Operating Ratings BOD and POR Characteristics. I/O Pin Characteristics.	.12 .12 .12 .14 .15 .15 .15 .15 .15 .15
<ol> <li>7.</li> <li>8.</li> <li>9.</li> <li>10.</li> </ol>	7.1. 7.2. Power Electr 9.1. 9.2. 9.3. 9.4. 9.5. Order	Definitions Measurement Time Consumption ical Specification Disclaimer Absolute Maximum Ratings General Operating Ratings BOD and POR Characteristics I/O Pin Characteristics	.12 .12 .12 .12 .14 .15 .15 .15 .15 .15 .16 .17
<ol> <li>7.</li> <li>8.</li> <li>9.</li> <li>10.</li> </ol>	<ul> <li>7.1.</li> <li>7.2.</li> <li>Powel</li> <li>Electr</li> <li>9.1.</li> <li>9.2.</li> <li>9.3.</li> <li>9.4.</li> <li>9.5.</li> <li>Order</li> <li>10.1.</li> </ul>	Definitions Measurement Time Consumption ical Specification Disclaimer Absolute Maximum Ratings General Operating Ratings BOD and POR Characteristics I/O Pin Characteristics I/O Pin Characteristics Product Information	12 12 12 14 15 15 15 15 15 16 17
<ol> <li>7.</li> <li>8.</li> <li>9.</li> <li>10.</li> <li>11</li> </ol>	<ul> <li>7.1.</li> <li>7.2.</li> <li>Powel</li> <li>Electri</li> <li>9.1.</li> <li>9.2.</li> <li>9.3.</li> <li>9.4.</li> <li>9.5.</li> <li>Order</li> <li>10.1.</li> <li>Packs</li> </ul>	Definitions. Measurement Time. Consumption. Consumption. Disclaimer. Absolute Maximum Ratings. General Operating Ratings BOD and POR Characteristics. I/O Pin Characteristics. I/O Pin Characteristics. I/O Pin Characteristics. I/O Pin Characteristics. I/O Pin Characteristics.	12 12 12 14 15 15 15 15 15 16 17 17
<ol> <li>7.</li> <li>8.</li> <li>9.</li> <li>10.</li> <li>11.</li> </ol>	<ul> <li>7.1.</li> <li>7.2.</li> <li>Powel</li> <li>Electri</li> <li>9.1.</li> <li>9.2.</li> <li>9.3.</li> <li>9.4.</li> <li>9.5.</li> <li>Orderi</li> <li>10.1.</li> <li>Packa</li> <li>11.1</li> </ul>	Definitions Measurement Time Consumption cal Specification Disclaimer Absolute Maximum Ratings General Operating Ratings BOD and POR Characteristics I/O Pin Characteristics I/O Pin Characteristics Ing Information Product Information BE Drawing	12 12 14 15 15 15 15 15 15 16 17 17 18
<ol> <li>7.</li> <li>8.</li> <li>9.</li> <li>10.</li> <li>11.</li> </ol>	<ul> <li>7.1.</li> <li>7.2.</li> <li>Powel</li> <li>Electri</li> <li>9.1.</li> <li>9.2.</li> <li>9.3.</li> <li>9.4.</li> <li>9.5.</li> <li>Order</li> <li>10.1.</li> <li>Packa</li> <li>11.1.</li> </ul>	Definitions. Measurement Time. Consumption. Consumption. Cal Specification. Disclaimer. Absolute Maximum Ratings. General Operating Ratings BOD and POR Characteristics. I/O Pin Characteristics. I/O Pin Characteristics. I/O Pin Characteristics. Ing Information. Product Information. Be Drawing	12 12 12 14 15 15 15 15 15 15 16 17 17 18 18
<ol> <li>7.</li> <li>8.</li> <li>9.</li> <li>10.</li> <li>11.</li> <li>12.</li> </ol>	<ul> <li>7.1.</li> <li>7.2.</li> <li>Power</li> <li>Electri</li> <li>9.1.</li> <li>9.2.</li> <li>9.3.</li> <li>9.4.</li> <li>9.5.</li> <li>Orderi</li> <li>10.1.</li> <li>Packa</li> <li>11.1.</li> <li>Apperi</li> </ul>	Definitions. Measurement Time. Consumption. ical Specification. Disclaimer. Absolute Maximum Ratings. General Operating Ratings BOD and POR Characteristics. I/O Pin Characteristics. I/O Pin Characteristics. Ing Information. Product Information. ge Drawing	12 12 14 15 15 15 15 15 15 16 17 17 18 18 23
<ol> <li>7.</li> <li>8.</li> <li>9.</li> <li>10.</li> <li>11.</li> <li>12.</li> </ol>	<ul> <li>7.1.</li> <li>7.2.</li> <li>Powel</li> <li>Electri</li> <li>9.1.</li> <li>9.2.</li> <li>9.3.</li> <li>9.4.</li> <li>9.5.</li> <li>Order</li> <li>10.1.</li> <li>Packa</li> <li>11.1.</li> <li>Apper</li> <li>12.1.</li> </ul>	Definitions Measurement Time Consumption ical Specification Disclaimer Absolute Maximum Ratings General Operating Ratings BOD and POR Characteristics I/O Pin Characteristics I/O Pin Characteristics ing Information Product Information ge Drawing 8-Pin SOIC150 dix Static Input Voltages	12 12 14 15 15 15 15 15 15 16 17 17 18 18 18 23 23

13. Conclusion	25
14. Revision History	26
The Microchip Website	27
Product Change Notification Service	27
Customer Support	27
Product Identification System	28
Microchip Devices Code Protection Feature	28
Legal Notice	28
Trademarks	29
Quality Management System	30
Worldwide Sales and Service	31

## 1. Pin Diagram

Figure 1-1. 8-Pin SOIC



Name	8-Lead SOIC	Usage
V <sub>DD</sub>	1	Power Supply (+)
CH0	2	Sensor Electrode Measurement
SHIELD	3	Shield Electrode Output Driver
OUT0	4	Touch Indication
CFG0	5	Response Time
CFG1	6	Oversampling
CFG2	7	Sensitivity
GND	8	Power Supply (-)

## 2. Configuration

Three configuration input pins are provided on the MTCH1010 and each one controls one of the following configuration parameters:

- Response Time
- Oversampling
- Sensitivity

Inputs are set by applying a voltage level to the respective CFG pin. Options how to generate these input voltages are provided in the Appendix.

At power-up, the configuration inputs are read by the MTCH1010 and sensor parameters are set accordingly. During run time, the inputs are measured once every two seconds and configuration changes are applied at subsequent sensor measurements. Each input must be in the range of 0V to  $V_{DD}$ . CFG0 and CFG1 are split into four bands providing four options for each parameter and CFG2 provides a continuous adjustment of sensitivity between 0V and  $V_{DD}$ .

Input Range	Configuration Selection
0V to ¼ V <sub>DD</sub>	А
$1_4^{\prime}V_{DD}$ to $1_2^{\prime}V_{DD}$	В
$1\!\!\!/_2  V_{DD}$ to $3\!\!\!/_4  V_{DD}$	С
$_{4}^{3}$ V <sub>DD</sub> to V <sub>DD</sub>	D

### 2.1 CFG0 – Response Time

CFG0 selects a response time of up to 300 ms for the target application. Measurement and sleep cycles are adjusted on chip depending on the oversampling configuration to achieve this response time. This control allows the application designer to balance touch responsiveness against power consumption. Increasing the target response time reduces power consumption as the device spends a higher proportion of time in Sleep mode. Reducing the response time provides a faster indication of touch contact.

**Note:** The configuration input is in non-ascending order. Settings expected in low-power applications are tied directly to  $V_{DD}$  or GND as this removes the necessity for a resistive divider bridge and associated bias current.

To achieve the lowest power configurations, the longest response times are selected at CFG options A (300 ms) and D (100 ms).

Configuration	Response Time (ms)
A	300
В	0 (minimum)
C	50
D	100

## 2.2 CFG1 – Oversampling per Touch Scan Cycle

CFG1 selects the number of samples to take on each measurement cycle. Increased sampling provides more stable sensor operation and better tolerance for electrical noise, but at the cost of increased power consumption and response time.

**Note:** As mentioned above, configuration input is in non-ascending order to avoid the necessity of resistive divider bias current. Lowest power option X8 sampling is selected by CFG1 = 'A', while the next lowest option X16 sampling is selected by CFG1 = 'D'.

## MTCH1010 Configuration

Configuration	# Samples
A	8
В	64
С	32
D	16

### 2.3 CFG2 – Touch Sensitivity

CFG2 determines the sensitivity of the touch sensor. A thicker touch cover, smaller sensor or nearby ground referenced conductors require higher sensitivity settings. Sensitivity does not affect power consumption or measurement time, except in the case of a high setting which may consume extra power by triggering unnecessary wake-up events.

**Note:** Sensitivity input CFG2 is implemented as a full-scale linear input.

It is recommended to match higher sensitivity settings with higher oversampling for robust touch sensing.

Input Range	Sensitivity
0V to V <sub>DD</sub>	<ul> <li>Lowest at 0V</li> <li>Increases with increasing Voltage at CFG2</li> <li>Highest at V<sub>DD</sub></li> </ul>

### 2.4 Further Preset Configurations

Other touch parameters are pre-set to provide reliable and consistent operation in a wide range of applications. Further details on touch parameters can be found in the Touch library User Guide.

### 2.4.1 Touch Detection

Setting	Value	Description
Detect Hysteresis:	12.5%	Touch will be reported as released after the signal falls 12.5% below sensitivity setting.
Detect Count-In:	4	Touch is reported after confirmations scans confirmed the touched status four times in a row. These confirmation scans are executed right after the initial touch status detection. This suppresses detections generated by electrical noise or from quick brushes of an object and fosters robust touch operation.

### 2.4.2 Anti-Touch Recalibration

Anti-touch recalibration always provides the intended touch sensitivity.

An anti-touch occurs if a button is pressed longer than the maximum duration in the moment of release. Anti-touch re-calibration ensures that the button is capable of detection at the following touch.

#### 2.4.3 Maximum on Recalibration

Setting	Value	Description
Maximum on Duration:	8s	After eight seconds of a detected touch, a calibration will be performed, thus releasing the touch.

#### 2.4.4 Sensor Drift

The MTCH1010 provides robust touch sensing by considering environmental changes (such as temperature, humidity, etc.). Touch raw data signals might and will drift over time and it is crucial that drift is compensated, otherwise, false detections, non-detections, and sensitivity shifts might occur.

Drift compensation is performed on chip the MTCH1010 and no host intervention of any kind is needed.

#### Figure 2-1. Drift Compensation



#### 2.4.5 Frequency Hop with Auto-Tune

The MTCH1010 provides robust touch sensing by considering electrical noise. Built in are latest noise avoidance technologies such as frequency hopping with auto-tune. As a result, the MTCH1010 will proactively adopt the touch sensing frequency according to the noise scenario during run time. No host intervention of any kind is needed.

## 3. Sensor

### 3.1 CH0 – the Touch Electrode

CH0 is the touch sensor input pin, which needs to be connected to the sensor electrode via a series resistor, to reduce EMI and EMC. The series resistor may be 10 k $\Omega$  to 200 k $\Omega$ , depending on the sensor capacitance and desired level of EMC performance.

Refer to the Microchip Capacitive Touch Design Guide – AN2934 for further details.

### 3.2 SHIELD – Driven Shield

The MTCH1010 features an active shield (Driven shield) signal to enhance touch sensitivity and robustness. Driven shield benefits:

- Reduced sensor load
- A rear shield prevents touch detection behind
- Provides water tolerant touch
- Increases sensitivity
- Shields against electrical noise

Refer to the Microchip Capacitive Touch Design Guide – AN2934 for further details and layout considerations for Driven Shield usage.

## 4. Output

## 4.1 OUT0

OUT0 provides indication of the touch detection state of the sensor. This is an open-drain output requiring an external pull-up to  $V_{DD}$ . The pin is in a high-impedance state, while the touch sensor is not in detect, switching to output low when the sensor is touched.

## 5. Operation

### 5.1 Power On / Reset

Configuration inputs CFG0, CFG1, CFG2 are read during the device initialization and the corresponding parameters are loaded into the run-time memory. An internal timer is configured to wake up the device at the configured cycle interval.

### 5.2 Run Time

#### Sensor Measurement

Measurement of sensor capacitance using Capacitive Voltage Divider method (for further details, see Application Note 1478 Sensing method Capacitive Voltage Divider). Optional Shield Output driver (SHIELD) provides increased sensitivity, reduction of sensor capacitive load, and shielding of sensor electrode from electrical noise as well as water tolerance.

Accumulation of 8/16/32/64 pairs of measurements according to configured oversampling (CFG1).

#### Post Processing

- Frequency Hop Auto-tune
  - Signal variance check
  - Frequency adjustment
- Event Processing
  - Power-on reference calibration timer-based reference drift
  - Touch detection
  - Anti-touch recalibration
  - Maximum on tecalibration

#### Sleep

Device enters Sleep mode until woken by the cycle timer.

#### Configuration

Every two seconds, the MTCH1010 re-reads the input configuration pins and updates the measurement/timing configuration accordingly.

## 6. Example Circuit

### Figure 6-1. Example Circuit



#### Example:

- CFG0 is connected to GND and so is read as 'A', setting the response time to its longest duration of 300 ms
- CFG1 is connected to V<sub>DD</sub>, read as 'D' and selects the number of samples at 16
- CFG2 is connected to Vh1, or (2/3) V<sub>DD</sub>.

In the example, the resistor ladder used to generate the input voltages for CFG1 and CFG2 will result in a bias current of 11 uA /17 uA pending  $V_{DD}$  of 3.3V or 5V.

See Appendix for further guidance on generation static or dynamic configuration voltages.

## 7. Response Time

## 7.1 Definitions

Response time	Maximum or worst-case 'delay' between physical contact until touch reporting on OUT That time is selected via CFG0.
Measurement time	Total time required to acquire (including oversampling) and post process touch signals
Sleep time	The time the device sleeps between measurements
Cycle time	Time between start of one measurement to start of next measurement – it includes: <ul> <li>Measurement time</li> <li>Sleep time</li> </ul>

### Figure 7-1. Timing Diagram



### 7.2 Measurement Time

Measurement time is dependent on oversampling:

Number of samples (CFG1)	Measurement time
8	1 ms
16	1.9 ms
32	3.4 ms
64	6.8 ms

To meet the response time configuration, the MTCH1010 calculates and executes the cycle time according to the oversampling selection:

Power/Sleep cycle:	4 x Measurement time + 2 x Cycle time
Free-running measurements (GFG0 = B):	5 x Measurement time

# MTCH1010

Response	Time
----------	------

Response time setting CFG0 (ms)	Cycle times executed to achieve response times (ms)						
	CFG1 X8 oversampling	CFG1 X16 oversampling	CFG1 X32 oversampling	CFG1 X64 oversampling			
Free run	(1)	(1.9)	(3.4)	(6.8)			
50	23	21	18	12			
100	48	46	43	37			
300	148	146	143	137			

Keep in mind that the CFG1 response time assumes that physical touch happens right at the beginning of sleep, from a timing perspective worst-case scenario. The table below reflects the expected minimum, average, and maximum values for response times under standard conditions.

Response	Min / AVG / Max resulting response time (ms)											
time setting		(8 overe	ampling	CFG1 X	(16		CFG1 X	(32		CFG1		
CFG0 (ms)	CFG1 X8 oversampling		oversampling		oversampling		X64 oversampling					
	Min	Avg	Max	Min	Avg	Max	Min	Avg	Max	Min	Avg	max
Free run	7		11		21		40					
50	27	39	50	29	40	50	32	41	50	39	45	50
100	52	76	100	54	77	100	57	79	100	64	82	100
300	152	226	300	154	227	300	157	229	300	164	232	300

#### Figure 7-2. Response Time



**Note:** During high noise, the response times may exceed the configured target, due to the automatic adjustment of oversampling period by frequency hopping. In the worst-case frequency selection, the maximum response time may be extended by 30%.

## 8. Power Consumption

Average power consumption in uA by Oversampling,  $V_{\text{DD}},$  Response Time.

I <sub>DD</sub> (uA) / 8x Oversampling					
Response CFG1 (ms)	V <sub>DD</sub> = 3.3V	V <sub>DD</sub> = 5V			
Free Run	1571	2410			
50	69.5	111			
100	35.6	55			
300	12.7	20.3			

I <sub>DD</sub> (uA) / 16x Oversampling					
Response CFG1 (ms)	V <sub>DD</sub> = 3.3V	V <sub>DD</sub> = 5V			
Free Run	1580	2381			
50	133	222.5			
100	63	105.5			
300	21.5	33.7			

I <sub>DD</sub> (uA) / 32x Oversampling					
Response CFG1 (ms)	V <sub>DD</sub> = 3.3V	V <sub>DD</sub> = 5V			
Free Run	1583	2417			
50	301.5	500.5			
100	124	211			
300	39.5	66.5			

I <sub>DD</sub> (uA) / 64x Oversampling					
Response CFG1 (ms)	V <sub>DD</sub> = 3.3V	V <sub>DD</sub> = 5V			
Free Run	1583.5	2446.5			
50	869	1466			
100	285	499			
300	80.5	159			

## 9. Electrical Specification

### 9.1 Disclaimer

All typical values are measured at T =  $25^{\circ}$ C and V<sub>DD</sub> = 3V, unless otherwise specified. All minimum and maximum values are valid across operating temperature and voltage unless otherwise specified.

### 9.2 Absolute Maximum Ratings

Stresses beyond those listed in this section may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

#### **Absolute Maximum Ratings**

Symbol	Description	Min	Мах	Unit
	Ambient temperature under bias	-40	+105	°C
TStorage	Storage temperature	-65	+150	°C
VPin	Pin voltage with respect to GND	-0.5	V <sub>DD</sub> + 0.5	V
IPin	I/O pin sink/source current	-40	+40	mA
	Maximum output current	-15	15	mA

### 9.3 General Operating Ratings

The device must operate within the ratings listed in this section for all other electrical characteristics and typical characteristics of the device to be valid.

#### Table 9-1. General Operating Conditions

Symbol	Description	Condition	Min.	Max.	Unit
V <sub>DD</sub>	Operating supply voltage	—	2	5.5	V
Т	Operating temperature range <sup>(1)</sup>	Standard temperature range	-40	105	°C

#### Note:

1. Refer to the device ordering codes for the device temperature range.

### 9.4 BOD and POR Characteristics

#### Table 9-2. Power Supply Characteristics

Symbol	Description	Condition	Min.	Тур.	Max.	Unit
SRON	Power-on Slope	—	—	—	100	V/ms

#### Table 9-3. Power-On Reset (POR) Characteristics

Symbol	Description	Condition	Min.	Тур.	Max.	Unit
VPOR	POR threshold voltage on V <sub>DD</sub> falling	V <sub>DD</sub> falls/rises at 0.5 V/ms or slower	0.8	—	1.6	V
	POR threshold voltage on VDD rising		1.4		1.8	

#### Table 9-4. Brown-Out Detection (BOD) Characteristics

Symbol	Description	Condition	Min.	Тур.	Max.	Unit
VBOD	BOD triggering level (falling/rising)	—	1.7	1.8	2.0	V
V <sub>HYS</sub>	Hysteresis			25	_	mV
TBOD	Detection time	Continuous	_	7	—	μs
		Sampled, 1 kHz	—	1	—	ms
		Sampled, 125 Hz	_	8	_	
T <sub>Start</sub>	Start-up time	Time from enable to ready	_	40	—	μs

## 9.5 I/O Pin Characteristics

### Table 9-5. I/O Pin Characteristics (T<sub>A</sub> = [-40, 105]°C, V<sub>DD</sub> = [2.7, 5.5]V Unless Otherwise Stated)

Symbol	Description	Condition	Min.	Тур.	Max.	Unit
VOL	I/O pin drive strength	V <sub>DD</sub> = 3.0V, I <sub>OL</sub> = 7.5 mA	—	_	0.6	V
		V <sub>DD</sub> = 5.0V, I <sub>OL</sub> = 15 mA	—	—	1	
VOH	I/O pin drive strength	V <sub>DD</sub> = 3.0V, I <sub>OH</sub> = 7.5 mA	2.4	_	_	V
		V <sub>DD</sub> = 5.0V, I <sub>OH</sub> = 15 mA	4	—	—	
V <sub>IL2</sub>	Input low-voltage on CFG1 pin as I/O	—	-0.2	_	0.3 × V <sub>DD</sub>	V
V <sub>IH2</sub>	Input high-voltage on CFG1 pin as I/O	-	0.7 × V <sub>DD</sub>	_	V <sub>DD</sub> + 0.2V	V
V <sub>OL2</sub>	I/O pin drive strength on CFG1 pin as I/O	V <sub>DD</sub> = 3.0V, I <sub>OL</sub> = 0.25 mA	—	_	0.6	V
		V <sub>DD</sub> = 5.0V, I <sub>OL</sub> = 0.5 mA	—	_	1	-
VOH2	I/O pin drive strength on CFG1 pin as I/O	V <sub>DD</sub> = 3.0V, I <sub>OH</sub> = 0.25 mA	2.4	_	_	V
		V <sub>DD</sub> = 5.0V, I <sub>OH</sub> = 0.5 mA	4	_	_	
<sup>t</sup> RISE	Rise time	V <sub>DD</sub> = 3.0V, load = 20 pF	—	2.5	_	ns
		V <sub>DD</sub> = 5.0V, load = 20 pF	—	1.5	—	
<sup>t</sup> FALL	Fall time	V <sub>DD</sub> = 3.0V, load = 20 pF	—	2.0	_	ns
		V <sub>DD</sub> = 5.0V, load = 20 pF	—	1.3	_	
C <sub>PIN</sub>	I/O pin capacitance except CH0, SHIELD, OUT0, and CFG0 pins	_	—	3	_	pF
CPIN	I/O pin capacitance on CH0, SHIELD, OUT0, and CFG0 pins	-	—	10	_	pF
Rp	Pull-up resistor	_	20	35	50	kΩ

#### Note:

1. Pin group x (Px[7:0]). The combined continuous sink/source current for all I/O ports should not exceed the limits.

## **10.** Ordering Information

Available ordering options can be found by:

- Clicking on one of the following product page links:
  - MTCH1010 Product Page
  - Searching by product name at microchipdirect.com
  - Contacting your local sales representative

### **10.1 Product Information**

Ordering Code(1)	Supply Voltage	Package Type(2)	Packing Media	Temperature Range
MTCH1010-V/SN	2V – 5.5V	SOIC150	Tube	-40°C +105°C
MTCH1010T-V/SN	2V – 5.5V	SOIC150	Tape & Reel	-40°C +105°C

#### Notes:

- 1. PB-free packaging complies to the European Directive for Restriction Hazardous Substances (RoHS directive). Also Halide free and fully Green.
- 2. Package outline drawings can be found in the Package Drawing chapter.

## 11. Package Drawing

### 11.1 8-Pin SOIC150

Figure 11-1. Package Marking Information

8-Lead SOIC 150





#### 

### 8-Lead Plastic Small Outline - Narrow, 3.90 mm (.150 In.) Body [SOIC]



Microchip Technology Drawing No. C04-057-SWB Rev E Sheet 1 of 2

### 8-Lead Plastic Small Outline – Narrow, 3.90 mm (.150 In.) Body [SOIC]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS			
Dimension L		MIN	NOM	MAX	
Number of Pins	N		8		
Pitch	е		1.27 BSC		
Overall Height	Α	-	-	1.75	
Molded Package Thickness	A2	1.25	-	-	
Standoff §	A1	0.10	-	0.25	
Overall Width	E	6.00 BSC			
Molded Package Width	E1		3.90 BSC		
Overall Length D 4.90 BS		4.90 BSC			
Chamfer (Optional)	h	0.25	-	0.50	
Foot Length	L	0.40	-	1.27	
Footprint	L1	1.04 REF			
Foot Angle	φ	0°	-	8°	
Lead Thickness	С	0.17	-	0.25	
Lead Width	b	0.31	-	0.51	
Mold Draft Angle Top	α	5°	-	15°	
Mold Draft Angle Bottom	β	5°	-	15°	

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.

2. § Significant Characteristic

- 3. Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.15mm per side.
- 4. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.

REF: Reference Dimension, usually without tolerance, for information purposes only.

5. Datums A & B to be determined at Datum H.

Microchip Technology Drawing No. C04-057-SWB Rev E Sheet 2 of 2

### 8-Lead Plastic Small Outline – Narrow, 3.90 mm (.150 In.) Body [SOIC]

**Note:** For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



### RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension	Limits	MIN	NOM	MAX
Contact Pitch	E		1.27 BSC	
Contact Pad Spacing	С		5.40	
Contact Pad Width (X8)	X1			0.60
Contact Pad Length (X8)	Y1			1.55

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing C04-2057-SWB Rev E

#### Table 11-1. Device and Package Maximum Weight

Maximum Weight

78 mg

### Table 11-2. Package Characteristics

Moisture Sensitivity Level

MSL3

## 12. Appendix

### 12.1 Static Input Voltages

These methods will configure the MTCH1010 and provide a fixed behavior at power-up and run time.

### 12.1.1 Resistor Ladder



Note: Both R1 and R2 are recommended to be greater than 100K for lower power consumption

### 12.1.2 Direct Connect to V<sub>DD</sub> or GND

Use a series resistor in case a setting is set by connecting a CFGx pin to  $V_{DD}$  or GND.



The pull-up/pull-down resistor is a precautionary recommendation, as MTCH1010 will not pull the CFGx neither to the  $V_{DD}$  nor to the GND during the operation.

### 12.2 Dynamic Input Voltages

These methods enable flexible settings during run time or development. They are controlled by the human developer or the host IC.

#### 12.2.1 Potentiometer

A useful method during development; this method is also used on the MTCH1010 DevKit.



#### 12.2.2 DAC Controlled by Host

This is advised if settings will dynamically change during run time.



### 12.2.3 PWM Controlled by Host

This is advised if settings will dynamically change during run time.



Note: Refer to Application Note 'Using PWM to Generate Analog Outpout (AN538)' for details about how to choose appropriate R and C values

## 13. Conclusion

The MTCH1010 offers the performance and robust touch experience of Microchips library-based touch solutions. The MTCH1010 is easy to use and to configure, and it is the first of a growing family of devices. Find the latest in Touch from Microchip on www.microchip.com/touch.

## 14. Revision History

Revision	Date	Description
A	04/2021	Initial document release

## The Microchip Website

Microchip provides online support via our website at www.microchip.com/. This website is used to make files and information easily available to customers. Some of the content available includes:

- **Product Support** Data sheets and errata, application notes and sample programs, design resources, user's guides and hardware support documents, latest software releases and archived software
- General Technical Support Frequently Asked Questions (FAQs), technical support requests, online discussion groups, Microchip design partner program member listing
- **Business of Microchip** Product selector and ordering guides, latest Microchip press releases, listing of seminars and events, listings of Microchip sales offices, distributors and factory representatives

## **Product Change Notification Service**

Microchip's product change notification service helps keep customers current on Microchip products. Subscribers will receive email notification whenever there are changes, updates, revisions or errata related to a specified product family or development tool of interest.

To register, go to www.microchip.com/pcn and follow the registration instructions.

## **Customer Support**

Users of Microchip products can receive assistance through several channels:

- Distributor or Representative
- Local Sales Office
- Embedded Solutions Engineer (ESE)
- Technical Support

Customers should contact their distributor, representative or ESE for support. Local sales offices are also available to help customers. A listing of sales offices and locations is included in this document.

Technical support is available through the website at: www.microchip.com/support

## **Product Identification System**

To order or obtain information, e.g., on pricing or delivery, refer to the factory or the listed sales office.

PART NO	). [X] <sup>(1)</sup>	- <u>X</u>	/ <u>XX</u>
Device	Tape and Reel	Temperature Range	Package

Device:	Device A, Feature A, (Package A) Device B, Feature B, (Package B)		
Tape & Reel Option:	Blank	= Tube	
	Т	= Tape & Reel	
Temperature Range:	I	= -40°C to +85°C (Industrial)	
	E	= -40°C to +125°C (Extended)	
Package:	AA	= Package AA	
	BB	= Package BB	

Examples:

- MCPXXXXAT-E/AA: Tape and Reel, Extended temperature, XAA package
- MCPXXXXBT-E/BB: Tape and Reel Extended temperature, XBB package

#### Notes:

- 1. Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.
- 2. Small form-factor packaging options may be available. Please check www.microchip.com/packaging for smallform factor package availability, or contact your local Sales Office.

## **Microchip Devices Code Protection Feature**

Note the following details of the code protection feature on Microchip devices:

- · Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods being used in attempts to breach the code protection features of the Microchip devices. We believe that these methods require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Attempts to breach these code protection features, most likely, cannot be accomplished without violating Microchip's intellectual property rights.
- · Microchip is willing to work with any customer who is concerned about the integrity of its code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code
  protection does not mean that we are guaranteeing the product is "unbreakable." Code protection is constantly
  evolving. We at Microchip are committed to continuously improving the code protection features of our products.
  Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act.
  If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue
  for relief under that Act.

## Legal Notice

Information contained in this publication is provided for the sole purpose of designing with and using Microchip products. Information regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL OR CONSEQUENTIAL LOSS, DAMAGE, COST OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

## Trademarks

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, chipKIT, chipKIT logo, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PackeTime, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

AgileSwitch, APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, FlashTec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, Augmented Switching, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, Espresso T1S, EtherGREEN, IdealBridge, In-Circuit Serial Programming, ICSP, INICnet, Intelligent Paralleling, Inter-Chip Connectivity, JitterBlocker, maxCrypto, maxView, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, RTAX, RTG4, SAM-ICE, Serial Quad I/O, simpleMAP, SimpliPHY, SmartBuffer, SMART-I.S., storClad, SQI, SuperSwitcher, SuperSwitcher II, Switchtec, SynchroPHY, Total Endurance, TSHARC, USBCheck, VariSense, VectorBlox, VeriPHY, ViewSpan, WiperLock, XpressConnect, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

<sup>©</sup> 2021, Microchip Technology Incorporated, Printed in the U.S.A., All Rights Reserved.

ISBN: 978-1-5224-8115-7

AMBA, Arm, Arm7, Arm7TDMI, Arm9, Arm11, Artisan, big.LITTLE, Cordio, CoreLink, CoreSight, Cortex, DesignStart, DynamIQ, Jazelle, Keil, Mali, Mbed, Mbed Enabled, NEON, POP, RealView, SecurCore, Socrates, Thumb, TrustZone, ULINK, ULINK2, ULINK-ME, ULINK-PLUS, ULINKpro, µVision, Versatile are trademarks or registered trademarks of Arm Limited (or its subsidiaries) in the US and/or elsewhere.

© 2021 Microchip Technology Inc.

## Quality Management System

For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.



# **Worldwide Sales and Service**

AMERICAS	ASIA/PACIFIC	ASIA/PACIFIC	EUROPE
Corporate Office	Australia - Sydnev	India - Bangalore	Austria - Wels
2355 West Chandler Blvd.	Tel: 61-2-9868-6733	Tel: 91-80-3090-4444	Tel: 43-7242-2244-39
Chandler, AZ 85224-6199	China - Beiiing	India - New Delhi	Fax: 43-7242-2244-393
Tel: 480-792-7200	Tel: 86-10-8569-7000	Tel: 91-11-4160-8631	Denmark - Copenhagen
Fax: 480-792-7277	China - Chengdu	India - Pune	Tel: 45-4485-5910
Technical Support:	Tel: 86-28-8665-5511	Tel: 91-20-4121-0141	Fax: 45-4485-2829
www.microchip.com/support	China - Chongging	Japan - Osaka	Finland - Espoo
Web Address:	Tel: 86-23-8980-9588	Tel: 81-6-6152-7160	Tel: 358-9-4520-820
www.microchip.com	China - Dongguan	Japan - Tokvo	France - Paris
Atlanta	Tel: 86-769-8702-9880	Tel: 81-3-6880- 3770	Tel: 33-1-69-53-63-20
Duluth. GA	China - Guangzhou	Korea - Daegu	Fax: 33-1-69-30-90-79
Tel: 678-957-9614	Tel: 86-20-8755-8029	Tel: 82-53-744-4301	Germany - Garching
Fax: 678-957-1455	China - Hangzhou	Korea - Seoul	Tel: 49-8931-9700
Austin. TX	Tel: 86-571-8792-8115	Tel: 82-2-554-7200	Germany - Haan
Tel: 512-257-3370	China - Hong Kong SAR	Malaysia - Kuala Lumpur	Tel: 49-2129-3766400
Boston	Tel: 852-2943-5100	Tel: 60-3-7651-7906	Germany - Heilbronn
Westborough MA	China - Naniing	Malaysia - Penang	Tel: 49-7131-72400
Tel: 774-760-0087	Tel: 86-25-8473-2460	Tel: 60-4-227-8870	Germany - Karlsruhe
Eax: 774-760-0088	China - Qingdao	Philippines - Manila	Tel: 49-721-625370
Chicago	Tel: 86-532-8502-7355	Tel: 63-2-634-9065	Germany - Munich
Itasca II	China - Shanghai	Singanore	Tel: 49-89-627-144-0
Tel: 630-285-0071	Tel: 86-21-3326-8000	Tel: 65-6334-8870	Fax: 49-89-627-144-44
Eax: 630-285-0075	China - Shenyang	Taiwan - Hsin Chu	Germany - Rosenheim
Dallas	Tel: 86-24-2334-2829	Tel: 886-3-577-8366	Tel: 49-8031-354-560
Addison TX	China - Shenzhen	Taiwan - Kaobsiung	Israel - Ba'anana
Tel: 072-818-7/23	Tel: 86-755-8864-2200	Tel: 886-7-213-7830	Tel: 072-0-744-7705
Fax: 072-818-2024	China - Suzhou	Taiwan - Tainei	Italy - Milan
Detroit	Tel: 86-186-6233-1526	Tel: 886-2-2508-8600	Tel: 39-0331-742611
Novi MI	China - Wuhan	Thailand - Bangkok	Fax: 39-0331-466781
Tel: 248-848-4000	Tel: 86-27-5980-5300	Tel: 66-2-604-1351	Italy - Padova
Houston TX	China - Xian	Vietnam - Ho Chi Minh	Tel: 30-040-7625286
Tel: 281-894-5983	Tel: 86-29-8833-7252	Tel: 84-28-5448-2100	Netherlands - Drupen
Indiananolis	China - Xiamen	101. 04-20-0440-2100	Tel: 31-416-690399
Noblesville IN	Tel: 86-592-2388138		Eax: 31-416-690340
Tel: 317-773-8323	China - Zhuhai		Norway - Trondheim
Eax: 317-773-5453	Tel: 86-756-3210040		Tel: 47-72884388
Tel: 317-536-2380	161. 00-730-3210040		Boland - Warsaw
			Tel: 48-22-3325737
Mission Vielo CA			Romania - Bucharest
Tal: 040 462 0523			
Eax: 040 462 0608			Spain Madrid
Tak. 949-402-9000			Tol: 34 01 708 08 00
Balaigh NC			Eax: 34 01 708 08 01
Tel: 010-844-7510			Sweden - Gothenberg
			Tel: 46-31-704-60-40
Tel: 631-435-6000			Sweden - Stockholm
San lose CA			Tel: 46-8-5000-4654
Jan JUSE, CA			181. 40-0-3090-4034
101. 400-7 30-9110 Tal: 409 426 4270			
161. 400-430-4270			101. 44-110-921-3000
			rax: 44-118-921-5820
Fax. 900-090-2010			

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Microchip:

MTCH1010T-V/SN MTCH1010-V/SN