

# VSC7432

24×1-Gigabit and 2×10/12 Gbps L2 Enterprise Ethernet Switch with High Performance Stacking and 416 MHz CPU

Microsemi's next-generation switch family delivers a comprehensive end-to-end Enterprise Ethernet solution.

The VSC7432 E-StaX-III-48 stackable Enterprise Ethernet switch contains twenty-four 10/100/1000 Mbps Ethernet ports and two 10G XAUI ports. The XAUI ports can also be configured as two 12 Gbps stacking ports.

VSC7432 provides a rich set of Enterprise Ethernet switching features. Using multistage Versatile TCAM technology (VCAP), it delivers VLAN and QoS processing, enabling the delivery of differentiated services, security through intelligent frame processing, and egress frame manipulation.

The VSC7432 device contains a powerful 416 MHz CPU, enabling full management of both a standalone switch as well as a full stackable Ethernet switch solution.


A comprehensive application programming interface (API) and software development package is available for Managed stackable Ethernet applications for faster time-to-market. The software API package integrates easily with third-party software, preserving existing software investments.

### **Highlights**

- Supports 12G stacking with less than 100 ms failover
- Management of 800 switch ports from a single IP address
- Lowest latency architecture
- New shared buffer memory architecture

#### **Applications**

- Stackable Smart switch
- Fully managed L2/L3 switch
- Fully managed Stackable switch



Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi described to grant explicitly to may patt rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information provided in this document or to any products and services at any time without notice.



# VSC7432

24×1-Gigabit and 2×10/12 Gbps L2 Enterprise Ethernet Switch with High Performance Stacking and 416 MHz CPU

#### Features

- 24×1 GbE ports with SGMII, 1000BASE-X SerDes, 100BASE-FX
- Up to 8× 2.5 GbE ports
- 2× 12 Gbps stacking ports or 2×10 GbE XAUI ports supporting four-lane XAUI or two-lane VAUI
- Internal shared memory buffer (8 queues per port)
- Jumbo frame support
- Strict priority and DWRR scheduler/shaper
- Integrated 416 MHz MIPS CPU
- 27 mm × 27 mm FCBGA

### Layer 2 Switching and Layer 3 Forwarding

- 802.1Q VLAN switch with 16K MACs and 4K VLANs
- Push, pop, and translate ingress/egress
- Policing with storm control and MC/BC protection
- RSTP and MSTP support
- Independent and shared VLAN learning (IVL, SVL)
- Hardware and software-based learning
- TCAM-based classification and VCAP-II security
- Layer 3 unicast and multicast routing

## **Multicast**

- Layer 2
- IPv4 and IPv6
- IGMP and MLD


#### Stacking

- VStaX<sup>™</sup> stacking protocol
- Hardware support for shortest path forwarding
- Fast failover within 100 ms
- 2× 12 Gbps uplink bandwidth using standard cables
- Stacking of up to 16 switches
- Stack-side congestion management

### **Related Products**

Visit www.microsemi.com for information about these related products:

- SparX-III nonstackable Gigabit Ethernet switches with integrated copper PHYs
- VSC8512 12-port copper PHY
- VSC8488 and VSC8484 dual and quad 10G optical PHYs





Microsemi Corporate Headquarters One Enterprise, Aliso Viejo, CA 92656 USA Within the USA: +1 (800) 713-4113 Outside the USA: +1 (949) 380-6100 Sales: +1 (949) 380-6136 Fax: +1 (949) 215-4996 email: sales.support@microsemi.com www.microsemi.com Microsemi Corporation (Nasdaq: MSCC) offers a comprehensive portfolio of semiconductor and system solutions for communications, defense and security, aerospace, and industrial markets. Products include high-performance and radiationhardened analog mixed-signal integrated circuits, FPGAs, SoCs, and ASICs; power management products; timing and synchronization devices and precise time solutions; voice processing devices; RF solutions; discrete components; enterprise storage and communications solutions, security technologies, and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California, and has approximately 4,800 employees worldwide. Learn more at www.microsemi.com.

©2010–2016 Microsemi Corporation. All rights reserved. Microsemi and the Microsemi logo are registered trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

 Microchip:

 VSC7432YIH
 VSC7432YIH-01