


MSC035SMA070S Silicon Carbide N-Channel Power MOSFET

1 Product Overview

The silicon carbide (SiC) power MOSFET product line from Microsemi increases the performance over silicon MOSFET and silicon IGBT solutions while lowering the total cost of ownership for high-voltage applications. The MSC035SMA070S device is a 700 V, 35 mΩ SiC MOSFET in a TO-268 (D³PAK) package.



1.1 Features

The following are key features of the MSC035SMA070S device:

- Low capacitances and low gate charge
- Fast switching speed due to low internal gate resistance (ESR)
- Stable operation at high junction temperature, $T_{J(max)} = 175\text{ }^{\circ}\text{C}$
- Fast and reliable body diode
- Superior avalanche ruggedness
- RoHS compliant

1.2 Benefits

The following are benefits of the MSC035SMA070S device:

- High efficiency to enable lighter, more compact system
- Simple to drive and easy to parallel
- Improved thermal capabilities and lower switching losses
- Eliminates the need for external freewheeling diode
- Lower system cost of ownership

1.3 Applications

The MSC035SMA070S device is designed for the following applications:

- PV inverter, converter, and industrial motor drives
- Smart grid transmission and distribution
- Induction heating and welding
- H/EV powertrain and EV charger
- Power supply and distribution

2 Device Specifications

This section shows the specifications of the MSC035SMA070S device.

2.1 Absolute Maximum Ratings

The following table shows the absolute maximum ratings of the MSC035SMA070S device.

Table 1 • Absolute Maximum Ratings

| Symbol | Characteristic | Ratings | Unit |
|----------|-----------------------------------------------------------------|-----------|-----------------------|
| V_{DS} | Drain source voltage | 700 | V |
| I_D | Continuous drain current at $T_C = 25\text{ }^{\circ}\text{C}$ | 65 | A |
| | Continuous drain current at $T_C = 100\text{ }^{\circ}\text{C}$ | 46 | |
| I_{DM} | Pulsed drain current ¹ | 163 | |
| V_{GS} | Gate-source voltage | 23 to -10 | V |
| P_D | Total power dissipation at $T_C = 25\text{ }^{\circ}\text{C}$ | 206 | W |
| | Linear derating factor | 1.37 | W/ $^{\circ}\text{C}$ |

Note:

1. Repetitive rating: pulse width and case temperature limited by maximum junction temperature.

The following table shows the thermal and mechanical characteristics of the MSC035SMA070S device.

Table 2 • Thermal and Mechanical Characteristics

| Symbol | Characteristic | Min | Typ | Max | Unit |
|-----------------|---------------------------------------------------------|-----|------|------|-----------------------------|
| $R_{\theta JC}$ | Junction-to-case thermal resistance | | 0.49 | 0.73 | $^{\circ}\text{C}/\text{W}$ |
| T_J | Operating junction temperature | -55 | | 175 | $^{\circ}\text{C}$ |
| T_{STG} | Storage temperature | -55 | | 150 | |
| T_L | Soldering temperature for 10 seconds (1.6 mm from case) | | | 260 | |
| Wt | Package weight | | 0.14 | | oz |
| | | | 4.0 | | g |

2.2 Electrical Performance

The following table shows the static characteristics for the MSC035SMA070S device. $T_J = 25^\circ\text{C}$ unless otherwise specified.

Table 3 • Static Characteristics

| Symbol | Characteristic | Test Conditions | Min | Typ | Max | Unit |
|--------------------------------|-----------------------------------------|------------------------------------------------------------------------------|-----|------|-----------|----------------------|
| $V_{(BR)DSS}$ | Drain-source breakdown voltage | $V_{GS} = 0\text{ V}$, $I_D = 100\text{ }\mu\text{A}$ | 700 | | | V |
| $R_{DS(on)}$ | Drain-source on resistance ¹ | $V_{GS} = 20\text{ V}$, $I_D = 30\text{ A}$ | | 35 | 44 | m Ω |
| $V_{GS(th)}$ | Gate-source threshold voltage | $V_{GS} = V_{DS}$, $I_D = 1\text{ mA}$ | 1.9 | 2.7 | | V |
| $\Delta V_{GS(th)}/\Delta T_J$ | Threshold voltage coefficient | $V_{GS} = V_{DS}$, $I_D = 1\text{ mA}$ | | -5.0 | | mV/ $^\circ\text{C}$ |
| I_{DSS} | Zero gate voltage drain current | $V_{DS} = 700\text{ V}$, $V_{GS} = 0\text{ V}$ | | | 100 | μA |
| | | $V_{DS} = 700\text{ V}$, $V_{GS} = 0\text{ V}$ $T_J = 125^\circ\text{C}$ | | | 500 | |
| I_{GSS} | Gate-source leakage current | $V_{GS} = 20\text{ V}/-10\text{ V}$ | | | ± 100 | nA |

Note:

1. Pulse test: pulse width < 380 μs , duty cycle < 2%.

The following table shows the dynamic characteristics of the MSC035SMA070S device. $T_J = 25^\circ\text{C}$ unless otherwise specified.

Table 4 • Dynamic Characteristics

| Symbol | Characteristic | Test Conditions | Min | Typ | Max | Unit |
|--------------|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|------|-----|---------------|
| C_{iss} | Input capacitance | $V_{GS} = 0\text{ V}$, $V_{DD} = 700\text{ V}$, $V_{AC} = 25\text{ mV}$, $f = 1\text{ MHz}$ | | 2010 | | pF |
| C_{rss} | Reverse transfer capacitance | | | 17 | | |
| C_{oss} | Output capacitance | | | 247 | | |
| Q_g | Total gate charge | $V_{GS} = -5\text{ V}/20\text{ V}$, $V_{DD} = 470\text{ V}$ $I_D = 30\text{ A}$ | | 99 | | nC |
| Q_{gs} | Gate-source charge | | | 33 | | |
| Q_{gd} | Gate-drain charge | | | 18 | | |
| $t_{d(on)}$ | Turn-on delay time | $V_{DD} = 470\text{ V}$, $V_{GS} = -5\text{ V}/20\text{ V}$, $I_D = 30\text{ A}$ $R_{G(ext)} = 2.5\text{ }\Omega$ ¹ Freewheeling diode = MSC035SMA070S ($V_{GS} = -5\text{ V}$) | | 18 | | ns |
| t_r | Current rise time | | | 6 | | |
| $t_{d(off)}$ | Turn-off delay time | | | 25 | | |
| t_f | Current fall time | | | 7 | | |
| E_{on2} | Turn-on switching energy ² | | | 230 | | μJ |
| E_{off} | Turn-off switching energy | | | 40 | | |
| $t_{d(on)}$ | Turn-on delay time | $V_{DD} = 470\text{ V}$, $V_{GS} = -5\text{ V}/20\text{ V}$, $I_D = 30\text{ A}$ $R_{G(ext)} = 2.5\text{ }\Omega$ ¹ Freewheeling diode = MSC010SDA070S | | 20 | | ns |
| t_r | Current rise time | | | 9 | | |
| $t_{d(off)}$ | Turn-off delay time | | | 25 | | |
| t_f | Current fall time | | | 10 | | |
| E_{on2} | Turn-on switching energy ² | | | 165 | | μJ |
| E_{off} | Turn-off switching energy | | | 55 | | |
| ESR | Equivalent series resistance | $f = 1\text{ MHz}$, 25 mV, drain short | | 1.13 | | Ω |

| Symbol | Characteristic | Test Conditions | Min | Typ | Max | Unit |
|----------|--------------------------------|------------------------------------------------------------------------|-----|------|-----|---------------|
| SCWT | Short circuit withstand time | $V_{DS} = 560\text{ V}$, $V_{GS} = 20\text{ V}$ | | 3 | | μs |
| E_{AS} | Avalanche energy, single pulse | $V_{DS} = 150\text{ V}$, $V_{GS} = 20\text{ V}$, $I_D = 30\text{ A}$ | | 1400 | | mJ |

Notes:

1. R_G is total gate resistance excluding internal gate driver impedance.
2. E_{on2} includes energy of freewheeling diode.

The following table shows the body diode characteristics of the MSC035SMA070S device.

Table 5 • Body Diode Characteristics

| Symbol | Characteristic | Test Conditions | Min | Typ | Max | Unit |
|-----------|--------------------------|-----------------------------------------------------------------|-----|-----|-----|------|
| V_{SD} | Diode forward voltage | $I_{SD} = 30\text{ A}$, $V_{GS} = 0\text{ V}$ | | 3.8 | | V |
| | | $I_{SD} = 30\text{ A}$, $V_{GS} = -5\text{ V}$ | | 4.0 | | V |
| t_{rr} | Reverse recovery time | $I_{SD} = 30\text{ A}$, $V_{GS} = -5\text{ V}$ | | 75 | | ns |
| Q_{rr} | Reverse recovery charge | $V_{DD} = 470\text{ V}$ $dI/dt = -1000\text{ A}/\mu\text{s}$ | | 305 | | nC |
| I_{RRM} | Reverse recovery current | | | 11 | | A |

2.3 Typical Performance Curves

This section shows the typical performance curves of the MSC035SMA070S device.

Figure 1 • Drain Current vs. Drain-to-Source Voltage




Figure 2 • Drain Current vs. Drain-to-Source Voltage




Figure 3 • Drain Current vs. Drain-to-Source Voltage




Figure 4 • Drain Current vs. Drain-to-Source Voltage




Figure 5 • RDS(on) vs. Junction Temperature




Figure 6 • Gate Charge Characteristics




Figure 7 • Capacitance vs. Drain-to-Source Voltage




Figure 8 • IDM vs. Gate-to-Source Voltage




Figure 9 • IDM vs. VDS Third Quadrant Conduction




Figure 10 • IDM vs. VDS Third Quadrant Conduction




Figure 11 • VGS(th) vs. Junction Temperature




Figure 12 • Forward Safe Operating Area





Figure 13 • Maximum Transient Thermal Impedance




3 Package Specification

This section shows the package specification of the MSC035SMA070S device.

3.1 Package Outline Drawing

The following figure illustrates the TO-268 package outline of the MSC035SMA070S device.

Figure 14 • Package Outline Drawing



The following table lists the TO-268 dimensions and should be used in conjunction with the package outline drawing.

Table 6 • TO-268 Dimensions

| Symbol | Min (mm) | Max (mm) | Min (in.) | Max (in.) |
|------------|-----------------|----------|------------------|-----------|
| A | 4.90 | 5.10 | 0.193 | 0.201 |
| B | 15.85 | 16.20 | 0.624 | 0.638 |
| C | 18.70 | 19.10 | 0.736 | 0.752 |
| D | 1.00 | 1.25 | 0.039 | 0.049 |
| E | 13.80 | 14.00 | 0.543 | 0.551 |
| F | 13.30 | 13.60 | 0.524 | 0.535 |
| G | 2.70 | 2.90 | 0.106 | 0.114 |
| H | 1.15 | 1.45 | 0.045 | 0.057 |
| I | 1.95 | 2.21 | 0.077 | 0.087 |
| J | 0.94 | 1.40 | 0.037 | 0.055 |
| K | 2.40 | 2.70 | 0.094 | 0.106 |
| L | 0.40 | 0.60 | 0.016 | 0.024 |
| M | 1.45 | 1.60 | 0.057 | 0.063 |
| N | 0.00 | 0.18 | 0.000 | 0.007 |
| O | 12.40 | 12.70 | 0.488 | 0.500 |
| P | 5.45 BSC (nom.) | | 0.215 BSC (nom.) | |
| Terminal 1 | Gate | | | |
| Terminal 2 | Drain | | | |
| Terminal 3 | Source | | | |
| Terminal 4 | Drain | | | |

**Microsemi Headquarters**

One Enterprise, Aliso Viejo,
CA 92656 USA

Within the USA: +1 (800) 713-4113

Outside the USA: +1 (949) 380-6100

Sales: +1 (949) 380-6136

Fax: +1 (949) 215-4996

Email: sales.support@microsemi.com

www.microsemi.com

© 2020 Microsemi. All rights reserved. Microsemi and the Microsemi logo are trademarks of Microsemi Corporation. All other trademarks and service marks are the property of their respective owners.

Microsemi makes no warranty, representation, or guarantee regarding the information contained herein or the suitability of its products and services for any particular purpose, nor does Microsemi assume any liability whatsoever arising out of the application or use of any product or circuit. The products sold hereunder and any other products sold by Microsemi have been subject to limited testing and should not be used in conjunction with mission-critical equipment or applications. Any performance specifications are believed to be reliable but are not verified, and Buyer must conduct and complete all performance and other testing of the products, alone and together with, or installed in, any end-products. Buyer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the Buyer's responsibility to independently determine suitability of any products and to test and verify the same. The information provided by Microsemi hereunder is provided "as is, where is" and with all faults, and the entire risk associated with such information is entirely with the Buyer. Microsemi does not grant, explicitly or implicitly, to any party any patent rights, licenses, or any other IP rights, whether with regard to such information itself or anything described by such information. Information provided in this document is proprietary to Microsemi, and Microsemi reserves the right to make any changes to the information in this document or to any products and services at any time without notice.

Microsemi, a wholly owned subsidiary of Microchip Technology Inc. (Nasdaq: MCHP), offers a comprehensive portfolio of semiconductor and system solutions for aerospace & defense, communications, data center and industrial markets. Products include high-performance and radiation-hardened analog mixed-signal integrated circuits, FPGAs, SoCs and ASICs; power management products; timing and synchronization devices and precise time solutions; setting the world's standard for time; voice processing devices; RF solutions; discrete components; enterprise storage and communication solutions; security technologies and scalable anti-tamper products; Ethernet solutions; Power-over-Ethernet ICs and midspans; as well as custom design capabilities and services. Microsemi is headquartered in Aliso Viejo, California, and has approximately 4,800 employees globally. Learn more at www.microsemi.com.

050-7749 | November 2020 | Released

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Microchip:](#)

[MSC035SMA070S](#)