

MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

EEPROM 6 Click





PID: MIKROE-4296

EEPROM 6 Click is a compact add-on board that contains a serial EEPROM memory that operates from the 1-Wire interface. This board features the <u>DS28EC20</u>, a 20480-bit EEPROM organized as 80 memory pages of 256 bits each from <u>Analog Devices</u>. As a specific feature, blocks of eight memory pages can be write-protected or put in "EPROM-Emulation" Mode, where bits can only be changed from a 1 to a 0 state. It communicates with MCU at 15.4kbps or 90kbps over the 1-Wire protocol and has a 64-bit registration number that ensures error-free device selection. This Click board[™] is suitable for applications like device authentication, data for self-configuration of central office switches, wireless base stations, or other modular-based rack systems.

EEPROM 6 Click is supported by a <u>mikroSDK</u> compliant library, which includes functions that simplify software development. This <u>Click board</u> comes as a fully tested product, ready to be used on a system equipped with the <u>mikroBUS</u> socket.

How does it work?

EEPROM 6 Click is based on the DS28EC20, a 20Kb of data EEPROM with a fully featured 1-Wire interface in a single chip from Analog Devices. The memory is organized as 80 pages of 256 bits each. In addition, the device has one page for control functions such as permanent write protection and EPROM-Emulation mode for individual 2048-bit (8-page) memory blocks. A volatile 256-bit memory page called the scratchpad acts as a buffer when writing data to the EEPROM to ensure data integrity. Data is first written to the scratchpad, from which it can be read back for verification before transferring it to the EEPROM.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.





MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com



Each DS28EC20 has its own unalterable and unique 64-bit registration number. The registration number guarantees unique identification and is used to address the device in a multidrop 1-Wire net environment. In addition to the EEPROM, the device has a 32-byte volatile scratchpad. Writes to the EEPROM array are a two-step process. First, data is written to the scratchpad and then copied into the main array. The user can verify the data in the scratchpad before copying.

The protocol for accessing the DS28EC20 through the 1-Wire interface consists of additional steps:

- **Initialization sequence** It consists of a reset pulse transmitted by the MCU followed by the presence pulse transmitted by the DS28EC20, which gives the MCU information that the DS28EC20 is on the bus and is ready to operate.
- **ROM Function Command** Once the MCU has detected a presence, it can issue one of the seven ROM function commands that the DS28EC20 support.
- **Memory Function Command** Commands necessary for accessing the memory of the DS28EC20.
- **Transaction/Data** The idle state for the 1-Wire bus is high. If for any reason a transaction needs to be suspended, the bus MUST be left in the idle state if the transaction is to resume. If this does not occur and the bus is left low for more than 16 μ s (Overdrive speed) or more than 120 μ s (Standard speed), one or more devices on the bus can be reset.

The EEPROM 6 Click communicates with MCU using the 1-Wire interface that supports both a Standard and Overdrive communication speed of 15.4kbps (max) and 90kbps (max), respectively. If not explicitly set into the Overdrive mode, the DS28EC20 communicates at Standard speed. The 1-Wire communication line is routed to the SMD jumper labeled as GP SEL, which allows routing of the 1-Wire communication either to the PWM pin or to the AN pin of the mikroBUS[™] socket. These pins are labeled as GP0 and GP1 respectively, the same as the SMD jumper positions, making the selection of the desired pin simple and straightforward.

This Click board[™] is designed to be operated with both 3.3V and 5V logic voltage levels that can be selected via VCC SEL jumper. This allows for both 3.3V and 5V capable MCUs to use the 1-Wire communication lines properly. However, the Click board[™] comes equipped with a library that contains easy to use functions and an example code that can be used as a reference for further development.

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.





Specifications

| Туре | EEPROM |
|------------------|---|
| Applications | Can be used for applications like device authentication, analog-sensor calibration, ink and toner printer cartridge identification, data for self-configuration of central office switches, wireless base stations, or other modular-based rack systems. |
| On-board modules | EEPROM 6 Click is based on the DS28EC20, a 20Kb of data EEPROM with a fully featured 1-Wire interface in a single chip from Maxim Integrated. |
| Key Features | Unique registration number that ensures error- free device selection, switchpoint hysteresis and filtering to optimize performance in the presence of noise, 200k write/erase cycle endurance, and more. |
| Interface | 1-Wire |
| Feature | No ClickID |
| Compatibility | mikroBUS™ |
| Click board size | S (28.6 x 25.4 mm) |
| Input Voltage | 3.3V or 5V |

Pinout diagram

This table shows how the pinout on EEPROM 6 Click corresponds to the pinout on the mikroBUS^m socket (the latter shown in the two middle columns).

| Notes | Pin | ● ● mikro* ● ● ● BUS | | | TM- | Pin | Notes | |
|--------------------|------|-------------------------|------|-----|-----|-----|--------------------|--|
| 1-Wire Data IN/OUT | GP1 | 1 | AN | PWM | 16 | GP0 | 1-Wire Data IN/OUT | |
| | NC | 2 | RST | INT | 15 | NC | | |
| | NC | 3 | CS | RX | 14 | NC | | |
| | NC | 4 | SCK | TX | 13 | NC | | |
| | NC | 5 | MISO | SCL | 12 | NC | | |
| | NC | 6 | MOSI | SDA | 11 | NC | | |
| Power Supply | 3.3V | 7 | 3.3V | 5V | 10 | 5V | Power Supply | |
| Ground | GND | 8 | GND | GND | 9 | GND | Ground | |

Onboard settings and indicators

| Label | Name | Default | Description |
|-------|---------|---------|---|
| LD1 | PWR | - | Power LED Indicator |
| JP1 | VCC SEL | Right | Power Supply Voltage Selection 3V3/5V: Left position 3V3, Right |

Mikroe produces entire development rooknains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.





MIKROELEKTRONIKA D.O.O, Batajnički drum 23, 11000 Belgrade, Serbia VAT: SR105917343 Registration No. 20490918 Phone: + 381 11 78 57 600 Fax: + 381 11 63 09 644 E-mail: office@mikroe.com www.mikroe.com

| | | | position 5V |
|-----|--------|-------|--------------------------|
| JP2 | GP SEL | Right | 1-Wire Data |
| | | | Communication Pin |
| | | | Selection: Left position |
| | | | GP1, Right position |
| | | | GP0 |

EEPROM 6 Click electrical specifications

| Description | Min | Тур | Max | Unit |
|--------------------------------|------|-----|-----|-------|
| Supply Voltage | -0.5 | - | 6 | V |
| Memory Size | - | - | 20 | Kb |
| Write/Erase Cycles (Endurance) | 200k | - | - | cycle |
| Operating Temperature Range | -40 | - | +85 | °C |

Software Support

We provide a library for the EEPROM 6 Click on our <u>LibStock</u> page, as well as a demo application (example), developed using MikroElektronika <u>compilers</u>. The demo can run on all the main MikroElektronika <u>development boards</u>.

Library Description

The EEPROM 6 Click utilises the "One_Wire" Library for it's communications and functionalities.

Key functions:

- void eeprom6_one_wire_init () Function initialises one wire communication.
- void eeprom6_read_mem (uint16_t reg_adr, uint16_t n_len) The Read Memory function allows data to be sequentially read starting at an initial address.
- uint8_t eeprom6_write_mem (uint16_t reg_adr, uint16_t n_len) The Write Memory function allows data bytes to be written sequentially.

Examples description

The application is composed of three sections :

- System Initialization Initializes LOG structure.
- Application Initialization Initalizes the device, performs safety check, and start to write log.
- Application Task This example shows capabilities of EEPROM 6 Click board by writting "MikroE" into first 6 memory locations, and then reading it back.

The full application code, and ready to use projects can be found on our LibStock page.

Other mikroE Libraries used in the example:

- void eeprom6_one_wire_init () Function initialises one wire communication , returns Family Code.
- void eeprom6_rom_skip () Function sends skip ROM command.
- void eeprom6_read_mem (uint16_t reg_adr, uint16_t n_len) The Read Memory function allows data to be sequentially read starting at an initial address.
- uint8_t eeprom6_write_mem (uint16_t reg_adr, uint16_t n_len) The Write Memory Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.





function allows data bytes to be written sequentially, returns 1 if error has occured.

The full application code, and ready to use projects can be found on our <u>LibStock</u> page.

Other mikroE Libraries used in the example:

- One Wire
- UART

Additional notes and informations

Depending on the development board you are using, you may need <u>USB UART click</u>, <u>USB UART</u> <u>2 click</u> or <u>RS232 click</u> to connect to your PC, for development systems with no UART to USB interface available on the board. The terminal available in all MikroElektronika <u>compilers</u>, or any other terminal application of your choice, can be used to read the message.

mikroSDK

This Click board^m is supported with <u>mikroSDK</u> - MikroElektronika Software Development Kit. To ensure proper operation of mikroSDK compliant Click board^m demo applications, mikroSDK should be downloaded from the <u>LibStock</u> and installed for the compiler you are using.

For more information about mikroSDK, visit the official page.

Resources

<u>mikroBUS</u>™

<u>mikroSDK</u>

Click board[™] Catalog

Click boards[™]

Downloads

EEPROM 6 click example on Libstock

EEPROM 6 click 2D and 3D files

DS28EC20 datasheet

EEPROM 6 click schematic

Mikroe produces entire development toolchains for all major microcontroller architectures.

Committed to excellency, we are dedicated to helping engineers bring the project development up to speed and achieve outstanding results.



ISO 27001: 2013 certification of informational security management system. ISO 14001: 2015 certification of environmental management system. OHSAS 18001: 2008 certification of occupational health and safety management system.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mikroe:

MIKROE-4296