

# RVT50AQFFWN00

# LCD TFT Datasheet

Rev.1.4

2016-10-17

ITEM	CONTENTS	UNIT
LCD Type	TFT/Transmissive/Normally white	/
Size	5.0	Inch
Viewing Direction	12:00 (without image inversion)	O' Clock
Gray Scale Inversion Direction	6:00	O' Clock
LCM (W $\times$ H $\times$ D)	121.50 x 76.60 x 7.60	mm³
Active Area (W × H)	108.00 × 64.80	mm <sup>2</sup>
Dot Pitch (W × H)	0.045×0.135	mm <sup>2</sup>
Number of Dots	800 x (RGB) × 480	/
Driver IC	FT812	/
Backlight Type	12 LEDs	/
Surface Luminance	600	cd/m <sup>2</sup>
Interface Type	SPI/QSPI	/
Color Depth	16.7M	/
Pixel Arrangement	RGB Vertical Stripe	/
Surface Treatment	Anti-glare	/
Input Voltage	3.3	V
With/Without TSP	Without TP	/
Weight	TBD	g

Note 1: RoHS compliant

**Note 2:** LCM weight tolerance: ± 5%.



## **REVISION RECORD**

<b>REVNO.</b>	REVDATE	CONTENTS	REMARKS
1.0	2015-10-06	Initial Release	
1.1	2015-11-30	Updating drawing about ZIF connector	
1.2	2016-02-15	Update LED Backlight Current and Input Voltage for LED Inverter, LCD Timing Characteristics information	
1.3	2016-06-06	Update Interface description (pin 4 and pin 5)	
1.4	2016-10-17	Added Inspection Standards	

## CONTENTS

REV	/ISIO	IN RECORD
COI	NTE	NTS
1	M	ODULE CLASSIFICATION INFORMATION
2	M	DDULE DRAWING
3	AB	SOLUTE MAXIMUM RATINGS
4	ELE	ECTRICAL CHARACTERISTICS
5	BA	CKLIGHT CHARACTERISTICS
6	ELI	ECTRO-OPTICAL CHARACTERISTICS
7	IN	TERFACE DESCRIPTION
8	FT	812 CONTROLLER SPECIFICATIONS
8	8.1	Serial host interface
8	3.2	Block Diagram
8	3.3	Host interface SPI mode 0
8	3.4	Backlight driver block diagram
9	LCI	D TIMING CHARACTERISTICS
9	9.1	Clock and data input time diagram10
9	).2	Parallel RGB timing table
10		INSPECTION
1	.0.1	Inspection condition
1	.0.2	Inspection standard
11		RELIABILITY TEST 15
12	I	LEGAL INFORMATION




## 1 MODULE CLASSIFICATION INFORMATION

RV	Т	50	A	۵	F	F	W	Ν	00
1.	2.	3.	4.	5.	6.	7.	8.	9.	10.

1.	BRAND	<b>RV</b> – Riverdi
2.	PRODUCT TYPE	T – TFT Standard
<u> </u>		<b>F</b> – TFT Custom
		<b>35</b> – 3.5″
3.	DISPLAY SIZE	<b>43 –</b> 4.3″
5.		50 – 5.0"
		<b>70</b> – 7.0"
4.	MODEL SERIAL NO.	A (A-Z)
5.	RESOLUTION	Q– 800x480 px
		<b>T</b> – TFT LCD, RGB
6	INTERFACE	L – TFT LCD, LVDS
6.		<b>S</b> – TFT + Controller SSD1963
		F – TFT + Controller FT812
-	FRAME	<b>N</b> – No Frame
7.	TRAME	F – Mounting Frame
8.	BACKLIGHT TYPE	W – LED White
		N – No Touch Panel
9.	TOUCH PANEL	<b>R</b> – Resistive Touch Panel
		<b>C</b> – Capacitive Touch Panel
10.	VERSION	<b>00</b> (00-99)

#### LCD TFT Datasheet Rev.1.4 RVT50AQFFWN00





## RVT50AOFFWN00



## 3 ABSOLUTE MAXIMUM RATINGS

PARAMETER	SYMBOL	MIN	MAX	UNIT
Supply Voltage for Logic	VDD	-0,3	4.0	V
Input Voltage for Logic	VIN	VSS-0.5	VDD+0.3	V
LED forward current (each LED)	IF	-	60	mA
Operating Temperature	Тор	-20	70	°C
Storage Temperature	Tst	-30	80	°C
Humidity	RH	-	90% (Max 60°C)	RH

## 4 ELECTRICAL CHARACTERISTICS

PARAMETER	SYMBOL	MIN	ΤΥΡ	MAX	UNIT	NOTES
Supply Voltage For Module	VDD	3.0	3.3	3.6	V	
Input Voltage for LED Inverter	BLVDD	2.8	3.3	5.5	V	
LED Backlight Current	$IDD_{backlight}$	-	290	363	mA	BLVDD=3.3V
LED Backlight Current	$IDD_{backlight}$	-	180	225	mA	BLVDD=5V
Input Leakage Current	Ilkg	-	-	-	μΑ	
Input Voltage ' H ' level	VIH	0.8VDD	-	VDD	V	
Input Voltage ' L ' level	VIL	-0.3	-	0.2VDD	V	

**Note:** The LED life time is defined as the module brightness decrease to 50% original brightness at Ta=25°C.

## 5 BACKLIGHT CHARACTERISTICS

ITEM	SYMBOL	MIN	ΤΥΡ	MAX	UNIT
Voltage for LED backlight	VI	17.4	18.3	19.6	V
Current for LED backlight	lı lı	30	40	50	mA
LED Life Time	-	30000	50000	-	Hrs

**Note:** The LED Supply Voltage is defined by the numbers of LED at Ta=25°C and  $I_L$ = 40mA.

## 6 ELECTRO-OPTICAL CHARACTERISTICS

ITEM		SYMBOL	CONDITION	MIN	ΤΥΡ	MAX	UNIT	REMARK	NOTE
Response Tim	e	Tr+Tf		-	20	-	ms	Figure 1	4
Contrast Ratio	)	Cr	θ=0°	-	500	-		Figure 2	1
Luminance Un	iformity	δ WHITE	Ø=0° Ta=25	75	80	-	%	Figure 2	3
Surface Lumin	ance	Lv		550	600	-	cd/m <sup>2</sup>	Figure 2	2
			Ø = 90°	40	50	-	deg	Figure 3	
		0	Ø = 270°	60	70	-	deg	Figure 3	
Viewing Angle	Pango	θ	Ø = 0°	60	70	-	deg	Figure 3	6
	Nange		Ø = 180°	60	70	-	deg	Figure 3	0
	Red	х		0.540	0.590	0.640			
	Reu	У		0.300	0.350	0.400			
	Green	х	θ=0°	0.298	0.348	0.398			
	Green	У	Ø=0°	0.520	0.570	0.620		igure 2	
CIE (x, y)	Blue	х	φ=0 Ta=25	0.095	0.145	0.195	I	igule 2	
Chromaticity	ыце	У	18-25	0.060	0.110	0.160			5
,	White	х		0.270	0.320	0.370	1		
	white	У		0.310	0.360	0.410			



**Note 1.** Contrast Ratio(CR) is defined mathematically as below, for more information see Figure 1.

$$Contrast Ratio = \frac{Average Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}{Average Surface Luminance with all black pixels (P1, P2, P3, P4, P5)}$$

**Note 2.** Surface luminance is the LCD surface from the surface with all pixels displaying white. For more information, see Figure 2.

Lv = Average Surface Luminance with all white pixels (P1, P2, P3, P4, P5)

**Note 3.** The uniformity in surface luminance  $\delta$  WHITE is determined by measuring luminance at each test position 1 through 5, and then dividing the maximum luminance of 5 points luminance by minimum luminance of 5 points luminance. For more information, see Figure 2.

$$\delta \text{ WHITE } = \frac{\text{Minimum Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}}{\text{Maximum Surface Luminance with all white pixels (P1, P2, P3, P4, P5)}}$$


**Note 4.** Response time is the time required for the display to transition from white to black (Rise Time, Tr) and from black to white (Decay Time, Tf). For additional information see FIG 1. The test equipment is Autronic-Melchers's ConoScope series.

**Note 5.** CIE (x, y) chromaticity, the x, y value is determined by measuring luminance at each test position 1 through 5, and then make average value.

**Note 6.** Viewing angle is the angle at which the contrast ratio is greater than 2. For TFT module the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see Figure 3.

**Note 7.** For viewing angle and response time testing, the testing data is based on Autronic-Melchers's ConoScope series. Instruments for Contrast Ratio, Surface Luminance, Luminance Uniformity, CIE the test data is based on TOPCON's BM-5 photo detector.

**Note 8.** For TFT module, Gray scale reverse occurs in the direction of panel viewing angle.





## LCD TFT Datasheet Rev.1.4 RVT50AOFFWN00




-► A

P2

P3/


Figure 2. Measuring method for Contrast ratio, surface luminance, Luminance uniformity, CIE (x, y) chromaticity





\*

P4



#### 7 INTERFACE DESCRIPTION

PIN NO.	SYMBOL	DESCRIPTION
1	VDD	Power Supply
2	GND	Ground
3	SPI_SCLK	SPI SCK Signal, Internally 47k Pull UP
4	MISO/ 101	SPI MISO Signal / SPI Quad mode: SPI data line 1
5	MOSI/ 100	SPI MOSI Signal / SPI Quad mode: SPI data line 0
6	CS	SPI Chip Select Signal, Internally 47k Pull UP
7	INT	Interrupt Signal, Active Low, Internally 47k Pull UP
8	PD	Power Down Signal, Active Low, Internally 47k Pull UP
9	NC	Not Connected
10	AUDIO_OUT	Audio Out Signal
11	GPI00/I02	SPI Single mode: General purpose IOO/ SPI Quad mode: SPI data line 2
12	GPIO1/IO3	SPI Single mode: General purpose IO1/ SPI Quad mode: SPI data line 3
13	GPIO2	General purpose IO2
14	GPIO3	General purpose IO3 or analog input for ADC
15	NC	Not Connected
16	NC	Not Connected
17	BLVDD	Backlight Power Supply, Can Be Connected to VDD
18	BLVDD	Backlight Power Supply, Can Be Connected to VDD
19	BLGND	Backlight Ground, Internally connected to GND
20	BLGND	Backlight Ground, Internally connected to GND



#### 8 FT812 CONTROLLER SPECIFICATIONS

FT812 or EVE (Embedded Video Engine) simplifies the system architecture for advanced human machine interfaces (HMIs) by providing functionality for display, audio, and touch as well as an object oriented architecture approach that extends from display creation to the rendering of the graphics.

#### 8.1 Serial host interface





Figure 4.SPI interface connection



SPI Interface – the SPI slave interface operates up to 30MHz.

Only SPI mode 0 is supported. The SPI interface is selected by default (MODE pin is internally pulled low by 47k resistor).

**QSPI Interface** – the QSPI slave interface operates up to 30MHz. Only SPI mode 0 is supported. The QSPI can be configured as a SPI slave in SINGLE, DUAL or QUAD data bus modes.


By default the SPI slave operates in the SINGLE channel mode with MOSI as input from the master and MISO as output to the master. DUAL and QUAD channel modes can be configured through the SPI slave itself. To change the channel modes, write to register REG\_SPI\_WIDTH.

# LCD TFT Datasheet Rev.1.4


## RVT50AOFFWN00



#### 8.2 Block Diagram



#### 8.3 Host interface SPI mode 0




For more information about FT812 controller please go to official FT81x website.

http://www.ftdichip.com/Products/ICs/FT81X.html

#### 8.4 Backlight driver block diagram

Backlight enable signal is internally connected to FT812 Backlight control pin. This pin is controlled by two FT812's registers. One of them specifies the PWM output frequency, second one specifies the duty cycle. Refer to FT812 datasheet for more information.





#### RVT50AOFFWN00



#### 9 LCD TIMING CHARACTERISTICS

#### 9.1 Clock and data input time diagram





Figure 10. Vertical input timing diagram



#### 9.2 Parallel RGB timing table

PARAMETER	SYMBOL	MIN	ΤΥΡ	MAX	UNIT
Horizontal Display Area	Thd	-	800	-	DCLK
DCLK Frequency	Fclk	-	30	50	MHz
One Horizontal Line	Th	889	928	1143	DCLK
HS pulse width	Thpw	1	48	255	DCLK
HS Blanking	Thb	-	88	-	DCLK
HS Front Porch	Thfp	1	40	255	DCLK
Vertical Display Area	Tvd	-	480	-	TH
VS period time	Tv	513	525	767	TH
VS pulse width	Tvpw	3	3	255	TH
VS Blanking	Tvb	-	32	-	TH
VS Front Porch	Tvfp	1	13	255	TH



#### **10 INSPECTION**

Standard acceptance/rejection criteria for TFT module.

#### 10.1 Inspection condition

#### Ambient conditions:


- Temperature: 25±°C
- Humidity: (60±10) %RH
- Illumination: Single fluorescent lamp non-directive (300 to 700 lux)

#### Viewing distance:

35±5cm between inspector bare eye and LCD.

#### Viewing Angle:

U/D: 45°/45°, L/R 45°/45°



#### 10.2

ltem	Criterion			
Black spots, white spots, light leakage, Foreign Particle	x	_	c:	
(round Type)		Average	Size < 5"	Qualified Oty
() )		D < 0.2		Qualified Qty Ignored
	×			3
				2
		0.5 mm		0
	(x+y)		Size >= 5"	
	$D = \frac{(x+y)}{2}$	Average		Qualified Qty
	-	D<0.2 n	nm	Ignored
	*Spots density: 10 mm	0.2 mm		4
				2
		0.5 mm	< D	0
spots, light leakage	Width	_	Size < 5"	
spots, light leakage	Width	Length	Size < 5″ Width	Qualified Qty
spots, light leakage	Width	Length -		
spots, light leakage	Width	Length - L < 3.0	Width	Qty Ignored
spots, light leakage	Width	-	Width W< 0.02 0.02 < W <0.0 0.05 < W <0.0	Qty Ignored 25 2 28 -
spots, light leakage		- L < 3.0	Width W< 0.02 0.02 < W <0.0	Qty Ignored 25 2
LCD black spots, white spots, light leakage (line Type)	Width	- L < 3.0	Width W< 0.02 0.02 < W <0.0 0.05 < W <0.0 0.08 < W	Qty Ignored 25 2 28 -
spots, light leakage		- L < 3.0	Width W< 0.02 0.02 < W <0.0 0.05 < W <0.0	Qty Ignored 25 2 28 -
spots, light leakage		- L < 3.0 L < 2.5 -	Width W< 0.02 0.02 < W <0.0 0.05 < W <0.0 0.08 < W Size >= 5"	Qty Ignored 2 2 0 0 0
pots, light leakage		- L < 3.0 L < 2.5 -	Width         W< 0.02	Qty Ignored 2 2 3 3 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
spots, light leakage		- L < 3.0 L < 2.5 - Length	Width         W< 0.02	Qty Ignored 2 2 3 3 4 4 3 4 3 3 4 3 3 3 3 3 3 3 3 3



# LCD TFT Datasheet Rev.1.4

## RVT50AOFFWN00



Item	Criterion			
Clear spots	Size < 5"			
	Average Diameter		Qualified Qty	
	D < 0.2 mm		Ignored	
	0.2 mm < D < 0.3 mm		3	
	0.3 mm < D < 0.5 mm		2	
	0.5 mm < D		0	
			I	
		Size >= 5"		
	Average Diameter		Qualified Qty	
	D<0.2 mm		Ignored	
	0.2 mm < D < 0.3 mm		4	
	0.3 mm < D < 0.5 mm		2	
	0.5 mm < D		0	
Polarizer bubbles	*Spots density: 10 mm			
Polarizer bubbles		Size < 5"		
	Average Diameter	5126 < 5	Qualified Qty	
	D < 0.2  mm		Ignored	
	0.2 mm < D < 0.5 mm		3	
	0.5 mm < D < 1 mm		2	
	1 mm < D		0	
	Total Q'ty		3	
		Size >= 5"		
	Average Diameter		Qualified Qty	
	D<0.25 mm		Ignored	
	0.25 mm < D < 0.5 mm		3	
	0.5 mm < D		0	
Electrical Dot				
Defect	item	Size < 5"	Qualified Oty	
	Black do defect		Qualified Qty 4	
			2	
	Bright dot defect Total Dot		5	
			5	
		Size >= 5"		
	item		Qualified Qty	
	Black do defect		5	
	Bright dot defect		2	
	Total Dot		5	

## LCD TFT Datasheet Rev.1.4

#### RVT50AOFFWN00



Item	Criterion			
Touch panel spot				
	Size < 5″			
	Average Diam	Average Diameter		
	D < 0.2 mm	D < 0.2 mm		
	0.2 mm < D < 0.4 mm		5	
	0.4 mm < D <	0.5 mm	2	
	0.5 mm < D		0	
		Size >= 5"		
	Average Diam	Average Diameter		
	D<0.25 mm			
	0.25 mm < D	< 0.5 mm	4	
	0.5 mm < D		0	
	0.5 mm < D		0	
Touch panel White	0.5 mm < D		0	
Touch panel White Line Scratch	0.5 mm < D	Size < 5"	0	
•	0.5 mm < D	Size < 5" Width	0 Qualified Qty	
•				
•		Width	Qualified Qty	
•	Length -	Width W< 0.02	Qualified Qty Ignored	
•	Length - L < 3.0	Width W< 0.02 0.02 < W <0.05	Qualified Qty Ignored	
•	Length - L < 3.0	Width           W< 0.02	Qualified Qty Ignored 2	
•	Length - L < 3.0	Width           W< 0.02	Qualified Qty Ignored 2	
•	Length - L < 3.0	Width           W< 0.02	Qualified Qty Ignored 2	
•	Length - L < 3.0 L < 2.5 -	Width         W< 0.02	Qualified Qty Ignored 2 0	
•	Length - L < 3.0 L < 2.5 -	Width           W< 0.02	Qualified Qty Ignored 2 0 0 Qualified Qty	



## **11 RELIABILITY TEST**

NO.	TEST ITEM	TEST CONDITION
1	High Temperature Storage	80±2°C/240hours
2	Low Temperature Storage	-30±2°C/240hours
3	High Temperature Operating	70±2°C/240hours
4	Low Temperature Operating	-20±2°C/240hours
5	Temperature Cycle	-30±2°C~25~80±2°C × 20 cycles (30min.) (5min.) (30min.)
6	Damp Proof Test	60°C ±5°C × 90%RH/240hours
7	Vibration Test	Frequency 10Hz~55Hz Amplitude of vibration : 1.5mm Sweep: 10Hz~55Hz~10Hz X, Y, Z 2 hours for each direction.
8	Package Drop Test	Height:60 cm 1 corner, 3 edges, 6 surfaces
9	ESD Test	Air: ±4KV 150pF/330Ω 5 times Contact: ±2KV 150pF/330Ω 5 time



## 12 LEGAL INFORMATION

Riverdi makes no warranty, either expressed or implied with respect to any product, and specifically disclaims all other warranties, including, without limitation, warranties for merchantability, non-infringement and fitness for any particular purpose. Information about device are the property of Riverdi and may be the subject of patents pending or granted. It is not allowed to copy or disclosed this document without prior written permission.

Riverdi endeavors to ensure that the all contained information in this document are correct but does not accept liability for any error or omission. Riverdi products are in developing process and published information may be not up to date. Riverdi reserves the right to update and makes changes to Specifications or written material without prior notice at any time. It is important to check the current position with Riverdi.

Images and graphics used in this document are only for illustrative the purpose. All images and graphics are possible to be displayed on the range products of Riverdi, however the quality may vary. Riverdi is no liable to the buyer or to any third part for any indirect, incidental, special, consequential, punitive or exemplary damages (including without limitation lost profits, lost savings, or loss of business opportunity) relating to any product, service provided or to be provided by Riverdi, or the use or inability to use the same, even if Riverdi has been advised of the possibility of such damages.

Riverdi products are not fault tolerant nor designed, manufactured or intended for use or resale as on line control equipment in hazardous environments requiring fail – safe performance, such as in the operation of nuclear facilities, aircraft navigation or communication systems, air traffic control, direct life support machines or weapons systems in which the failure of the product could lead directly to death, personal injury or severe physical or environmental damage ('High Risk Activities'). Riverdi and its suppliers specifically disclaim any expressed or implied warranty of fitness for High Risk Activities. Using Riverdi products and devices in 'High Risk Activities' and in any other application is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Riverdi from any and all damages, claims or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Riverdi intellectual property rights.



# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Mikroe: MIKROE-2169